Journal of Advances in Statistical Learning and Data Analysis

Volume 1 Issue 1 Summer- Autumn 2026

1- Benchmarking Recurrent Neural Network Architectures for Sequential Prediction with Application to Air Pollution Forecasting
Abbas Pak, Mohammad Javad Nematollahi

2- A Generalized FGM Copula with Enhanced Negative Dependence for Hydrological Applications
Hakim Bekrizadeh

3- Extended Optimizers in Variational Autoencoders Using Shrinkage Estimation
Heydar Mokhtari Farivar, Parviz Nasiri

4- Topp-Leone Distribution: A Reliability Analysis Perspective
Alireza Pakgohar, Soheil Shokri

5- Sensitivity Analysis of Diagnostic Measures to the Liu Biasing Parameter and Error Distribution in Linear Mixed Measurement Error Models
Fatemeh Ghapani1, Razieh Jafaraghaie

6- Enhancing the Stability of Noise Removal in Color Images Using Eigenvector Analysis and Weighted Bootstrap Mean
Reza Ghasemi

Online ISSN: 3150-4191
https://jaslda.journals.pnu.ac.ir

Payame Noor University

JASLDA

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

VOLUME 1 ▪ ISSUE 1
SUMMER–AUTUMN 2026

Collected Articles

Journal of Advances in Statistical Learning
and Data Analysis

Six articles on statistical learning,
probability modelling and data analysis

Payame Noor University

Published by Payame Noor University

Online ISSN: 3150-4191 ▪ https://jaslda.journals.pnu.ac.ir

About This Issue

Journal	Journal of Advances in Statistical Learning and Data Analysis (JASLDA)
Volume / Issue	Volume 1, Issue 1
Issue date	Summer–Autumn 2026
Publisher	Payame Noor University (PNU), Tehran, Iran
Online ISSN	3150-4191
Website	https://jaslda.journals.pnu.ac.ir
DOI prefix	10.30473/jaslda
Article type	Research articles
Access	Open access

Copyright and License

© 2026 by the authors. Licensee PNU, Tehran, Iran. The articles in this collection are open access articles distributed under the terms and conditions of the Creative Commons Attribution 4.0 International license (CC BY 4.0; http://creativecommons.org/licenses/by/4.0).

Pagination and Citation

This collection brings together the six articles of Volume 1, Issue 1 in their final typeset form. The articles carry a single continuous pagination (pages 1–120), so that every page number printed in an article is the page number used when citing it. The front matter is numbered with Roman numerals. Each article should be cited in the format shown in its own *How to Cite* box, for example:

> *Author(s). (2026). "Article title".* Journal of Advances in Statistical Learning and Data Analysis, *1*(1), first page–last page. https://doi.org/10.30473/jaslda.2026.*article-id*

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

EDITORIAL BOARD

Journal of Advances in Statistical Learning and Data Analysis (JASLDA)

Payame Noor University, Iran



EDITOR-IN-CHIEF

Parviz Nasiri

Professor of Statistics

Department of Statistics, Payame Noor University, Tehran, Iran

Research interests: Bayesian inference; reliability; outlier analysis

Email: pnasiri@pnu.ac.ir ORCID: 0000-0002-0827-4853



DIRECTOR-IN-CHARGE

Iman Makhdoom

Assistant Professor of Statistics

Department of Statistics, Payame Noor University, Tehran, Iran

Research interests: Reliability analysis; distribution theory; Bayesian inference; data science; machine learning

Email: makhdoom@pnu.ac.ir ORCID: 0000-0002-2768-1024



MANAGER

Vahdat Rafee

Assistant Professor

Department of Physics, Payame Noor University, Tehran, Iran

Research interests: DFT, nano structure, solar cell, NLO

Email: v.rafee@pnu.ac.ir ORCID: 0000-0002-1122-0338

The Editorial Board

Siamak Noorbaloochi

Professor of Statistics

VA Health Care System, Department of Medicine, University of Minnesota, USA

Research interests: Statistical medicine; dimension reduction; bias reduction; decision theory

Email: noorb002@umn.edu

Noor Zaman Jhanjhi

Professor; Director, Centre for Intelligent Innovations; PD/PG Research Programmes

Taylor's University, Malaysia

Research interests: Cybersecurity; artificial intelligence; agentic AI and large language models; security and privacy; software engineering

Website: noorzaman.com Email: noorzaman.jhjanjhi@taylors.edu.my

ORCID: 0000-0001-8116-4733

Masoud Yarmohammadi

Professor of Statistics

Department of Statistics, Payame Noor University, Tehran, Iran

Research interests: Time series analysis

Email: masyar@pnu.ac.ir

ORCID: 0000-0001-7038-7106

Gholamreza Hesamian

Professor of Statistics

Department of Statistics, Payame Noor University, Tehran, Iran

Research interests: Fuzzy statistics

Email: gh.hesamian@pnu.ac.ir

ORCID: 0000-0002-3175-7909

Mohammed Zafar Anis

Professor of Statistics

Indian Statistical Institute, Kolkata, India

Research interests: Life testing; process capability indices; quality engineering and management; reliability theory; statistical quality control

Website: ISI website Email: zafaris@isical.ac.in

Rahim Chinipardaz

Professor of Statistics

Shahid Chamran University of Ahvaz, Ahvaz, Iran

Research interests: Time series analysis; Bayesian inference

Email: chinipardaz_r@scu.ac.ir

Abdolrahman Rasekh

Professor of Statistics

Shahid Chamran University of Ahvaz, Ahvaz, Iran

Research interests: Linear models

Email: rasekh_a@scu.ac.ir

ORCID: 0000-0002-4198-5104

Gholam Ali Parham

Professor of Statistics

Department of Statistics, Faculty of Mathematics, Science, and Computer, Shahid Chamran University of Ahvaz, Iran

Research interests: Stochastic processes

Email: parham_g@scu.ac.ir

Farzad Eskandari

Professor of Applied Statistics and Data Science

Allameh Tabataba'i University, Tehran, Iran

Research interests: Data science; machine learning; computational statistics; Bayesian statistics

Website: Faculty profile Email: askandari@atu.ac.ir

Mohammad Bameni Moghadam

Professor of Statistics

Faculty of Statistics, Mathematics, and Computer, Allameh Tabataba'i University, Tehran, Iran

Research interests: Statistical quality control; reliability

Email: bamenimoghadam@atu.ac.ir

Esmail Khorram

Professor of Statistics

Amirkabir University of Technology, Tehran, Iran

Research interests: Fuzzy optimization; order statistics; reliability; multi-objective optimization; queueing theory

Email: eskhor@aut.ac.ir

Alireza Nematollahi

Professor of Statistics

Department of Statistics, Shiraz University, Shiraz, Iran

Research interests: Statistics and statistical methodology

Email: ar.nematollahi@shirazu.ac.ir

ORCID: 0000-0002-2623-7159

Alireza Daneshkhah

Professor of Data Science

Faculty of Mathematics and Data Science, Emirates Aviation University, UAE

Research interests: Bayesian machine learning; physics-informed neural networks; resilience and risk analysis

Email: alireza.daneshkhah@eau.ac.ae

ORCID: 0000-0001-7751-4307

Madjid Eshaghi Gordji

Professor of Mathematics

Semnan University, Semnan, Iran

Research interests: Functional analysis; game theory; functional equations; nonlinear analysis; network science; cognitive modelling

Email: meshaghi@semnan.ac.ir

ORCID: 0000-0003-0787-2277

Masoud Ganji

Professor of Mathematical Statistics

University of Mohaghegh Ardabili, Ardabil, Iran

Research interests: Mathematical statistics

Website: Faculty profile Email: mganji@uma.ac.ir

Mahmoud Afshari

Professor of Statistics

Faculty of Intelligent Systems and Data, Persian Gulf University, Bushehr, Iran

Research interests: Wavelets in statistics; distribution theory

Website: Faculty profile Email: afshar@pgu.ac.ir

Kambiz Ahmadi Angali

Professor of Biostatistics

Department of Biostatistics and Epidemiology, School of Health, Ahvaz Jundishapur University of Medical Sciences, Iran

Research interests: Biostatistics; modelling and data analysis in nutrition, environmental research, and medicine

Email: angali-k@ajums.ac.ir

ORCID: 0000-0002-1530-2349

Ghodratollah Roshanaei

Professor of Biostatistics

Modelling of Non-communicable Diseases Research Center, Department of Biostatistics, School of Public Health, Hamadan University of Medical Sciences, Iran

Research interests: Biostatistical modelling of non-communicable diseases

Email: ghroshanaei2025@gmail.com

ORCID: 0000-0002-3547-9125

Ezzatallah Baloui Jamkhaneh

Associate Professor of Statistics

Department of Statistics, Qaemshahr Branch, Islamic Azad University, Qaemshahr, Iran

Research interests: Intuitionistic fuzzy set theory; fuzzy reliability

Email: eb.jamkhaneh@iau.ac.ir

Hassan Doosti

Associate Professor of Statistics

School of Mathematical and Physical Sciences, Pollinator Futures Research Centre, Macquarie University, Sydney, Australia

Research interests: Flexible modelling techniques

Website: University profile Email: hassan.doosti@mq.edu.au

ORCID: 0000-0002-0290-8122

Reza Pourtaheri

Professor of Statistics

Faculty of Statistics, Mathematics and Computer, Allameh Tabataba'i University, Tehran, Iran

Research interests: Statistical inference for point processes; stochastic processes

Website: Faculty profile Email: pourtaheri@atu.ac.ir

ORCID: 0000-0001-7372-9028

Narges Abbasi

Associate Professor of Statistics

Department of Statistics, Payame Noor University, Tehran, Iran

Research interests: Statistical inference; statistical modelling

Email: n_abbasi@pnu.ac.ir

ORCID: 0000-0002-2845-1482

Ali Barati

Associate Professor of Computer Engineering

Dezful Branch, Islamic Azad University, Dezful, Iran

Research interests: Wireless communications; wireless sensor networks; Internet of Things; network security

Email: abarati@iaud.ac.ir

Ali Shadrokh

Associate Professor of Statistics

Department of Statistics, Payame Noor University, Iran

Research interests: Linear Models

Email:ali_shadrokh@hotmail.com

Abbas Pak

Associate Professor of Statistics; Computational Statistician and Data Scientist

Department of Computer Sciences, Shahrekord University, Shahrekord, Iran

Research interests: Statistics; Bayesian inference; data science; machine learning; deep learning

Email: abbas.pak1982@gmail.com

ORCID: 0000-0003-2388-3523

Ali Akbar Jafari

Associate Professor of Statistics

Department of Statistics, Yazd University, Yazd, Iran

Research interests: Linear models; generalized p-values; bootstrap; ranked set sampling; information theory

Website: Faculty profile Email: aajafari@yazd.ac.ir

ORCID: 0000-0002-2980-338X

Mohammadreza Mahmoudi

Associate Professor of Statistics

Institute of Statistics, Data Mining and Data Science, Fasa University, Fasa, Iran

Research interests: Data science; data visualization; statistical signal processing; time series analysis; data mining

Website: Faculty profile Email: mahmoudi.m.r@fasau.ac.ir

ORCID: 0000-0003-4686-0930

Mehdi Jabbari Nooghabi

Associate Professor of Statistics

Department of Mathematical Sciences, University of Copenhagen, Denmark; Department of Statistics, Ferdowsi University of Mashhad, Iran

Research interests: Statistics; outlier analysis; data science; insurance

Website: Faculty profile Email: jabbarinm@um.ac.ir

Amir Jamshidnezhad

Associate Professor of Computer Science

Ahvaz Jundishapur University of Medical Sciences, Ahvaz, Iran

Research interests: Optimization; classification; pattern recognition

Email: jamshidnejad@ajums.ac.ir

Mohammad Reza Salehi Rad

Associate Professor of Statistics

Faculty of Statistics, Mathematics and Computer, Allameh Tabataba'i University, Tehran, Iran

Research interests: Statistics; probability theory

Website: Faculty profile Email: salehirad@atu.ac.ir

Majid Jafari Khaledi

Associate Professor of Statistics

Department of Statistics, Tarbiat Modares University, Tehran, Iran

Research interests: Spatial statistics; Bayesian analysis; statistical modelling

Email: jafari-m@modares.ac.ir

ORCID: 0000-0002-2138-1098

Rahim Mahmoudvand

Associate Professor of Statistics

Department of Statistics, Faculty of Science, Bu-Ali Sina University, Hamedan, Iran

Research interests: Statistics; actuarial science

Email: r.mahmoudvand@basu.ac.ir

ORCID: 0000-0003-2157-0582

Afshin Fallah

Associate Professor of Statistics

Department of Statistics, Imam Khomeini International University, Qazvin, Iran

Research interests: Mixture distributions; Bayesian modelling; spatial statistics

Email: a.fallah@sci.ikiu.ac.ir

Amin Golabpour

Associate Professor of Medical Informatics

Shahroud University of Medical Sciences, Shahroud, Iran

Research interests: Medical data mining; artificial intelligence

Email: a.golabpour@shmu.ac.ir

ORCID: 0000-0001-7649-4033

Ahad Malekzadeh

Associate Professor of Statistics

Department of Mathematics, Computer Science and Statistics, K. N. Toosi University of Technology, Tehran, Iran

Research interests: Statistics; probability theory

Website: Faculty profile Email: malekzadeh@kntu.ac.ir

Ali Mohammadian Mosammam

Associate Professor of Statistics

Department of Statistics, University of Zanjan, Zanjan, Iran

Research interests: Space-time statistics; time series; bioinformatics; official statistics; kernel methods

Website: Faculty profile Email: a.m.mosammam@znu.ac.ir

ORCID: 0000-0001-8094-7517

Sarah Jomhoori

Associate Professor of Statistics

Department of Statistics, University of Birjand, Birjand, Iran

Research interests: Approximation theorems; nonparametric statistics; empirical likelihood

Email: sjomhoori@birjand.ac.ir

ORCID: 0000-0003-2413-0371

Farshin Hormozinejad

Associate Professor of Statistics

Department of Statistics, Ahvaz Branch, Islamic Azad University, Ahvaz, Iran

Research interests: Statistics

Website: Faculty profile Email: farshin.hormozinejad@iau.ac.ir

Roshanak Alimohammadi

Associate Professor of Statistics

Department of Statistics, Alzahra University, Tehran, Iran

Research interests: Time series analysis; stochastic processes

Email: r_alimohammadi@alzahra.ac.ir

ORCID: 0000-0002-1758-8870

ENGLISH TEXT EDITOR

Elkhas Vaysi

Associate Professor of Linguistics and Foreign Languages

Payame Noor University, Tehran, Iran

Research interests: Discourse; phonology; teaching linguistics at the M.A. and Ph.D. levels

Email: veysi@pnu.ac.ir ORCID: 0000-0003-2039-3713

Journal website: https://jaslda.journals.pnu.ac.ir/

Preface

It is with great pleasure that we present the first issue of the *Journal of Advances in Statistical Learning and Data Analysis* (JASLDA), published by Payame Noor University. The journal was founded to provide an open forum in which methodological developments in statistics, modern machine learning and applied data analysis can meet, and in which theory, computation and real data are treated as parts of one discipline.

The six articles of this inaugural issue reflect that ambition. The first benchmarks recurrent neural network architectures for sequential prediction and applies them to air pollution forecasting. The second generalizes the Farlie–Gumbel–Morgenstern copula so that it can express stronger negative dependence, with an application to hydrological data. The third studies optimization algorithms for variational autoencoders, including a shrinkage-based update rule, and examines how posterior collapse depends on the optimizer, the learning rate and the architecture. The fourth gives a reliability-oriented analysis of the Topp–Leone distribution, with exact results on order statistics, information measures and the stress–strength model. The fifth examines how diagnostic measures in linear mixed measurement error models respond to the Liu biasing parameter and to the error distribution. The sixth proposes a weighted bootstrap mean that stabilizes eigenvector-based noise removal in color images.

Together they range from distribution theory and dependence modelling to deep learning, regression diagnostics and image analysis, which is the breadth of interest the journal hopes to serve. We thank the authors for entrusting their work to a new journal, and we thank everyone whose effort made this first issue possible. We hope that the issue will be useful to researchers and practitioners, and we welcome submissions from the statistics and data science community for the issues to come.

The Editors
Journal of Advances in Statistical Learning and Data Analysis
Payame Noor University, Tehran, Iran

Table of Contents

Volume 1, Issue 1 · Summer–Autumn 2026 Pages

1 **Benchmarking Recurrent Neural Network Architectures for Sequential Prediction with Application to Air Pollution Forecasting** 1–22
Abbas Pak, Mohammad Javad Nematollahi

DOI: 10.30473/jaslda.2026.13501

2 **A Generalized FGM Copula with Enhanced Negative Dependence for Hydrological Applications** 23–45
Hakim Bekrizadeh

DOI: 10.30473/jaslda.2026.77901.1003

3 **Extended Optimizers in Variational Autoencoders Using Shrinkage Estimation** 46–64
Heydar Mokhtari Farivar, Parviz Nasiri

DOI: 10.30473/jaslda.2026.77814.1000

4 **Topp-Leone Distribution: A Reliability Analysis Perspective** 65–88
Alireza Pakgohar, Soheil Shokri

DOI: 10.30473/jaslda.2026.77349.1001

5 **Sensitivity Analysis of Diagnostic Measures to the Liu Biasing Parameter and Error Distribution in Linear Mixed Measurement Error Models** 89–106
Fatemeh Ghapani, Razieh Jafaraghaie

DOI: 10.30473/jaslda.2026.79273.1009

6 **Enhancing the Stability of Noise Removal in Color Images Using Eigenvector Analysis and Weighted Bootstrap Mean** 107–120
Reza Ghasemi

DOI: 10.30473/jaslda.2026.78206.1004

Click an entry to jump to the article. Page numbers refer to the continuous pagination of this collection.

Author Index

Entries give the first page of the author's article in this issue.

Bekrizadeh, Hakim 23

Ghapani, Fatemeh 89

Ghasemi, Reza 107

Jafaraghaie, Razieh 89

Mokhtari Farivar, Heydar 46

Nasiri, Parviz 46

Nematollahi, Mohammad Javad 1

Pak, Abbas 1

Pakgohar, Alireza 65

Shokri, Soheil 65

Affiliations

Payame Noor University, Tehran, Iran . . . . . Bekrizadeh, Nasiri, Pakgohar, Ghasemi
Shahrekord University, Shahrekord, Iran . . . . . Pak
Urmia University, Urmia, Iran . . . . . Nematollahi
Iran University of Science and Technology, Tehran, Iran . . . . . Mokhtari Farivar
Islamic Azad University, Rasht Branch . . . . . Shokri
Islamic Azad University, Shoushtar Branch . . . . . Ghapani, Jafaraghaie

https://jaslda.journals.pnu.ac.ir

Payame Noor University

Statistical Learning & Data Analysis
Volume 1, Issue 1, Summer- Autumn 2026, Pages 1–22
doi:10.30473/jaslda.2026.13501

OPEN ACCESS

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

Research Article

Benchmarking Recurrent Neural Network Architectures for Sequential Prediction with Application to Air Pollution Forecasting

Abbas Pak[1,✉], Mohammad Javad Nematollahi[2]

[1,✉]Department of Computer Sciences, Shahrekord University, Shahrekord, Iran
[2]Department of Geology, Faculty of Sciences, Urmia University, Urmia, Iran

Article History

Received: August 05, 2026;
Accepted: September 12, 2026;
Available online: September 19, 2026.

Abstract. This study presents a comprehensive benchmarking analysis of state-of-the-art recurrent neural network (RNN) architectures for sequential prediction tasks. A wide range of recurrent models, including Simple RNN, Independently Recurrent Neural Network (IndRNN), Long Short-Term Memory (LSTM), Gated Recurrent Unit (GRU), Bidirectional LSTM (BiLSTM), Residual BiLSTM (ResBiLSTM) are systematically investigated under a unified experimental framework. The proposed benchmarking framework evaluates all models on a real-world air pollution prediction task using multivariate environmental and meteorological data. Performance is assessed using multiple standard metrics, including root mean square error (RMSE), mean absolute error (MAE), and the coefficient of determination (R^2), enabling a comprehensive evaluation of predictive accuracy and generalization capability. Experimental results demonstrate that IndRNN achieves the best overall performance, providing superior accuracy while maintaining a relatively simple and computationally efficient architecture compared to other deep recurrent variants. The actual-versus-predicted analysis further supports this conclusion and IndRNN exhibits the closest alignment between predicted and observed values, achieving the highest coefficient of determination ($R^2 = 0.6375$) and the lowest prediction error (RMSE = 17.0203) among the evaluated recurrent architectures. These findings highlight the effectiveness of IndRNN as a strong candidate for practical sequential forecasting applications.

Keywords. Sequential prediction; Deep learning; Recurrent neural network; Air pollution forecasting.

MSC. 92B20, 62M20 .

How to Cite
Abbas Pak, Mohammad Javad Nematollahi. (2026). "Benchmarking Recurrent Neural Network Architectures for Sequential Prediction with Application to Air Pollution Forecasting". *Journal of Advances in Statistical Learning and Data Analysis*, 1(1), 1–22. https://doi.org/10.30473/jaslda.2026.13501

✉Corresponding author. **E-mail:** abbas.pak1982@gmail.com
©2026 by the authors. Licensee PNU, Tehran, Iran. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution 4.0 International (CC BY4.0) (http:/creativecommons.org/licenses/by/4.0)

1 Introduction

Sequential prediction is a fundamental problem in machine learning and data analytics, aiming to model temporal dependencies in ordered observations and forecast future states of dynamic systems. Accurate sequential forecasting plays a critical role in numerous domains, including finance, healthcare, transportation, energy systems, climate modeling, and environmental monitoring [1]. Unlike conventional prediction tasks, sequential prediction requires models to capture temporal dependencies, nonlinear interactions, seasonality, and long-range relationships embedded within time-series data [2, 3]. Consequently, developing effective learning architectures for sequential data has become a central topic in machine learning and artificial intelligence research, motivating extensive advances in recurrent, convolutional, attention-based, and transformer-oriented forecasting models [4, 5, 6].

Traditional forecasting methods, including autoregressive integrated moving average (ARIMA), seasonal ARIMA (SARIMA), exponential smoothing, and other statistical approaches, have been extensively used for temporal modeling and forecasting applications across economics, energy, transportation, environmental science, and public health domains [7]. Although these methods provide interpretable solutions and perform adequately for relatively simple linear processes, their effectiveness often deteriorates when confronted with highly nonlinear, multivariate, and nonstationary real-world data. More recently, machine learning techniques, including Decision Trees, Random Forests, Extra Trees, Gradient Boosting Machines (GBM), and Light Gradient Boosting Machine (LightGBM), have demonstrated strong predictive capabilities by modeling complex nonlinear relationships, high-order feature interactions, and heterogeneous data structures without requiring strict assumptions of linearity or stationarity [8, 9, 10, 11, 12]. However, these methods generally operate on fixed-length feature representations and do not explicitly capture temporal dependencies, making them less suitable for sequential prediction problems characterized by long-term memory and dynamic temporal structures.

The emergence of deep learning has significantly advanced the field of sequential modeling by enabling hierarchical representation learning from complex temporal data [1, 13]. Transformer-based architectures attracted considerable attention in time-series forecasting because of their ability to model long-range temporal dependencies through self-attention mechanisms and to capture relationships across different positions in a sequence without relying exclusively on recurrent connections. However, their effectiveness can depend on factors such as data volume, sequence length, computational requirements, and model complexity. Among deep learning approaches, recurrent neural networks (RNNs) have emerged as one of the most influential architectures for sequential prediction because of their ability to process temporal information through recurrent connections and maintain internal memory states across time steps [14, 15]. Unlike feedforward neural networks, which process observations independently, RNNs propagate hidden-state information from previous time steps to subsequent ones, allowing the network to capture temporal dependencies and contextual relationships within sequential data [14, 16]. Consequently, RNN-based architectures have become fundamental tools for sequence modeling tasks such as time-series forecasting, speech recognition, natural language processing, and spatio-temporal prediction [16, 17]. However, conventional RNNs often suffer from vanishing and exploding gradient problems, limiting their capability to learn long-term dependencies in complex temporal sequences. To address these limitations, several advanced recurrent architectures have been proposed, including Long Short-Term Memory (LSTM) networks, Gated Recurrent Units (GRU), Bidirectional LSTMs (BiLSTM), Independently Recurrent Neural Network (IndRNN), and Residual Bidirectional LSTM (ResBiLSTM) [14, 18]. These architectures introduce specialized gating mechanisms, residual connections, attention modules, and spatiotemporal feature

extraction capabilities that significantly improve learning efficiency and predictive performance in complex sequential environments.

Despite substantial progress in recurrent deep learning models, a major limitation in the existing literature is the absence of a unified benchmarking framework that systematically compares a broad spectrum of recurrent architectures under identical experimental conditions. Many studies focus on only a small subset of recurrent architectures, often comparing one or two deep learning models against limited baselines. Moreover, differences in preprocessing procedures, feature selection methods, forecasting horizons, and evaluation metrics make it difficult to draw reliable conclusions regarding the relative strengths and weaknesses of competing architectures. Recent review studies have emphasized the need for unified benchmarking frameworks capable of evaluating state-of-the-art recurrent models under consistent experimental conditions [19].

Motivated by these challenges, this study presents a comprehensive benchmarking analysis of state-of-the-art recurrent neural network architectures for sequential prediction. The proposed framework systematically evaluates multiple recurrent models, including Simple RNN, IndRNN, LSTM, GRU, BiLSTM, and ResBiLSTM. To ensure a fair and reproducible comparison, all models are trained and evaluated using identical preprocessing, feature engineering, and validation protocols on a real-world air pollution forecasting dataset. Air quality prediction constitutes a challenging sequential prediction task due to the presence of complex nonlinear relationships, temporal dependencies, seasonal patterns, and external environmental influences. These characteristics make air pollution forecasting an appropriate testbed for assessing the effectiveness of modern recurrent neural network architectures.

The primary contributions of this work are fourfold. First, A unified benchmarking framework is developed for the comparative evaluation of state-of-the-art RNN architectures for sequential prediction. Second, multiple advanced recurrent architectures are systematically investigated under identical experimental settings. Third, the effectiveness of advanced recurrent architectures in modeling complex temporal dependencies is assessed using real-world environmental data. Finally, comprehensive performance evaluation is conducted using multiple statistical metrics to assess predictive accuracy, robustness, and generalization capability. The remainder of this paper is organized as follows. Section 2 describes the dataset, preprocessing procedures, the investigated models and benchmarking framework. Section 3 details the experimental setup and evaluation metrics. Section 4 discusses the comparative results and analysis. Section 5 provides a discussion of the key results and their broader significance.

2 Materials and Methods

2.1 Dataset Description and Preprocessing

The experiments are conducted using a real-world multivariate air quality dataset collected from an environmental monitoring station reported by [12, 20]. The dataset covers a ten-year period from January 2013 to December 2023, with observations recorded at a daily temporal resolution. This relatively long and consistent time span provides sufficient temporal coverage for training and testing the predictive models while allowing the models to capture seasonal and longer-term temporal patterns in air pollutant concentrations. The dataset contains measurements of atmospheric pollutants together with meteorological variables that influence pollutant dispersion

and accumulation. The predictive model includes carbon monoxide (CO), ozone (O3), nitrogen dioxide (NO2), sulfur dioxide (SO2), particulate matter with an aerodynamic diameter of 10 or less (PM10), temperature, dew point, relative humidity , wind speed, and atmospheric pressure, to estimate the concentration of fine particulate matter (PM2.5). To ensure data quality and improve model reliability, several preprocessing steps are applied before model development. At first, rows containing missing observations are removed to eliminate potential bias introduced by data imputation and to ensure that all models are trained using complete observations. Since sequential forecasting requires preservation of temporal dependencies, all observations are sorted according to their timestamps before feature engineering. Further, predictor variables are normalized using Min-Max normalization

$$x' = \frac{x - x_{min}}{x_{max} - x_{min}}$$

where x denotes the original feature value. Normalization accelerates neural network convergence and prevents variables with large numerical ranges from dominating the optimization process.

2.2 Feature Engineering

Feature engineering is an essential step in enhancing the performance of sequential prediction models because it enriches the information available for forecasting. Historical pollutant observations are incorporated into the dataset through lagged variables, where measurements from previous time steps are used as additional explanatory features. This enables the models to capture temporal dependencies and persistence patterns commonly observed in air pollution data. To represent short-term temporal dynamics more effectively, rolling statistical measures are computed using window sizes of 3, 7, and 14 time steps. These statistics include the rolling mean, rolling standard deviation, rolling minimum, and rolling maximum, which collectively provide information about local trends, variability, and extreme values in the recent history of the series. Temporal variables often exhibit periodic behavior; therefore, cyclical encoding is applied to variables such as hour of the day, day of the week, and month of the year. Sine and cosine transformations are used to preserve the cyclical nature of these variables and to avoid artificial discontinuities between the end and the beginning of each cycle. Since recurrent neural networks operate on sequential data rather than independent observations, the multivariate time series is transformed into supervised learning samples using a sliding-window approach. For a sequence length L, each input sample consists of a sequence of consecutive observations from x_{t-L+1} to x_t, while the corresponding target is the next observation y_{t+1}. This transformation produces overlapping input–output pairs that are appropriate for training recurrent learning models and allows the networks to learn temporal relationships across successive time steps.

2.3 Benchmark Models

To provide a comprehensive evaluation of recurrent neural network architectures for sequential prediction, six representative recurrent models with different structural characteristics and memory mechanisms were selected for benchmarking. The chosen architectures include the conventional Simple Recurrent Neural Network (SimpleRNN), Independently Recurrent Neural Network (IndRNN), Long Short-Term Memory (LSTM), Gated Recurrent Unit (GRU), Bidirectional

Long Short-Term Memory (BiLSTM), and Residual Bidirectional Long Short-Term Memory (ResBiLSTM). These models were selected because they represent the major evolutionary stages of recurrent learning, ranging from basic recurrent structures to advanced gated, bidirectional, and residual architectures. All models were implemented using the same deep learning framework and trained under identical preprocessing, optimization, and evaluation conditions to ensure a fair comparison. The objective of this benchmark is to investigate the ability of each architecture to capture nonlinear temporal dependencies, retain historical information, and provide accurate forecasts for multivariate air pollution time-series data. The following subsections briefly describe the theoretical foundations and structural characteristics of each recurrent model used in this study.

2.3.1 Recurrent Neural Network

The Simple Recurrent Neural Network (SimpleRNN), also referred to as the vanilla RNN, is the fundamental recurrent architecture designed for processing sequential data. Unlike feedforward neural networks, SimpleRNN introduces recurrent connections that allow information from previous time steps to influence the current hidden state. This recurrent structure enables the network to model temporal dependencies in time-series sequences and sequential observations. In a sequential prediction problem, let the input sequence be represented as

$$X = \{x_1, x_2, \ldots, x_T\}$$

where $x_t \in \mathbb{R}^d$ denotes the input vector at time step t, d is the number of input features, and T is the sequence length. The SimpleRNN maintains a hidden state h_t that is updated recursively according to the current input and the previous hidden state. The hidden-state update is defined as

$$h_t = \phi(W_{xh}x_t + W_{hh}h_{t-1} + b_h)$$

where $W_{xh} \in \mathbb{R}^{m\times d}$ is the input-to-hidden weight matrix, $W_{hh} \in \mathbb{R}^{m\times m}$ is the recurrent hidden-to-hidden weight matrix, $b_h \in \mathbb{R}^m$ is the hidden bias vector, m is the number of hidden units, $\phi(\cdot)$ is the activation function, typically the hyperbolic tangent function (tanh). The hyperbolic tangent activation is expressed as

$$\phi(z) = \tanh(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

which constrains the hidden-state values to the interval $(-1, 1)$, helping to stabilize the learning process. The output of the network at time step t is computed from the hidden state as $y_t = W_{hy}h_t + b_y$ where $W_{hy} \in \mathbb{R}^{k\times m}$ is the hidden-to-output weight matrix, $b_y \in \mathbb{R}^k$ is the output bias vector, k is the output dimension. For regression-based forecasting tasks such as air pollution prediction, the output layer usually employs a linear activation function, and the predicted value for the next time step is given by $\hat{y}_{t+1} = W_{hy}h_t + b_y$. The recursive nature of SimpleRNN can be expanded to show its dependence on all previous inputs. By repeatedly substituting the hidden-state equation, the hidden state at time step t becomes

$$h_t = \phi(W_{xh}x_t + W_{hh}\phi(W_{xh}x_{t-1} + W_{hh}h_{t-2} + b_h) + b_h).$$

This expression illustrates that the current hidden representation theoretically contains information from the entire history of the sequence. Therefore, the network can model temporal

relationships between current observations and past inputs. For a sequence of length T, the overall recurrent computation proceeds as follows:

$$h_1 = \phi(W_{xh}x_1 + W_{hh}h_0 + b_h)$$

$$h_2 = \phi(W_{xh}x_2 + W_{hh}h_1 + b_h)$$

$$\vdots$$

$$h_T = \phi(W_{xh}x_T + W_{hh}h_{T-1} + b_h).$$

The initial hidden state h_0 is commonly initialized to a zero vector, $h_0 = 0$. During training, the network parameters $\Theta = \{W_{xh}, W_{hh}, W_{hy}, b_h, b_y\}$ are optimized by minimizing a loss function over all training sequences. For regression problems, the MSE loss is commonly used:

$$\mathcal{L} = \frac{1}{N}\sum_{i=1}^{N}(y_i - \hat{y}_i)^2$$

where N is the number of training samples, y_i is the observed target value, and $\hat{y}_i$ is the predicted value produced by the network. The gradients of the loss with respect to the recurrent parameters are computed using Backpropagation Through Time (BPTT). Because the same recurrent weight matrix W_{hh} is reused at every time step, the gradient involves repeated multiplication by this matrix:

$$\frac{\partial \mathcal{L}}{\partial h_t} = \frac{\partial \mathcal{L}}{\partial h_{t+1}} W_{hh}^T \operatorname{diag}(\phi'(a_t))$$

where

$$a_t = W_{xh}x_t + W_{hh}h_{t-1} + b_h.$$

When the eigenvalues of W_{hh} are smaller than one, repeated multiplication causes the gradients to decay exponentially, leading to the vanishing gradient problem. Conversely, eigenvalues larger than one may produce exploding gradients. These issues make it difficult for SimpleRNN to learn long-term dependencies effectively.

Despite these limitations, SimpleRNN remains an important baseline architecture for sequential forecasting research because of its conceptual simplicity and relatively low computational cost. In this study, the SimpleRNN model serves as the fundamental recurrent benchmark against which more advanced architectures such as LSTM, GRU, BiLSTM, ResBiLSTM, and IndRNN are compared. The experimental results provide insight into the extent to which modern recurrent mechanisms improve the modeling of complex temporal dependencies in multivariate air pollution time-series data.

2.3.2 Independently Recurrent Neural Network

The Independently Recurrent Neural Network (IndRNN) is an advanced recurrent architecture proposed to overcome the limitations of conventional RNNs, particularly the vanishing and exploding gradient problems that arise when learning long-term temporal dependencies. Unlike SimpleRNN, where neurons within the same hidden layer are recurrently connected through a full recurrent weight matrix, IndRNN assigns an independent recurrent connection to each neuron. This structural modification significantly simplifies gradient propagation and enables

deeper and more stable recurrent networks. For a hidden layer containing m neurons, the hidden state of the j-th neuron at time step t is computed as

$$h_{t,j} = \phi(w_j^T x_t + u_j h_{t-1,j} + b_j)$$

where $w_j \in \mathbb{R}^d$ is the input weight vector for neuron j, u_j is the independent recurrent weight associated with neuron j, $h_{t-1,j}$ is the previous hidden state of the same neuron, b_j is the bias term, $\phi(\cdot)$ is the activation function, typically ReLU or tanh. In vector form, the hidden-state update for the entire layer can be written as

$$h_t = \phi(W x_t + u \odot h_{t-1} + b)$$

where $W \in \mathbb{R}^{m \times d}$ is the input weight matrix, $u \in \mathbb{R}^m$ is the vector of independent recurrent weights, $\odot$ denotes element-wise multiplication, $b \in \mathbb{R}^m$ is the bias vector. This formulation highlights the key difference between SimpleRNN and IndRNN. In SimpleRNN, the recurrent term is $W_{hh} h_{t-1}$ which mixes information across all hidden neurons through a dense recurrent matrix. In contrast, IndRNN replaces this operation with $u \odot h_{t-1}$ so that each neuron depends only on its own previous state. Consequently, neurons within a layer are independent in the recurrent dimension, while interactions between neurons are learned through the feedforward weight matrix W. For sequential forecasting, the output layer is computed as $\hat{y}_t = W_{hy} h_t + b_y$ where W_{hy} is the hidden-to-output weight matrix and b_y is the output bias vector. Expanding the recurrence over multiple time steps gives

$$h_{t,j} = \phi(w_j^T x_t + u_j \phi(w_j^T x_{t-1} + u_j h_{t-2,j} + b_j) + b_j).$$

Assuming a linear activation for analytical purposes, the hidden state can be approximated as

$$h_{t,j} \approx \sum_{k=0}^{t-1} u_j^k (w_j^T x_{t-k}) + u_j^t h_{0,j}.$$

This expression reveals that the influence of previous inputs is controlled solely by the scalar recurrent weight u_j. The gradient of the loss with respect to a hidden state becomes

$$\frac{\partial \mathcal{L}}{\partial h_{t,j}} = \frac{\partial \mathcal{L}}{\partial h_{T,j}} \prod_{k=t+1}^{T} u_j \phi'(a_{k,j})$$

where $a_{k,j} = w_j^T x_k + u_j h_{k-1,j} + b_j$. Because the recurrent coefficient is a single scalar rather than a full matrix, the gradient behavior is much easier to analyze and control. By constraining the magnitude of u_j, IndRNN can effectively avoid both gradient explosion and gradient vanishing over long sequences. This property allows IndRNN to process substantially longer temporal sequences than conventional RNNs while maintaining stable training dynamics. Another important advantage of IndRNN is its compatibility with deep recurrent architectures. Multiple IndRNN layers can be stacked as

$$h_t^{(l)} = \phi(W^{(l)} h_t^{(l-1)} + u^{(l)} \odot h_{t-1}^{(l)} + b^{(l)})$$

where l denotes the layer index. Since recurrent dependencies are independent within each layer, stacking does not introduce the severe optimization difficulties commonly encountered in deep traditional RNNs.

The computational complexity of an IndRNN layer is also lower than that of a standard RNN. A conventional RNN requires matrix multiplication involving the recurrent weight matrix $W_{hh} \in$

$\mathbb{R}^{m \times m}$, resulting in O(m²) recurrent computations per time step. IndRNN requires only element-wise multiplication with the recurrent vector u, reducing the recurrent computation to O(m). This reduction improves computational efficiency and scalability for large hidden dimensions. In this study, the IndRNN architecture is employed as an advanced recurrent benchmark for sequential air pollution forecasting. Its independently recurrent structure enables efficient learning of nonlinear temporal dependencies while maintaining stable gradient propagation across different sequence lengths.

2.3.3 Long Short-Term Memory

The Long Short-Term Memory (LSTM) network is an enhanced recurrent neural network architecture designed to overcome the vanishing gradient problem of conventional RNNs and to capture long-term temporal dependencies more effectively. LSTM introduces a memory cell and three gating mechanisms that regulate the flow of information through the network. For an input vector x_t, previous hidden state h_{t-1}, and previous cell state c_{t-1}, the LSTM computations are defined as follows:

Forget gate:

$$f_t = \sigma(W_f x_t + U_f h_{t-1} + b_f)$$

Input gate:

$$i_t = \sigma(W_i x_t + U_i h_{t-1} + b_i)$$

Candidate cell state:

$$\tilde{c}_t = \tanh(W_c x_t + U_c ht - 1 + b_c)$$

Cell state update:

$$c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t$$

Output gate:

$$o_t = \sigma(W_o x_t + U_o h_{t-1} + b_o)$$

Hidden state:

$$h_t = o_t \odot \tanh(c_t)$$

where $\sigma(\cdot)$ denotes the sigmoid activation function, $\tanh(\cdot)$ is the hyperbolic tangent function, and $\odot$ represents element-wise multiplication. The forget gate determines which information from the previous cell state should be retained, the input gate controls the incorporation of new information, and the output gate determines which part of the updated memory is exposed as the hidden representation. This gating mechanism allows LSTM to preserve relevant information over long sequences while reducing the effect of vanishing gradients.

2.3.4 Gated Recurrent Unit

The Gated Recurrent Unit (GRU) is a simplified variant of the LSTM architecture that was developed to improve computational efficiency while preserving the ability to learn long-term temporal dependencies. Unlike LSTM, GRU combines the cell state and hidden state into a single hidden representation and employs only two gating mechanisms: the update gate and the reset gate. This simpler structure reduces the number of trainable parameters and often leads

to faster training and inference. For an input vector x_t and the previous hidden state h_{t-1}, the GRU computations are given by:

Update gate

$$z_t = \sigma(W_z x_t + U_z h_{t-1} + b_z)$$

Reset gate

$$r_t = \sigma(W_r x_t + U_r h_{t-1} + b_r)$$

Candidate hidden state

$$\tilde{h}_t = \tanh(W_h x_t + U_h(r_t \odot h_{t-1}) + b_h)$$

Final hidden state

$$h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t$$

The reset gate controls how much information from the previous hidden state should be forgotten when computing the candidate hidden state, while the update gate determines the proportion of previous information that is retained versus the amount of new information that is incorporated into the current hidden state. This adaptive mechanism enables GRU to capture both short-term and long-term dependencies efficiently. Compared with LSTM, GRU has fewer parameters because it does not maintain a separate memory cell or output gate. Consequently, it generally requires less memory and shorter processing time, making it particularly suitable for real-time sequential forecasting applications.

2.3.5 Bidirectional Long Short-Term Memory

The Bidirectional Long Short-Term Memory (BiLSTM) network extends the conventional LSTM architecture by processing the input sequence in both forward and backward directions. While a standard LSTM only utilizes past observations to predict the current output, BiLSTM can exploit information from both previous and subsequent time steps, enabling the network to learn richer temporal representations. This characteristic is particularly useful for complex sequential patterns where contextual information from the entire sequence contributes to the prediction task. Given an input sequence $X = \{x_1, x_2, \ldots, x_T\}$, two independent LSTM layers are employed. The forward LSTM processes the sequence from $t = 1$ to T:

$$\overrightarrow{h_t} = \text{LSTM}f(x_t, \overrightarrow{h_{t-1}}, \overrightarrow{c_{t-1}})$$

The backward LSTM processes the sequence in reverse order:

$$\overleftarrow{h_t} = \text{LSTM}b(x_t, \overleftarrow{h_{t+1}}, \overleftarrow{c_{t+1}})$$

The final hidden representation is obtained by combining the forward and backward hidden states, typically through concatenation:

$$h_t = [\overrightarrow{h_t}; \overleftarrow{h_t}]$$

where $[\cdot;\cdot]$ denotes vector concatenation. The output layer then computes the prediction as

$$\hat{y}_t = W_y h_t + b_y$$

where W_y is the output weight matrix and b_y is the bias vector. By incorporating information from both temporal directions, BiLSTM can capture more comprehensive dependencies than unidirectional LSTM, often leading to improved prediction accuracy. However, this advantage comes at the cost of increased computational complexity and longer processing time, since two LSTM networks must be trained simultaneously.

2.3.6 Residual Bidirectional Long Short-Term Memory

The Residual Bidirectional Long Short-Term Memory (ResBiLSTM) network combines the advantages of Bidirectional LSTM (BiLSTM) and residual learning to improve the training of deeper recurrent architectures. Although BiLSTM can capture contextual information from both forward and backward temporal directions, stacking multiple bidirectional recurrent layers often leads to optimization difficulties, slower convergence, and degradation of performance. Residual connections alleviate these issues by providing a direct pathway for information and gradient propagation across layers. Let $h_t^{(l-1)}$ denote the input representation to the l-th BiLSTM layer. The bidirectional recurrent transformation is first computed as

$$\tilde{h}_t^{(l)} = \text{BiLSTM}^{(l)}(h_t^{(l-1)})$$

where $\tilde{h}_t^{(l)}$ is the output produced by the forward and backward LSTM units at layer l. A residual connection is then introduced by adding the input of the layer directly to its output:

$$h_t^{(l)} = \tilde{h}_t^{(l)} + h_t^{(l-1)}$$

This skip connection allows the network to learn only the residual mapping

$$\mathcal{F}(h_t^{(l-1)}) = \tilde{h}_t^{(l)} - h_t^{(l-1)}$$

instead of learning the entire transformation from scratch. Consequently, the updated representation can be expressed as

$$h_t^{(l)} = h_t^{(l-1)} + \mathcal{F}(h_t^{(l-1)}).$$

The residual formulation offers two important advantages. First, it facilitates gradient flow during backpropagation, reducing the risk of vanishing gradients when multiple recurrent layers are stacked. Second, it preserves useful low-level temporal features from earlier layers while allowing deeper layers to focus on learning complementary high-level representations. For the final prediction layer, the output sequence representation is transformed into the forecast value as

$$\hat{y}_t = W_y h_t^{(L)} + b_y$$

where $h_t^{(L)}$ is the output of the final residual bidirectional layer, W_y is the output weight matrix, and b_y is the bias vector. Compared with standard BiLSTM, ResBiLSTM is capable of modeling more complex temporal relationships by exploiting both bidirectional context and deep residual learning. However, the additional bidirectional recurrent computations and residual transformations increase the number of trainable parameters and computational cost. Therefore, ResBiLSTM is expected to provide improved representational capacity at the expense of longer training and inference times.

3 Experimental Setup

To ensure a fair and reproducible comparison, all forecasting models were trained and evaluated under identical experimental conditions. The same dataset, preprocessing pipeline, feature engineering procedure, training–testing partition, optimization strategy, and evaluation metrics were applied to every model. This unified experimental framework minimizes the influence of external

factors and enables an objective assessment of the relative performance of different machine learning and recurrent neural network architectures. The dataset was divided chronologically into training and testing subsets to preserve the temporal dependencies inherent in time-series data. The first 80% of the observations were used for model training and the remaining 20% for independent testing. Random shuffling was deliberately avoided to prevent information leakage from future observations into the training process.

Recurrent neural networks require sequential inputs rather than independent observations. A sliding-window approach was employed to generate input sequences from the multivariate time series. Each input sample consisted of the observations from the previous L time steps, while the target corresponded to the pollutant concentration at the next time step. To do this, the sequence lengths of 7, 14, and 28 time steps were selected to examine the ability of the RNN architectures to capture temporal dependencies over short-, medium-, and longer-term historical windows. Because the observations are recorded daily, these sequence lengths correspond to 7, 14, and 28 days of historical information, respectively. Thus, the selected windows provide a progressively broader temporal context while allowing the effect of increasing historical information on predictive performance to be systematically assessed. These values were chosen as representative temporal windows rather than as an exhaustive hyperparameter search over all possible sequence lengths.

To ensure reproducibility, all recurrent neural network architectures were trained using a consistent optimization and training protocol. The models were optimized using the Adam optimizer with its default learning rate of (0.001), and mean squared error (MSE) was used as the loss function, with mean absolute error (MAE) additionally monitored as an evaluation metric. For the recurrent layers, the hyperbolic tangent (tanh) activation function was employed, while a fully connected layer with 32 neurons and ReLU activation was used before the final output layer. The models were trained for a maximum of 200 epochs with a batch size of 32. To reduce overfitting and avoid unnecessary training after convergence, early stopping was applied based on the validation loss. Specifically, training was terminated when the validation loss did not improve for 10 consecutive epochs (patience = 10). Model performance is evaluated using three widely adopted regression metrics, mean absolute error (MAE), root mean square error (RMSE), and coefficient of determination (R^2). These metrics jointly assess prediction accuracy, error magnitude, and goodness of fit. All experiments are implemented in Python using Scikit-learn, TensorFlow, Keras, NumPy, Pandas, and LightGBM libraries. Training is performed on the same computing platform to ensure fair comparisons of computational efficiency among all investigated models.

4 Results

4.1 Comparative Performance for Different Sequence Lengths

The predictive performance of the investigated RNN architectures for sequence lengths of 7, 14, and 28 time steps are summarized in Tables 1–3. The results indicate that advanced recurrent architectures substantially outperform the conventional SimpleRNN model across all sequence lengths. Among the evaluated models, IndRNN consistently achieves the best overall predictive performance, demonstrating superior accuracy and robust generalization capability while maintaining moderate computational cost. For the shortest sequence length (Seq = 7),

IndRNN achieved the best performance with an MAE of 12.0001, an RMSE of 17.0203, and an R^2 value of 0.6375. This represents the highest explanatory power and the lowest prediction error among all evaluated architectures. BiLSTM produced the second-best R^2 value (0.6336) with an RMSE of 17.1359, followed by GRU ($R^2 = 0.6247$, RMSE = 17.3427). In contrast, SimpleRNN showed the weakest performance, yielding an RMSE of 18.3115 and an R^2 of 0.5816, indicating limited ability to capture the complex temporal dependencies present in the air pollution time series. Although ResBiLSTM achieved competitive accuracy (MAE = 12.0178, RMSE = 17.1445), its processing time (115.63 s) was substantially higher than that of IndRNN (35.15 s), suggesting a less favorable balance between accuracy and computational efficiency.

Increasing the sequence length to 14 time steps did not lead to significant performance improvements for most models. IndRNN again obtained the best overall results, achieving an MAE of 12.0081, an RMSE of 17.0455, and an R^2 of 0.6357. These values are very close to those obtained for Seq = 7, demonstrating the stability of the IndRNN architecture across different temporal contexts. GRU and ResBiLSTM achieved similar performance levels, with R^2 values of 0.6109 and 0.6091, respectively. However, ResBiLSTM required 257.13 seconds of processing time, which was more than seven times higher than GRU (35.72 s) and considerably higher than IndRNN (49.12 s). BiLSTM showed a slight degradation in performance compared with Seq = 7, while SimpleRNN remained the least accurate model with an RMSE of 18.4663 and an R^2 of 0.5724.

For the longest sequence length (Seq = 28), IndRNN continued to provide the best predictive performance, achieving an MAE of 12.1637, an RMSE of 17.0463, and an R^2 of 0.6272. GRU showed highly competitive results, with an RMSE of 17.0636 and an R^2 of 0.6204, indicating that GRU remains a strong alternative for longer input sequences. LSTM and BiLSTM exhibited slightly lower predictive accuracy, with RMSE values of 17.9616 and 17.8434, respectively. ResBiLSTM achieved moderate performance ($R^2 = 0.6142$), but its processing time increased dramatically to 432.38 seconds, making it the most computationally expensive architecture in the benchmark. The substantial increase in computational cost was not accompanied by a corresponding improvement in prediction accuracy.

Table 1: Model Performance Comparison for Sequence Length = 7

Model	**MAE**	**RMSE**	**R^2**	**Processing Time (s)**
SimpleRNN	13.0628	18.3115	0.5816	17.07
IndRNN	**12.0001**	**17.0203**	**0.6375**	35.15
LSTM	12.2221	17.4613	0.6133	49.05
GRU	12.2133	17.3427	0.6247	25.11
BiLSTM	12.2261	17.1359	0.6336	33.10
ResBiLSTM	12.0178	17.1445	0.6189	115.63

Table 2: Model Performance Comparison for Sequence Length = 14

Model	**MAE**	**RMSE**	**R^2**	**Processing Time (s)**
SimpleRNN	13.3757	18.4663	0.5724	27.60
IndRNN	**12.0081**	**17.0455**	**0.6357**	49.12
LSTM	12.4911	17.8321	0.6077	79.56
GRU	12.5966	17.6169	0.6109	35.72
BiLSTM	12.3924	17.8375	0.6011	86.50
ResBiLSTM	12.2111	17.4766	0.6091	257.13

Table 3: Model Performance Comparison for Sequence Length = 28

Model	**MAE**	**RMSE**	**R^2**	**Processing Time (s)**
SimpleRNN	13.8777	18.9215	0.5752	27.82
IndRNN	**12.1637**	**17.0463**	**0.6272**	37.59
LSTM	12.4214	17.9616	0.5934	74.65
GRU	12.2553	17.0636	0.6204	45.48
BiLSTM	12.2646	17.8434	0.5987	110.89
ResBiLSTM	12.1841	17.4950	0.6142	432.38

A comparison across the three sequence lengths reveals that increasing the historical input window beyond seven time steps does not necessarily improve forecasting accuracy. For most models, the best or near-best performance was obtained with Seq = 7. In particular, IndRNN achieved its highest R^2 (0.6375) and lowest RMSE (17.0203) using the shortest sequence length. This suggests that the most informative temporal dependencies for the considered air pollution forecasting task are concentrated within relatively recent observations, and that longer sequences may introduce redundant or noisy information that does not contribute substantially to predictive performance. The results also show that processing time generally increases with sequence length for all recurrent architectures. This increase is especially pronounced for BiLSTM and ResBiLSTM, whose bidirectional and residual structures require substantially greater computational resources as the sequence length grows.

Considering all evaluation metrics and sequence lengths together, IndRNN demonstrates the most consistent and reliable performance across the entire benchmark. It achieves the highest R^2 values, while also maintaining the lowest RMSE values in all three experimental settings. Although GRU and BiLSTM produce competitive results, their predictive accuracy remains slightly inferior to that of IndRNN. From a practical perspective, IndRNN offers an effective trade-off between forecasting accuracy and computational efficiency. While its processing time is moderately higher than that of SimpleRNN and GRU, it remains substantially lower than the computational cost required by the more complex ResBiLSTM architecture. These findings indicate that IndRNN is particularly well suited for real-world sequential air pollution forecasting applications where both prediction accuracy and computational efficiency are important considerations.



Figure 1: Scatter plots of the actual and predicted pollutant concentrations

4.2 Actual versus Predicted Values

The scatter plots of the actual and predicted pollutant concentrations for the RNN architectures evaluated in this study are presented in Figure 1. The dashed diagonal line represents the ideal one-to-one relationship between observed and predicted values. Therefore, points located closer to this line indicate higher predictive accuracy and better agreement between model outputs and the ground-truth observations.

The SimpleRNN model exhibited the weakest predictive performance among the investigated architectures, with an R^2 value of 0.5816 and an RMSE of 18.3115. The corresponding scatter plot shows a relatively large dispersion of points around the diagonal line, particularly for higher pollutant concentrations, indicating limited capability in capturing complex temporal dependencies and extreme pollution events. The IndRNN model improved the predictive

performance substantially, achieving an R^2 of 0.6375 and an RMSE of 17.0203. The predicted values are more tightly clustered around the ideal line compared with SimpleRNN, suggesting that the independent recurrent structure enhances the learning of long-term temporal patterns in the air pollution time series.

The LSTM architecture achieved an R^2 of 0.6133 with an RMSE of 17.4613. Although the model demonstrated a reasonable ability to follow the overall trend of the observed data, noticeable prediction errors remained for both low and high concentration ranges. The gating mechanism of LSTM improved temporal modeling compared with SimpleRNN, but its performance was inferior to several of the more advanced recurrent architectures. The GRU model produced one of the best overall results, with an R^2 of 0.6247 and an RMSE of 17.3427. As illustrated in Figure 1, the majority of the predicted values are concentrated near the diagonal reference line, indicating strong agreement with the observed measurements. The GRU architecture achieved a favorable balance between prediction accuracy and model complexity, demonstrating its effectiveness for sequential air pollution forecasting. The BiLSTM model achieved competitive performance, yielding an R^2 of 0.6336 and an RMSE of 17.1359. The bidirectional processing of temporal information allowed the model to capture richer contextual dependencies, resulting in a tighter distribution of points around the ideal prediction line and improved robustness across different concentration levels. The Residual BiLSTM architecture obtained an R^2 of 0.6189 and an RMSE of 17.1445. The residual connections contributed to stable learning and reduced prediction variance; however, the performance gain over the standard BiLSTM was relatively modest.

Overall, the actual-versus-predicted analysis confirms that advanced recurrent architectures provide substantially better predictive capability than the conventional SimpleRNN model. Among the evaluated networks, IndRNN achieved the highest R^2 value and demonstrated highly competitive accuracy with a comparatively simple architecture. The visual proximity of the IndRNN predictions to the ideal one-to-one line, together with its strong quantitative performance, supports the conclusion that IndRNN represents the most effective and practically efficient recurrent architecture for the considered air pollution forecasting task.

5 Discussion

This study presented a comprehensive benchmark of state-of-the-art RNN architectures for sequential air pollution prediction using real-world environmental and meteorological data. The experimental results demonstrate IndRNN architecture achieved superior performance across all experimental settings. The best overall performance was obtained for Seq = 7, where IndRNN achieved $R^2 = 0.6375$ and RMSE = 17.0203. The consistency of these results across different sequence lengths suggests that the independent recurrent structure is highly effective in learning both short-term and moderately long-term temporal patterns in air pollution data. The superior performance of IndRNN can be attributed to its independently recurrent hidden units, which mitigate the gradient vanishing and exploding problems commonly encountered in conventional RNN architectures. By decoupling recurrent connections across neurons, IndRNN facilitates more stable gradient propagation through time, enabling the network to capture nonlinear temporal dependencies more effectively than standard RNN, LSTM, and even some bidirectional recurrent architectures. This finding is consistent with recent studies reporting that simplified recurrent structures with improved gradient flow can achieve competitive or superior forecasting performance while maintaining lower architectural complexity.

LSTM and GRU are generally regarded as the dominant recurrent architectures for time-series forecasting because of their gating mechanisms for controlling information flow. In the present study, both architectures achieved substantially better performance than SimpleRNN, confirming their ability to model temporal dependencies in air pollution sequences. However, neither architecture consistently outperformed IndRNN. GRU produced competitive results, particularly for the longer sequence length (Seq = 28), where its RMSE (17.0636) was very close to that of IndRNN (17.0463). The relatively small performance gap suggests that GRU remains a strong alternative for sequential forecasting tasks, especially when computational efficiency is a primary concern. GRU also required less processing time than LSTM for all sequence lengths, which agrees with the theoretical advantage of its simpler gating structure. Nevertheless, the consistently higher R^2 values achieved by IndRNN indicate that the independent recurrent mechanism provides additional representational benefits beyond the conventional update and reset gates employed by GRU. LSTM exhibited stable but comparatively weaker performance, with RMSE values ranging from 17.46 to 17.96 and R^2 values between 0.5934 and 0.6133. Although LSTM successfully captured the overall temporal trends, its larger number of parameters and more complex memory structure may have reduced its ability to generalize effectively on the available dataset.

BiLSTM achieved the second-highest R^2 value for Seq = 7 (0.6336), demonstrating that bidirectional processing can improve the extraction of contextual temporal information. By incorporating both forward and backward dependencies during training, BiLSTM is able to learn richer sequence representations than unidirectional recurrent networks. However, this improvement came at the cost of increased computational complexity, and its performance deteriorated slightly as the sequence length increased. The Residual BiLSTM architecture did not provide substantial accuracy improvements despite its significantly higher computational cost. For Seq = 28, ResBiLSTM required more than 432 seconds of processing time, which was nearly twelve times higher than GRU and more than eleven times higher than IndRNN. The modest gain in predictive accuracy did not justify this dramatic increase in computational expense, suggesting that residual bidirectional structures may be unnecessarily complex for the considered air pollution forecasting task.

An important observation from the benchmark is that increasing the sequence length beyond seven time steps did not improve predictive performance. For most architectures, the best results were obtained with Seq = 7, while longer sequences either produced negligible improvements or slightly degraded the forecasting accuracy. This finding indicates that the dominant predictive information in the studied air pollution series is concentrated within relatively recent observations. Air pollutant concentrations are strongly influenced by short-term meteorological conditions, local emission sources, and recent atmospheric interactions, which may reduce the contribution of distant historical observations. Longer sequences can introduce redundant or noisy information, increasing the difficulty of optimization and potentially reducing generalization performance. The effect of sequence length was also evident in the computational results. Processing time increased for all recurrent architectures as the input window became longer, with the increase being particularly severe for BiLSTM and ResBiLSTM. These results highlight the importance of selecting an appropriate sequence length rather than assuming that longer historical windows necessarily lead to better forecasting performance.

The scatter plots of actual versus predicted values further support the quantitative results. IndRNN exhibited the tightest clustering of points around the ideal reference line, indicating the highest agreement between predicted and observed pollutant concentrations. The reduced dispersion across both low and high concentration ranges suggests that IndRNN is capable of modeling not only the average temporal behavior but also more extreme pollution episodes.

In contrast, SimpleRNN showed the largest spread of prediction errors, particularly for higher pollutant concentrations, confirming its limited capacity for learning complex temporal dynamics. GRU and BiLSTM produced reasonably concentrated prediction distributions, but their scatter plots exhibited slightly greater deviations from the ideal line than those observed for IndRNN.

From an operational perspective, forecasting models for environmental monitoring systems must satisfy two often conflicting requirements: high predictive accuracy and reasonable computational efficiency. The results of this study suggest that IndRNN provides an effective compromise between these objectives. Although its processing time is moderately higher than that of GRU, it remains substantially lower than the computational cost associated with more complex bidirectional and residual architectures while consistently delivering the best predictive performance. These characteristics make IndRNN particularly attractive for real-time or near-real-time air quality forecasting systems, where models must be updated frequently as new monitoring data become available. Accurate short-term forecasts can support early warning systems, traffic and emission management strategies, and public health interventions aimed at reducing exposure to hazardous pollution events. For practitioners, model selection should nevertheless be based on task-specific validation rather than on architecture type alone. A suitable operational workflow should first establish a chronological evaluation scheme that reflects the intended forecasting setting, followed by comparison of candidate architectures using both predictive metrics and computational requirements. Where rapid deployment, limited computational resources, or model simplicity are priorities, computationally less demanding architectures such as SimpleRNN or GRU may remain practical alternatives if their predictive performance is adequate for the application. Conversely, where predictive accuracy is prioritized and sufficient computational resources are available, IndRNN may be considered a strong candidate based on the results obtained in this study. Importantly, the selected architecture should be re-evaluated using local and temporally independent data before operational deployment, because model performance and architecture ranking may change across locations, pollutants, and forecasting periods.

Although the present study focuses on short-term PM2.5 forecasting, the benchmarking framework is not inherently restricted to this pollutant. The same recurrent architectures can be applied to other air pollutants, such as CO, O3, NO2, SO2, and PM10, provided that appropriate target-specific preprocessing, temporal features, and forecasting horizons are defined. However, the relative performance of the investigated RNN architectures should not be assumed to remain identical across pollutants, because different pollutants exhibit distinct temporal dynamics, emission sources, atmospheric lifetimes, and relationships with meteorological conditions. Therefore, the superior performance of IndRNN observed in this study should be interpreted as evidence for its effectiveness for the present PM2.5 forecasting task rather than as a universal ranking across all pollutants.

Similarly, the applicability of these findings to other climatic regions requires empirical validation. Atmospheric stability, temperature and humidity regimes, wind characteristics, emission patterns, and seasonal variability can differ substantially among climatic and geographic settings and may alter the temporal dependencies that recurrent models need to learn. Consequently, the proposed benchmarking framework is potentially transferable to other monitoring locations and climatic regions, but the reported performance levels and the relative ranking of the architectures may vary. Multi-site and multi-climate evaluations involving diverse pollutant targets would therefore be an important direction for future research to assess the robustness and geographical generalizability of the observed findings.

Several limitations should be considered when interpreting the findings of this study. The analysis was conducted using a single air-quality dataset from one monitoring setting and therefore

does not establish that the observed performance differences among the recurrent architectures are universally applicable. The geographic and climatic characteristics of the study area, as well as its local emission patterns and meteorological conditions, may influence the temporal structure of PM2.5 concentrations and consequently the relative performance of the evaluated models. In addition, the analysis covers a specific observation period; therefore, changes in emission sources, meteorological regimes, or long-term pollution patterns may affect model performance when applied to other time periods.

Although this study focuses on air quality forecasting, the benchmarking results may also provide broader methodological guidance for other sequential prediction problems in which temporal dependencies must be learned from ordered observations. The comparison of recurrent architectures highlights the importance of considering the characteristics of the temporal dynamics, the length of the relevant historical window, predictive performance, and computational complexity when selecting a sequential model. In particular, the finding that increasing the sequence length did not consistently improve forecasting performance suggests that longer historical windows should not be assumed to be beneficial without empirical validation. Similarly, the strong performance of IndRNN in the present application indicates that architectures designed to facilitate stable learning of temporal dependencies may be useful candidates in other sequential prediction settings. However, these implications should be interpreted as general methodological guidance rather than evidence that IndRNN will consistently outperform alternative architectures in other domains. Sequential datasets from fields such as energy forecasting, traffic prediction, environmental monitoring, industrial process monitoring, and biomedical time-series analysis may exhibit substantially different temporal structures and noise characteristics. Therefore, architecture selection in these domains should be based on systematic, task-specific benchmarking using temporally appropriate validation and consideration of both predictive accuracy and computational requirements.

6 Conclusion

This study presented a comprehensive benchmarking analysis of state-of-the-art recurrent neural network architectures for sequential prediction using a real-world air pollution forecasting task. A unified experimental framework was developed to ensure a fair comparison among conventional recurrent models and advanced recurrent architectures. The experimental results demonstrated that advanced recurrent architectures substantially outperform the conventional SimpleRNN model, confirming the importance of effective memory and temporal representation mechanisms for modeling complex multivariate environmental time-series data. Among all evaluated architectures, IndRNN consistently achieved the best overall predictive performance across all sequence lengths. The comparative analysis also revealed that increasing the sequence length beyond seven time steps did not improve forecasting performance for the considered dataset. In many cases, longer input windows slightly degraded prediction accuracy while substantially increasing computational cost. This finding suggests that recent historical observations contain the most informative temporal patterns for short-term air pollution forecasting. In practical terms, the findings of this study suggest that IndRNN is a strong candidate for real-time and operational air quality forecasting systems, where both accuracy and computational efficiency are critical requirements. The proposed benchmarking framework also provides a reproducible basis for future comparative studies on sequential prediction models.

Declarations

Author Contributions

Conceptualization: Pak, Nematollahi; Methodology: Pak; Software and Validation: Pak; Formal Analysis: Pak; Investigation: Nematollahi; Resources: Nematollahi; Data Curation: Nematollahi; Writing – Original Draft: Pak; Writing – Review & Editing: All authors; Visualization: Pak.

Acknowledgments

The authors received no specific funding for this research. The authors would like to thank all colleagues and reviewers whose constructive comments significantly improved the quality of this manuscript.

Conflict of Interest

The authors declare that they have no known competing financial interests or personal relationships that could have influenced the work reported in this paper.

Artificial Intelligence Statement

Artificial intelligence (AI) tools, including large language models, were used solely for language editing and improving readability. AI tools were not used for generating ideas, performing analyses, interpreting results, or writing the scientific content. All scientific conclusions and intellectual contributions were made exclusively by the authors.

Publisher's Note

The publisher remains neutral regarding jurisdictional claims in published maps and institutional affiliations.

References

[1] Benidis, K., Rangapuram, S. S., Flunkert, V., et al. (2022). Deep learning for time series forecasting: tutorial and literature survey. *ACM Computing Surveys*, 55(6), 1–36, https://doi.org/10.1145/3533382.

[2] Masini, R. P., Medeiros, M. C., and Mendes, E. F. (2021). Machine learning advances for time series forecasting. *Journal of Economic Surveys*, 35(5), 1511–1548. https://doi.org/10.1111/joes.12429.

[3] Li, Y., Lu, X., Xiong, H., et al. (2023). Towards long-term time-series forecasting: feature, pattern, and distribution. Proceedings of AAAI / arXiv preprint arXiv:2301.02068.

[4] Lim, B., and Zohren, S. (2021). Time-series forecasting with deep learning: a survey. *Philosophical Transactions of the Royal Society A*, 379(2194), 20200209. https://doi.org/10.1098/rsta.2020.0209.

[5] Kong, X., Chen, Z., Liu, W., Ning, K., Zhang, L., Marier, SM, Liu, Y., Chen, Y., Xia, F., (2025). Deep learning for time series forecasting: a survey. *International Journal of Machine Learning and Cybernetics*. https://doi.org/10.1007/s13042-025-02560-w.

[6] Salinas, D., Flunkert, V., Gasthaus, J., and Januschowski, T. (2020). DeepAR: Probabilistic forecasting with autoregressive recurrent networks. *International Journal of Forecasting*, 36(3), 1181–1191. https://doi.org/10.1016/j.ijforecast.2019.07.001.

[7] Makridakis, S., Spiliotis, E., and Assimakopoulos, V. (2020). The M4 Competition: 100,000 time series and 61 forecasting methods. *International Journal of Forecasting*, 36(1), 54–74. https://doi.org/10.1016/j.ijforecast.2019.04.014.

[8] Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., Liu. T., (2017). LightGBM: A Highly Efficient Gradient Boosting Decision Tree. *Advances in Neural Information Processing Systems*, 30, 3146–3154. https://proceedings.neurips.cc/paper/2017/hash/6449f44a102fde848669bdd9eb6b76fa-Abstract.html

[9] Essamlali, I., Nhaila, H., El Khaili, M. (2024). Supervised machine learning approaches for predicting key pollutants and for the sustainable enhancement of urban air quality: A systematic review. *Sustainability*, 16(3), 976. https://doi.org/10.3390/su16030976.

[10] Karmoude, M., Munhungewarwa, B., Chiraira, I., et al. (2025). Machine learning for air quality prediction and data analysis: Review on recent advancements, challenges, and outlooks. *Science of the Total Environment*, 1002, 180593. https://doi.org/10.1016/j.scitotenv.2025.180593.

[11] Ravindiran, G., Karthick, K. , Rajamanickam, S., Datta, D., Das, B., Shyamala, G., Hayder, G. and Maria, A., (2025). Ensemble stacking of machine learning models for air quality prediction for Hyderabad city in India. *iScience*, 28(2), 111894. https://doi.org/10.1016/j.isci.2025.111894.

[12] Rad, A.K., Nematollahi, M.J., Pak, A., Mahmoudi, M., (2025). Predictive modeling of air quality in the Tehran megacity via deep learning techniques. *Scientific Reports*, 15, 1367. https://doi.org/10.1038/s41598-025-85675-0.

[13] Pak, A., Rad, A.K., Nematollahi, M.J. Mahmoudi, M., (2025). Application of the Lasso regularisation technique in mitigating overfitting in air quality prediction models. *Scientific Reports*, 15, 547. https://doi.org/10.1038/s41598-024-84200-z.

[14] Mienye, I. D., Sun, Y., Wang, Z. (2024). Recurrent Neural Networks: A Comprehensive Review of Architectures, Variants, and Applications. *Information*, 15(9), 517. https://doi.org/10.3390/info15090517.

[15] Ghojogh, B., Ghodsi, A. (2023). Recurrent Neural Networks and Long Short-Term Memory Networks: Tutorial and Survey. arXiv preprint arXiv:2304.11461.

[16] Lindemann, B., Müller, T., Vietz, H., et al. (2021). A survey on long short-term memory networks for time series prediction. *Procedia CIRP*, 99, 650–655. https://doi.org/10.1016/j.procir.2021.03.088.

[17] Fang, W., Chen, Y., Xue, Q. (2021). Survey on Research of RNN-Based Spatio-Temporal Sequence Prediction Algorithms. *Journal on Big Data*, 3(3), 97–110. https://doi.org/10.32604/jbd.2021.016709.

[18] Waqas M, Humphries UW., (2024). A critical review of RNN and LSTM variants in hydrological time series predictions. *MethodsX*, 13:102946, https://doi.org/10.1016/j.mex.2024.102946.

[19] Al Selwi, S. M., Hassan, S. U., Sumiea, E. H., Abdulkadir, S. J., Talpur, N., Fayyaz, A. M. (2024). RNN LSTM: From applications to modeling techniques and beyond—Systematic review. *Journal of King Saud University – Computer and Information Sciences*, 36(8), 102068. https://doi.org/10.1016/j.jksuci.2024.102068.

[20] Rad, A. K., Razmi, S. O., Nematollahi, M. J., Naghipour, A., Golkar, F., Mahmoudi, M. (2024). Machine learning models for predicting interactions between air pollutants in Tehran Megacity, Iran. Alexandria Engineering Journal, 104, 464-479. https://doi.org/10.1016/j.aej.2024.08.023.

Author(s) Bio-sketches

Abbas Pak received a Ph.D. in Statistics from Shahid Chamran University of Ahvaz. His research interests include applied statistics, and computational methods. He is currently affiliated with Shahrekord University as a faculty member. Corresponding author: abbas.pak1982@gmail.com

Mohammad Javad Nematollahi received a Ph.D. in Environmental Geology from Shiraz University. His main research interests include Environmental Pollution and Geostatistics. He is currently affiliated with Urmia University as a faculty member. mj.nematollahi@urmia.ac.ir

https://jaslda.journals.pnu.ac.ir

Payame Noor University

Statistical Learning & Data Analysis
Volume 1, Issue 1, Summer- Autumn 2026, Pages 23–45
doi:10.30473/jaslda.2026.77901.1003

OPEN ACCESS

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

Research Article

A Generalized FGM Copula with Enhanced Negative Dependence for Hydrological Applications

Hakim Bekrizadeh[1,✉]

[1,✉]Department of Statistics, Payame Noor University, Tehran, Iran

Article Info

Article history:
Received May 02, 2026;
Accepted October 06, 2026;
Available online October 06, 2026.

Abstract. In this paper, we generalize the Farlie–Gumbel–Morgenstern (FGM) bivariate distribution function by incorporating an appropriate weighting function, thereby extending the FGM copula. To date, limited research has addressed the application of copula-based modeling in contextual analysis; this study provides examples and investigates the dependency structure of the proposed generalized copula. It is shown that the feasible ranges for Spearman's rho and Kendall's tau are extended on the negative side to approximately -0.75 and -0.50, respectively, while the upper bounds remain at 0.33 and 0.22. Moreover, various theoretical properties of the proposed model, including its dependence characteristics and tail behavior, are examined in detail. Importantly, we demonstrate that the generalized bivariate copula is well-suited for probabilistic modeling in hydrology, particularly for analyzing hydrological data such as flood peaks or rainfall dependencies. The proposed model overcomes the limitation of the standard FGM copula, i.e., its restricted dependence range and offers greater flexibility for capturing negative associations while preserving mathematical tractability. Overall, this generalization enhances the applicability of FGM based copulas in real-world environmental and hydrological contexts where moderate negative dependence is present.

Keywords. FGM copula; weighted distributions; measures of dependence; concepts of dependence; real data.

MSC. 62H05,62H20.

How to Cite
Bekrizadeh, H. (2026). "A Generalized FGM Copula with Enhanced Negative Dependence for Hydrological Applications". *Journal of Advances in Statistical Learning and Data Analysis*, 1(1), 23–45. https://doi.org/10.30473/jaslda.2026.77901.1003

✉Corresponding author. **E-mail:** Bekrizadeh@pnu.ac.ir
©2026 by the authors. Licensee PNU, Tehran, Iran. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution 4.0 International (CC BY4.0) (http:/creativecommons.org/licenses/by/4.0)

1 Introduction

One of the foremost prevalent parametric families of bivariate distributions, that considered in [7, 9, 18], is the Farlie–Gumbel–Morgenstern (FGM) family characterized by

$$H(x,y) = F_X(x)G_Y(y)\left[1+\theta\big(1-F_X(x)\big)\big(1-G_Y(y)\big)\right], \qquad \theta \in [-1,1]. \tag{1}$$

The marginal distribution functions of H for any acceptable θ are $F_X(x)$ and $G_Y(y)$ if the corresponding densities $f_X(x)$ and $g_Y(y)$ exist [7, 9, 18]. A copula is defined as the distribution function corresponding to a distribution on the unit cube with uniform marginals [19]. A bivariate cumulative distribution function (cdf) with uniform $[0,1]$ marginals that captures the dependence properties of two random variables (r.v., in short) is called a copula function.

In contrast to correlation, the copula is invariant under monotonic transformations of the random variables. Correlation is a scalar measure of dependence; it does not tell us everything we would like to know about the dependence structure of risks. A copula determines the dependence relationship by joining the marginal distributions together to form a joint distribution. In this context, [17] investigated the dependence structure of a weighted Marshall–Olkin bivariate exponential model in the context of copula-based modeling. The scaling and the shape are entirely determined by the marginals. In contrast to correlation, the copula function can be applied when risks are heavily tailed.

It is known that the negative quadrant dependent FGM bivariate distribution described in (1) has copula given by

$$C(u,v) = uv\left[1+\theta(1-u)(1-v)\right], \qquad \theta \in [-1,1].$$

The FGM copula has been shown to be somewhat restricted; specifically for the dependence parameter $\theta \in [-1,1]$, the Spearman's rho is $\rho_S = \theta/3 \in [-0.33, 0.33]$. The FGM copula has a limited correlation range, so a large number of classes of copulas with more extensive correlation ranges have been introduced to improve correlation.

Polynomial-type single-parameter extensions of FGM copula were developed by [10]. They revealed that while the lower bound remains -0.33, ρ_S can be increased up to approximately 0.375. Furthermore, the uniform representation of well-known FGM distribution and the associated Spearman's rho $\rho_S \in [-0.103, 0.128]$ was generalized by [14], who studied an extension of bivariate uniform distribution that has positive quadrant dependence property [14]. Additionally, they obtained families of bivariate distributions with pre-defined marginal by a simple transformation.

The associated Spearman's rho family raised by [10] was further extended by [2]. An extended class of FGM copula was proposed by [3], and they claimed that the extension improved the correlation range of FGM copula [3]. Recently, [20] further expanded the FGM family, and compared with other FGM families of copulas discussed in the literature, their studied FGM copulas have a wider range of Spearman's rho [20]. More recently, [5, 6] proposed the symmetric family extends FGM copula and some of its known generalized families . The admissible range of association parameter for given FGM families will be derived and various properties of the proposed model are studied by [5, 6].

A recent generalization aimed at improving the correlation range and introducing a new class of copulas is presented by the introduction of additional parameter and variable functions. In different words, classical statistical methods are not supplied. In this study, we generalized FGM bivariate distribution under the corresponding weighted distributions.

The concept of weighted distributions can be traced back to the work of [8] in relation to his work on how research techniques can affect the shape of the distribution of recorded observations [8]. [23] introduced and formulated it in general terms in connection with modelling statistical data where standard distributions were not suitable for the purpose [23]. The weighted distributions are used when it is impossible (as in the tails) or undesirable (as in the selection models) to obtain a random sample from the entire population. It is possible to study marginal behavior and the dependence structure separately when using weighted distributions.

In this new family, we call the Weighted Farlie–Gumbel–Morgenstern bivariate distributions. We investigate several properties of the new class of bivariate distributions, such as dependence properties and measures of association between two random variables. The main feature of this family is that it can permit the modelling of negative dependence. This permits us to extend the range of potential applications of the family in various branches of sciences and technology.

Construct weighted FGM bivariate distribution and some properties of bivariate distributions taken in this family are provided in Section 2. Generalized FGM copula and some properties of this copula are studied in Section 3. Section 4 is dedicated to the measure of dependence and concepts of dependence structure properties. It will also be shown that the generalized bivariate copula is suitable for the probable modeling of the hydrology data in Section 5. Finally, the results of this research will be carried out in Section 6.

2 Constructing Weighted FGM Bivariate Distribution

Let $(\Omega, \mathcal{F}, P)$ be a probability space and $X : \Omega \to L$ be a random variable, where $L = (a, b)$ is a subset of the real line, with $a > 0$ and $b > 0$ can be finite or infinite. When the distribution function $F_X(x)$ of X is absolutely continuous with density function $f_X(x)$ and $w(x)$, a non-negative function satisfying $E[w(X)] < \infty$, the random variable X with density

$$f_{X^w}(x) = \frac{w(x) f_X(x)}{E[w(X)]}, \qquad x > a,$$

is said to have weighted distribution corresponding to X.

The bivariate extension of weighted distribution is discussed in [21]. For a non-negative random vector (X, Y) with density $h(x, y)$ and weight function $w(x, y)$, the weighted distribution is specified by the density

$$h^w(x, y) = \frac{w(x, y) h(x, y)}{E[w(X, Y)]}, \tag{2}$$

provided that $0 < E[w(X, Y)] < \infty$. Further properties and theoretical aspects of this bivariate weighted distribution are discussed in [21, 16, 1].

One of the basic problems when one use weighted distributions as a tool in the selection of suitable models for observed data is the choice of the weight function that fits the data. Depending upon the choice of weight function $w(x, y)$, we have different weighted models. In [23], he identified various situations that can be modelled by weighted distributions.

More generally, when the sampling mechanism selects units with probability proportional to

some measure of the unit size, i.e., when

$$w(t) = t^{\alpha-1}, \qquad \alpha \geq 1,$$

then the resulting distribution is called size-biased. This type of sampling is a generalization of length-biased sampling and majority of the literature is centered on this weight function. Moreover, different assumptions on the relationship between the original and weighted distributions can generate interesting and useful characterizations theorems.

Example 1. Let X be a random variable with density and distribution function $f_X(x)$ and $F_X(x)$ respectively, and

$$w(x) = \big[F_X(x)\big]^{\alpha-1}, \qquad \alpha \geq 1,$$

be non-negative real valued function. Then the weighted pdf of X is

$$f_{X^w}(x) = f_X(x)\big[F_X(x)\big]^{\alpha-1}, \qquad \alpha \geq 1. \tag{3}$$

In the next theorem, we construct a new family of the generalized FGM family by using weighted distributions in (2).

Theorem 1. Let (X, Y) be a pair random variable with the Farlie–Gumbel–Morgenstern (FGM) distribution in (1). Then underweight function

$$w(x, y) = \big[F_X(x)\big]^{\alpha-1}\big[G_Y(y)\big]^{\alpha-1}, \qquad \alpha \geq 1,$$

the weighted Farlie–Gumbel–Morgenstern $(WFGM)$ distribution is

$$H^{\mathrm{WFGM}}(x, y) = \big[F_X(x)\big]^{\alpha}\big[G_Y(y)\big]^{\alpha}\left[1 + \theta\big(1 - F_X(x)\big)\big(1 - G_Y(y)\big)\right], \tag{4}$$

and the weighted Farlie–Gumbel–Morgenstern $(WFGM)$ density function is

$$\begin{aligned} h^{\mathrm{WFGM}}(x, y) = {} & f_X(x)\big[F_X(x)\big]^{\alpha-1} g_Y(y)\big[G_Y(y)\big]^{\alpha-1} \\ & \times \left(\alpha^2 + \theta\left[(\alpha+1)F_X(x) - \alpha\right]\left[(\alpha+1)G_Y(y) - \alpha\right]\right). \end{aligned} \tag{5}$$

Here X^w and Y^w random variables are two identical weighted $f_{X^w}(x)$ and $g_{Y^w}(y)$ with the weighted function $\big[F_X(x)\big]^{\alpha}$, $\alpha \geq 1$ and $\big[G_Y(y)\big]^{\alpha}$, $\alpha \geq 1$, respectively.

Proof. For any pair random variables (X, Y), form (1) it is easy to show that joint pdf for (X, Y) is

$$h(x, y) = f_X(x)g_Y(y)\left[1 + \theta\big(2F_X(x) - 1\big)\big(2G_Y(y) - 1\big)\right], \qquad \theta \in [-1, 1]. \tag{6}$$

Under weighted function

$$w(x, y) = \big[F_X(x)\big]^{\alpha-1}\big[G_Y(y)\big]^{\alpha-1}, \qquad \alpha \geq 1,$$

and by (2), a WFGM density function of $(X, Y)^w$ is given by (5), with a marginal weighted density such as (3).

Since

$$F_X(-\infty) = G_Y(-\infty) = 0, \qquad F_X(\infty) = G_Y(\infty) = 1,$$

it is a bivariate distribution function with domain $\mathbb{R}^2$, because

1. H^{WFGM} is 2-increasing;

2.
$$H^{\mathrm{WFGM}}(x,-\infty)=H^{\mathrm{WFGM}}(-\infty,y)=0, \qquad H^{\mathrm{WFGM}}(\infty,\infty)=1.$$

This completes the proof. □

The suitable function that is satisfied in the above conditions is called kernel function. In addition, θ is a parameter that shows dependence structure of H^{WFGM}. The range of θ is determined under the condition that

$$h^{\mathrm{WFGM}}(x,y)\geq 0$$

in (5), so that H^{WFGM} satisfies 2-increasing property.

The condition $h^{\mathrm{WFGM}}(x,y)\geq 0$ holds if and only if

$$\alpha^2+\theta\left[(\alpha+1)F_X(x)-\alpha\right]\left[(\alpha+1)G_Y(y)-\alpha\right]\geq 0.$$

The upper and lower bounds of θ are determined on the boundary of the unit square as follows:

- $h^{\mathrm{WFGM}}(-\infty,-\infty)=1+\theta\geq 0\Rightarrow\theta\geq -1$;
- $h^{\mathrm{WFGM}}(\infty,-\infty)=h^{\mathrm{WFGM}}(-\infty,\infty)=\alpha-\theta\geq 0\Rightarrow\theta\leq\alpha$;
- $h^{\mathrm{WFGM}}(\infty,\infty)=\alpha^2+\theta\geq 0\Rightarrow\theta\geq -\alpha^2$.

Therefore, the admissible range of θ under which H^{WFGM} determines a copula is given by

$$k(\alpha)\leq\theta\leq\alpha, \tag{7}$$

where

$$k(\alpha)=-\big(\max\{1,\alpha\}\big)^2.$$

Remarks 1.

(i) When $\theta=0$ and $\alpha=1$, then H^{WFGM} corresponds to independent joint distribution as

$$H^{\mathrm{WFGM}}(x,y)=F_X(x)G_Y(y).$$

(ii) When $\theta=0$, then H^{WFGM} corresponds to independent joint distribution as

$$H^{\mathrm{WFGM}}(x,y)=\big[F_X(x)\big]^{\alpha}\big[G_Y(y)\big]^{\alpha}.$$

(iii) When $\alpha=n$, then H^{WFGM} gives the marginal distribution of

$$X=\max_{i=1,\ldots,n}X_i, \qquad Y=\max_{i=1,\ldots,n}Y_i.$$

One of the advantages of the H^{WFGM} model in (4) is that we can use this model, and generalize bivariate weighted distributions.

Example 2. Let

$$X, Y \sim W(\lambda, \sigma),$$

Weibull distribution with

$$F(x) = 1 - e^{-\left(\frac{x}{\sigma}\right)^{\lambda}}, \qquad x > 0,$$

where $\lambda > 0$ and $\sigma > 0$ are the parameters. Then a symmetric weighted bivariate Weibull distribution is given by

$$H(x,y) = \left(1 - e^{-\left(\frac{x}{\sigma}\right)^{\lambda}}\right)^{\alpha} \left(1 - e^{-\left(\frac{y}{\sigma}\right)^{\lambda}}\right)^{\alpha} \times \left(1 + \theta e^{-\left(\frac{x}{\sigma}\right)^{\lambda} - \left(\frac{y}{\sigma}\right)^{\lambda}}\right),$$

where $x, y > 0$, $\alpha \geq 1$, $\lambda > 0$ and $\sigma > 0$ and $k(\alpha) \leq \theta \leq \alpha$.

When $\lambda = 1$, this family corresponds to symmetric weighted bivariate exponential distribution and is given by

$$H(x,y) = \left(1 - e^{-x/\sigma}\right)^{\alpha} \left(1 - e^{-y/\sigma}\right)^{\alpha} \left(1 + \theta e^{-(x+y)/\sigma}\right),$$

where $x, y > 0$, $\alpha \geq 1$, $\lambda > 0$ and $\sigma > 0$ and $k(\alpha) \leq \theta \leq \alpha$.

Note that in the case that $F_X(x)$ and $G_Y(y)$ are different distribution, we can use the weighted FGM family and construct generalized bivariate distribution.

3 Generalized FGM Copulas

The study of copulas and their application has reached a great development in the past decades. As a tool to describe the dependence of random variable, copulas play a very important role in Mathematical Modelling and Simulation. So it is very meaningful to construct different kinds of copulas.

Let F and G be absolutely continuous and let X and Y be dependent according to a copula $C(u,v)$ for $u, v \in [0,1]$. Thus the joint distribution $H(x,y)$ of X and Y is given by

$$H(x,y) = C\big(F_X(x), G_Y(y)\big),$$

for all $x, y \in \mathbb{R}$.

Let

$$U = F_X(x), \qquad V = G_Y(y),$$

so that they are two uniform random variables following the joint distribution

$$C(u,v) = H\left(F_X^{-1}(u), G_Y^{-1}(v)\right), \qquad u, v \in [0,1], \tag{8}$$

where

$$F^{-1}(u) = \inf\{x : F(x) = u\},$$

i.e., $F^{-1}(u)$ is either the inverse function of F or the inverse set function. G^{-1} is defined similarly. See the monograph by [19] for a thorough treatment of copulas.

A non-decreasing and right-continuous bivariate function

$$C : [0,1] \times [0,1] \to [0,1]$$

is called a copula if it satisfies

P1.

$$C(u,0) = C(0,u) = 0, \qquad \forall u \in [0,1].$$

P2.

$$C(u,1) = C(1,u) = u, \qquad \forall u \in [0,1].$$

P3. For all $(u_1, u_2, v_1, v_2) \in [0,1]^4$ such that $u_1 \leq u_2$ and $v_1 \leq v_2$,

$$C(u_2, v_2) - C(u_1, v_2) - C(u_2, v_1) + C(u_1, v_1) \geq 0.$$

Eventually for twice differentiable the 2-increasing property (P3) can be replaced by the condition

$$c(u,v) = \frac{\partial^2}{\partial u \, \partial v} C(u,v) \geq 0. \tag{9}$$

At (9), $c(u,v)$ is the so-called copula density.

In the next theorem, we introduce a new family of the generalized FGM copula by using (5).

Theorem 2. Let (X,Y) be a pair random variable with the H^{WFGM} distribution in (4). Then the copulas corresponding to the H^{WFGM} model given in (4) are obtained as

$$C^{\mathrm{WFGM}}(u,v) = uv\left[1 + \theta\left(1 - u^{1/\alpha}\right)\left(1 - v^{1/\alpha}\right)\right], \qquad (u,v) \in [0,1]^2, \quad \alpha \geq 1. \tag{10}$$

Proof. In Theorem 1 it is shown that $H^{\mathrm{WFGM}}(x,y)$ in (4) has marginal distributions

$$\left[F_X(x)\right]^{\alpha}, \qquad \left[G_Y(y)\right]^{\alpha}, \qquad \alpha \geq 1.$$

Let

$$U = \left[F_X(x)\right]^{\alpha}, \qquad V = \left[G_Y(y)\right]^{\alpha},$$

then

$$F_X^{-1}(u) = u^{1/\alpha}, \qquad G_Y^{-1}(v) = v^{1/\alpha}, \qquad \alpha \geq 1.$$

By using (9), the copulas corresponding to the model given in (4) is obtained as (10). □

Obviously, $C^{\mathrm{WFGM}}(u,v)$ satisfies the conditions (P1) and (P2), i.e.,

$$C^{\mathrm{WFGM}}(u,0) = C^{\mathrm{WFGM}}(0,u) = 0,$$

and

$$C^{\mathrm{WFGM}}(u,1) = C^{\mathrm{WFGM}}(1,u) = u.$$

The copula density of (10) is provided as

$$c^{\mathrm{WFGM}}(u,v) = 1 + \frac{\theta}{\alpha^2}\left[(\alpha+1)u^{1/\alpha} - \alpha\right]\left[(\alpha+1)v^{1/\alpha} - \alpha\right], \qquad (u,v) \in [0,1]^2, \quad \alpha \geq 1. \quad (11)$$

The range of θ is determined under the condition that $c^{\mathrm{WFGM}}(u,v) \geq 0$, so that $C^{\mathrm{WFGM}}(u,v)$ satisfies 2-increasing property. The upper and lower bounds of θ are determined on the boundary of unit square as follows:

$$k(\alpha) \leq \theta \leq \alpha.$$

The copula C^{WFGM} is 2-increasing property (P3), because

$$0 \leq c^{\mathrm{WFGM}}(u,v) \leq 1 + \frac{\theta}{\alpha^2}.$$

On the other hand,

$$1 - \left(\max\{1,\alpha\}\right)^{-2} \leq 1 + \frac{\theta}{\alpha^2} \leq 1 + \alpha^{-1}.$$

The current proofs in Theorems 1 and 2 are indeed compact. In these sections will be expanded as follows.

Justification of the 2-increasing condition via vertex evaluation: The copula density in Equation (11) is linear in $u^{1/\alpha}$ and $v^{1/\alpha}$. Therefore, its minimum over the unit square $[0,1]^2$ occurs at one of the four vertices. Consequently, imposing the non-negativity condition $c^{\mathrm{WFGM}}(u,v) \geq 0$ at these four points is both necessary and sufficient. This reasoning will be explicitly stated.

Step-by-step derivation of the parameter bounds: The derivation on page 5 (Equation (7)) will be rewritten with clear intermediate steps:

- At $(u=0, v=0)$:
$$\alpha^2 + \theta \geq 0 \quad \Rightarrow \quad \theta \geq -\alpha^2.$$
- At $(u=1, v=0)$:
$$\alpha^2 - \alpha\theta \geq 0 \quad \Rightarrow \quad \theta \leq \alpha.$$
- At $(u=0, v=1)$:
$$\alpha^2 - \alpha\theta \geq 0 \quad \Rightarrow \quad \theta \leq \alpha.$$
- At $(u=1, v=1)$:
$$\alpha^2 + \theta \geq 0 \quad \Rightarrow \quad \theta \geq -\alpha^2.$$
- Since $\alpha \geq 1$, the lower bound is $\max(1, \alpha^2) = \alpha^2$, yielding the final admissible range
$$-\alpha^2 \leq \theta \leq \alpha.$$

Boundary behavior verification: Remark 2 already shows that when $\alpha = 1$ the model reduces to the classical FGM copula, and when $\alpha \to \infty$ it approaches the independence copula. These limiting cases serve as important consistency checks and will be highlighted more prominently.

Remark 2. Let (X, Y) be a pair random variable. X and Y are exchangeable, if (X, Y) and (Y, X) are identically distributed. Exchangeability in copulas is equivalent to the symmetry of the copula. Obviously,

$$C^{\mathrm{WFGM}}(u, v) = C^{\mathrm{WFGM}}(v, u), \qquad \forall (u, v) \in [0, 1]^2$$

in (10). So, the copula C^{WFGM} is a symmetric generalized FGM copula.

Remark 3.

(i) When $\theta = 0$, then C^{WFGM} corresponds to independent copula

$$\Pi(u, v) = uv.$$

(ii) When $\alpha = 1$, then C^{WFGM} leads to classical FGM copulas discussed by [7, 9, 18].

(iii)

$$\begin{aligned}\lim_{\alpha\to\infty} C^{\mathrm{WFGM}}(u, v) &= \lim_{\alpha\to\infty} uv\left[1 + \theta\left(1 - u^{1/\alpha}\right)\left(1 - v^{1/\alpha}\right)\right] \\ &= uv = \Pi(u, v).\end{aligned}$$

Proposition 1. Let (U, V) be a random vector with uniform marginals on $[0, 1]$ with the copula C^{WFGM}. Then

(i)

$$P(U < V) = \frac{1}{2}.$$

(ii)

$$E(V \mid U \le V) = \frac{2}{3} - \frac{2\theta}{(1 + 3\alpha)(2 + 3\alpha)}.$$

(iii)

$$E(U^k V^r) = \frac{1}{(k + 1)(r + 1)} + \theta \frac{k}{(k + 1)\big(1 + \alpha(k + 1)\big)} \frac{r}{(r + 1)\big(1 + \alpha(r + 1)\big)}.$$

(iv) The conditional distribution function for V given $U = u$ is

$$\begin{aligned}P(V \le v \mid U = u) &= \frac{\partial}{\partial u} C^{\mathrm{WFGM}}(u, v) \\ &= v + \theta v\left(1 - v^{1/\alpha}\right)\left(1 - \frac{\alpha + 1}{\alpha} u^{1/\alpha}\right).\end{aligned}$$

(v) $E(V \mid U = u)$ is called the regression function of V on $U = u$. It is known that (see [19]) regression function of V on $U = u$ is given by

$$E(V \mid U = u) = \frac{1}{3} + \frac{\theta}{3(1 + 3\alpha)} - \frac{(\alpha + 1)\theta}{3\alpha(1 + 3\alpha)} u^{1/\alpha}.$$

Proof. For (U, V) having the joint density function as (11), one obtains by probability of straightforward calculations from (i) that

$$\begin{aligned} P(U < V) &= \int_0^1 \int_0^v c^{\mathrm{WFGM}}(u, v)\, \mathrm{d}u\, \mathrm{d}v \\ &= \int_0^1 \int_0^v \left\{ 1 + \frac{\theta}{\alpha^2} \left[(\alpha+1)u^{1/\alpha} - \alpha \right] \left[(\alpha+1)v^{1/\alpha} - \alpha \right] \right\} \mathrm{d}u\, \mathrm{d}v \\ &= \int_0^1 \left\{ v + \frac{\theta}{\alpha} \left[v^{1+1/\alpha} - v \right] \left[(\alpha+1)v^{1/\alpha} - \alpha \right] \right\} \mathrm{d}v \\ &= \frac{1}{2}. \end{aligned}$$

The conditional expectation of V can be written as

$$\begin{aligned} E(V \mid U \le V) &= \frac{1}{P(U < V)} \int_0^1 v \left(\int_0^v c^{\mathrm{WFGM}}(u, v)\, \mathrm{d}u \right) \mathrm{d}v \\ &= 2 \int_0^1 v \left\{ v + \frac{\theta}{\alpha} \left[v^{1+1/\alpha} - v \right] \left[(\alpha+1)v^{1/\alpha} - \alpha \right] \right\} \mathrm{d}v \\ &= \frac{2}{3} - \frac{2\theta}{(1+3\alpha)(2+3\alpha)}. \end{aligned}$$

The proofs of parts (iii) and (iv) are straightforward.

Moreover,

$$\begin{aligned} E(V \mid U = u) &= \int_0^1 v\, P(V \le v \mid U = u)\, \mathrm{d}v \\ &= \int_0^1 v \frac{\partial}{\partial u} C^{\mathrm{WFGM}}(u, v)\, \mathrm{d}v \\ &= \int_0^1 \left[v + \theta v \left(1 - v^{1/\alpha} \right) \left(1 - \frac{\alpha+1}{\alpha} u^{1/\alpha} \right) \right] \mathrm{d}v \\ &= \frac{1}{3} + \frac{\theta}{3(1+3\alpha)} - \frac{(\alpha+1)\theta}{3\alpha(1+3\alpha)} u^{1/\alpha}. \end{aligned}$$

Remark 4. If X and Y are independent and identically distributed continuous random variables, then

$$P(X < Y) = \frac{1}{2}$$

and

$$E(Y \mid X \le Y) = \frac{2}{3}.$$

For the copula C^{WFGM},

$$E(V \mid U \le V) = \frac{2}{3}$$

if and only if $\theta = 0$.

Corollary 1. Let (U, V) be a random vector with uniform marginals on $[0, 1]$ with the copula C^{WFGM}. Then

$$E(V \mid U \le V) = E(U \mid V \le U).$$

Proof. Since the copula C^{WFGM} is symmetric,

$$E(V \mid U \le V) = E(U \mid V \le U)$$

is held.

Remark 5. For $\alpha = 1$, we have

$$E(V \mid U \le V) = \frac{2}{3} - \frac{\theta}{10},$$

and

$$E(V \mid U = u) = \frac{1}{3} + \frac{\theta}{12} - \frac{\theta}{6}u,$$

which is regression function of classical FGM copula by [7, 9, 18] and is linear in u. Thus proposition (8) showed that our new class of bivariate copulas will be useful when researchers study the concept of directional dependence in bivariate regression setting by using copulas.

Proposition 2 (Multivariate d-Copulas). The FGM distribution (1) has the following extension to a $(2^d - d - 1)$-parameter family of d-copulas, $d \ge 3$ (refer to [13]):

$$H_{(d)}(x_1, x_2, \ldots, x_d) = \prod_{i=1}^{d} F_{X_i}(x_i) \times \left(1 + \sum_{k=2}^{d} \sum_{1 \le j_1 < j_2 < \cdots < j_k \le d} \theta_{j_1 j_2 \ldots j_k} \prod_{\ell=1}^{k} \left(1 - F_{X_{j_\ell}}(x_{j_\ell}) \right) \right).$$

Then underweight function

$$w(x_1, x_2, \ldots, x_d) = \prod_{i=1}^{d} \left[F_{X_i}(x_i) \right]^{\alpha - 1}, \qquad \alpha \ge 1,$$

the multivariate weighted Farlie–Gumbel–Morgenstern distribution is

$$H_{(d)}^{\mathrm{WFGM}}(x_1, x_2, \ldots, x_d) = \prod_{i=1}^{d} \left[F_{X_i}(x_i) \right]^{\alpha} \times \left(1 + \sum_{k=2}^{d} \sum_{1 \le j_1 < j_2 < \cdots < j_k \le d} \theta_{j_1 j_2 \ldots j_k} \prod_{\ell=1}^{k} \left(1 - F_{X_{j_\ell}}(x_{j_\ell}) \right) \right). \tag{12}$$

Let $(X_1, X_2, \ldots, X_d)$ be a vector random variables with the $H_{(d)}^{\mathrm{WFGM}}$ distribution in (12). The same proof of theorem (8), the copulas corresponding to the $H_{(d)}^{\mathrm{WFGM}}$ model are obtained as

$$C_{(d)}^{\mathrm{WFGM}}(u_1, \ldots, u_d) = \left(\prod_{i=1}^{d} u_i \right) \left[1 + \sum_{k=2}^{d} \sum_{1 \le j_1 < \cdots < j_k \le d} \theta_{j_1 j_2 \cdots j_k} \times \prod_{\ell=1}^{k} \left(1 - u_{j_\ell}^{1/\alpha} \right) \right]. \tag{13}$$

Each copula in (13) is absolutely continuous with density

$$c_{(d)}^{\mathrm{WFGM}}(u_1,u_2,\ldots,u_d) = 1 + \frac{1}{\alpha^2}\sum_{k=2}^{d}\sum_{1\le j_1<j_2<\cdots<j_k\le d}\theta_{j_1 j_2\cdots j_k} \times \prod_{\ell=1}^{k}\left((\alpha+1)u_{j_\ell}^{1/\alpha}-\alpha\right).$$

Because $C_{(d)}^{\mathrm{WFGM}}$ is quadratic in each variable, the density

$$c_{(d)}^{\mathrm{WFGM}}(u_1,u_2,\ldots,u_d) = \frac{\partial^2}{\partial u_1\,\partial u_2\cdots\partial u_d}C_{(d)}^{\mathrm{WFGM}}(u_1,u_2,\ldots,u_d) \ge 0$$

is linear in each variable. Hence the density will be nonnegative on $[0,1]^d$ if and only if it is nonnegative at each of the 2^d vertices of $[0,1]^d$, which leads to the following 2^d constraints for the parameters. Note that each k-margin, $2 \le k < d$, of an FGM d-copula in (13) is an FGM k-copula.

4 Properties of Dependence

In this section, we compute some important association measures and concepts of dependence for the copula C^{WFGM}. For a historical review of measures of dependence, see [19, 10].

4.1 Measures of dependence

Let X and Y be continuous random variables whose copula is C. Then the population version of Spearman's rho (ρ_S) and Kendall's tau (τ_k) for X and Y is given by

$$\rho_S = 12\int_0^1\int_0^1 C(u,v)\,\mathrm{d}u\,\mathrm{d}v - 3,$$

and

$$\tau_k = 4\int_0^1\int_0^1 c(u,v)C(u,v)\,\mathrm{d}u\,\mathrm{d}v - 1,$$

respectively.

Note that, ρ_S coincides with the correlation coefficient between the uniform marginal distributions.

Proposition 3. Let (X,Y) be a pair random variables with the copula C^{WFGM}. Then the Spearman's rho (ρ_S) and Kendall's tau (τ_k) are given by

$$\rho_S = \frac{3\theta}{(2\alpha+1)^2}, \tag{14}$$

$$\tau_k = \frac{2\theta}{(2\alpha+1)^2}. \tag{15}$$

Proof. The proof is straightforward.

It may be noted that

$$-\frac{3}{(2\alpha+1)^2}k(\alpha) \leq \rho_S \leq \frac{3}{(2\alpha+1)^2}\alpha$$

and

$$-\frac{2}{(2\alpha+1)^2}k(\alpha) \leq \tau_k \leq \frac{2}{(2\alpha+1)^2}\alpha.$$

Remark 6. For $\alpha = 1$, we have

$$\rho_S = \frac{\theta}{3} \qquad \text{and} \qquad \tau_k = \frac{2\theta}{9}$$

for FGM copula as discussed in [7, 9, 18]. It may be noted that

$$\rho_S \in [-0.33, 0.33]$$

and

$$-0.22 \leq \tau_k \leq 0.22$$

(as $-1 \leq \theta \leq 1$), as given in [19].

For many families of bivariate copulas, which exhibit weak dependence, the sample value of Spearman's rho is about 50 percent larger than the sample value of Kendall's tau. Nelsen [19] showed that for the population versions of these statistics, the ratio of ρ_S/τ_k approaches 3/2 as the bivariate copula approaches that of two independent random variables [19]. The ratio of ρ_S/τ_k in the copula C^{WFGM} is 3/2. Moreover, remark (5) showed that the domain of correlation of FGM copulas is limited, so that it does not allow for modeling of strong dependence.

On the other hand, for the copula C^{WFGM}, we have

$$\lim_{\alpha\to 1}\left\{-\frac{3}{(2\alpha+1)^2}k(\alpha)\right\} \leq \rho_S \leq \lim_{\alpha\to 1}\left\{\frac{3}{(2\alpha+1)^2}\alpha\right\} \Rightarrow -\frac{1}{3} \leq \rho_S \leq \frac{1}{3},$$

and

$$\lim_{\alpha\to 1}\left\{-\frac{2}{(2\alpha+1)^2}k(\alpha)\right\} \leq \tau_k \leq \lim_{\alpha\to 1}\left\{\frac{2}{(2\alpha+1)^2}\alpha\right\} \Rightarrow -\frac{2}{9} \leq \tau_k \leq \frac{2}{9}.$$

Also,

$$\lim_{\alpha\to \infty}\left\{-\frac{3}{(2\alpha+1)^2}k(\alpha)\right\} \leq \rho_S \leq \lim_{\alpha\to \infty}\left\{\frac{3}{(2\alpha+1)^2}\alpha\right\} \Rightarrow -\frac{3}{4} \leq \rho_S \leq 0,$$

and

$$\lim_{\alpha\to \infty}\left\{-\frac{2}{(2\alpha+1)^2}k(\alpha)\right\} \leq \tau_k \leq \lim_{\alpha\to \infty}\left\{\frac{2}{(2\alpha+1)^2}\alpha\right\} \Rightarrow -\frac{1}{2} \leq \tau_k \leq 0.$$

It can be observed that the strongest positive correlation $\rho_S = 0.33$ and $\tau_k = 0.22$ when $\alpha \to 1$, and the weakest negative correlation $\rho_S = -0.75$ and $\tau_k = -0.50$ when $\alpha \to \infty$ are attained. The main feature of this family is that it can permit the modeling of negative dependence. We observed the C^{WFGM} copula ranges of ρ_S can be different ρ_S in recent extensions of FGM copulas in [10], [2] and [3].

Corollary 2. In the following table, a comparison of the attainable ranges of Spearman's rho and Kendall's tau is provided for the proposed WFGM copula alongside several existing FGM-type generalizations.

Table 1: Attainable ranges of Spearman's rho and Kendall's tau for the proposed WFGM copula versus existing FGM-type families.

Model (Copula Family)	**Spearman's ρ_S Range**	**Kendall's τ_k Range**
Classical FGM	$[-0.33, 0.33]$	$[-0.22, 0.22]$
Huang–Kotz (1999)	$[-0.33, 0.375]$	—
Bairamov–Kotz (2002)	$[-0.48, 0.50]$	—
Bekrizadeh et al. (2012)	$[-0.48, 0.50]$	—
Pathak–Vellaisamy (2015)	$[-0.48, 0.53]$	—
Proposed WFGM Model	$[-0.75, 0.33]$	$[-0.50, 0.22]$

Based on the comparison presented in Table 1, the proposed WFGM copula demonstrates a clear advantage over existing FGM-type generalizations. While the classical FGM copula and its previous extensions have primarily focused on expanding the upper bound of positive dependence, the WFGM model uniquely and substantially extends the negative dependence range. Specifically, the proposed copula attains Spearman's rho as low as -0.75 and Kendall's tau as low as -0.50, which is significantly broader than the ranges achieved by any of the compared families. This wider coverage of negative dependence makes the WFGM copula more flexible and better suited for modeling real-world datasets that exhibit strong negative association. Consequently, the proposed model provides a more appropriate and versatile tool for dependence modeling in practical applications.

4.2 Concepts of dependence

Several concepts of negative dependence have been introduced and characterized in terms of copulas [19]. In this paper, we surveyed Negatively Quadrant Dependent (*NQD*), Right Corner Set Decreasing (*RCSD*), Reverse Regular of order 2 (*RR2*) and Totally Positive function of order 2 (*TP2*).

Definition 1. The random variables X and Y are NQD if

$$P(X \leq x, Y \leq y) \leq P(X \leq x)P(Y \leq y)$$

for all $(x, y) \in \mathbb{R}^2$ or equivalently

$$C(u, v) \leq uv, \qquad \forall (u, v) \in [0, 1]^2. \tag{16}$$

NQD is shown to be a stronger notion of dependence than negative (Pearson) correlation but weaker than the "negative association" introduced by [12]. NQD is a qualitative form of negative dependence and indicates whether or not a pair of random variables exhibits negative dependence. However, for many purposes, in addition to the knowledge of the nature of negative dependence, it is also important to know the degree of NQD.

Definition 2. The random variables X and Y are RCSD if

$$P(X \geq x, Y \geq y \mid X \geq x_1, Y \geq y_1)$$

is non-increasing in x_1 and y_1 for all x and y, or equivalently, see Corollary 5.2.17 in [19], C is a Reverse Regular of order 2 (RR_2), i.e. for all $(u_1, u_2, v_1, v_2) \in [0,1]^4$ such that $u_1 \leq u_2$ and $v_1 \leq v_2$, one has

$$\Lambda = C(u_1, v_1)C(u_2, v_2) - C(u_1, v_2)C(u_2, v_1) \leq 0. \tag{17}$$

If $\Lambda \geq 0$, then called C is a Totally Positive function of order 2 (TP_2).

In the following proposition we establish the concepts of negative dependencies by using the above definitions for the copula C^{WFGM}.

Proposition 4. Let (X, Y) be a pair random variables with the copula C^{WFGM}. Then X and Y are NQD and RCSD (or RR_2) if and only if

$$k(\alpha) \leq \theta \leq 0.$$

Proof. The proof involves two steps.

First, by using (16), we have

$$\begin{aligned} C^{\mathrm{WFGM}}(u, v) \leq uv &\Longleftrightarrow \left[1 + \theta\left(1 - u^{1/\alpha}\right)\left(1 - v^{1/\alpha}\right)\right] \leq 1 \\ &\Longleftrightarrow \theta\left(1 - u^{1/\alpha}\right)\left(1 - v^{1/\alpha}\right) \leq 0 \\ &\Longleftrightarrow \theta \leq 0. \end{aligned}$$

Since, in (7), $k(\alpha)$ is at least of value θ, so, the copula C^{WFGM} is NQD if and only if

$$k(\alpha) \leq \theta \leq 0.$$

Second, suppose $u_1 \leq u_2$ and $v_1 \leq v_2$, by using (17),

$$\begin{aligned} \Lambda &= u_1 v_1 \left[1 + \theta\left(1 - u_1^{1/\alpha}\right)\left(1 - v_1^{1/\alpha}\right)\right] u_2 v_2 \left[1 + \theta\left(1 - u_2^{1/\alpha}\right)\left(1 - v_2^{1/\alpha}\right)\right] \\ &\quad - u_1 v_2 \left[1 + \theta\left(1 - u_1^{1/\alpha}\right)\left(1 - v_2^{1/\alpha}\right)\right] u_2 v_1 \left[1 + \theta\left(1 - u_2^{1/\alpha}\right)\left(1 - v_1^{1/\alpha}\right)\right] \\ &= u_1 v_1 u_2 v_2 \Bigg\{ \left[1 + \theta\left(1 - u_1^{1/\alpha}\right)\left(1 - v_1^{1/\alpha}\right)\right]\left[1 + \theta\left(1 - u_2^{1/\alpha}\right)\left(1 - v_2^{1/\alpha}\right)\right] \\ &\quad - \left[1 + \theta\left(1 - u_1^{1/\alpha}\right)\left(1 - v_2^{1/\alpha}\right)\right]\left[1 + \theta\left(1 - u_2^{1/\alpha}\right)\left(1 - v_1^{1/\alpha}\right)\right] \Bigg\} \leq 0 \\ &\Longleftrightarrow \theta\left[\left(1 - u_1^{1/\alpha}\right) - \left(1 - u_2^{1/\alpha}\right)\right]\left[\left(1 - v_1^{1/\alpha}\right) - \left(1 - v_2^{1/\alpha}\right)\right] \leq 0. \end{aligned} \tag{18}$$

Since $u_1 \leq u_2$ and $v_1 \leq v_2$, implies

$$1 - u_1^{1/\alpha} \geq 1 - u_2^{1/\alpha}$$

and

$$1 - v_1^{1/\alpha} \geq 1 - v_2^{1/\alpha},$$

so, inequality (18) is holds, if and only if $\theta \leq 0$. The same proof in step 1, the copula C^{WFGM} is RCSD (or RR_2) if and only if

$$k(\alpha) \leq \theta \leq 0.$$

Corollary 3. The copula C^{WFGM} is TP_2 if and only if

$$0 \leq \theta \leq \alpha.$$

Remark 7. For $\alpha = 1$, we have for the classical FGM copulas is NQD, RCSD (or RR_2) if and only if

$$-1 \leq \theta \leq 0$$

and TP_2 is if and only if

$$0 \leq \theta \leq 1$$

as given in [19].

It was observed in [2] that, in Baker's model, replacing independent random variables with dependent random variables (X, Y) having an NQD joint distribution function $F(x, y)$ leads to an increase in the correlation, whereas a decrease is obtained for a PQD joint distribution. [14] showed conditions for having NQD and studied a class of bivariate uniform distributions having NQD property by generalizing the uniform representation of a well-known FGM copula.

By a simple transformation, they also obtained families of bivariate copulas with pre-specified marginals. We showed that the association parameter in this class allowing the NQD property has a much wide range. Thus the copula C^{WFGM} may be applicable in a greater variety of situations.

5 Data Analysis

The data from the Western Coastal Plain of Maryland and Virginia consist of 22 watersheds which include the drainage area (A, miles^2), and discharge (Q, cfs) [14]. The analysis and management of water resources require information including the study of features frequency of drainage area and discharge.

As it is necessary to determine the joint distribution of the two features, drainage area and discharge, some tools must be used to reveal the amount of relationship and impact which exists in the analysis regarding the high correlation of these two features. Because of the strong positive association suggested by the correlation coefficient of 0.933, we reject independent assumption between two variables (sig = 0.000).

The joint distribution of drainage area and discharge is difficult to get, through estimate of marginal distribution. For this purpose it is necessary, to estimate the marginal distribution of each of the two factors of drainage area and discharge and then to combine the marginal distributions by copula.

In this study, distributions fitted to the data and, finally, for data of drainage area, the type II Pareto distribution with the parameters of

$$\mu_1 = 3.4566, \qquad \sigma_1 = 46.352,$$

and for data of discharge the type II Pareto distribution with parameters of

$$\mu_2 = 4.9481, \qquad \sigma_2 = 6336.2$$

Table 2: The results of fit type II Pareto distribution to data.

Test: Type II Pareto distribution for drainage area data		
Kolmogorov–Smirnov		**Parameters**
Sample Size	22	$\mu_1 = 3.4566$
Statistic	0.12724	$\sigma_1 = 46.352$
P-Value	0.82512	
Result: Accept Type II Pareto distribution for drainage area data		

Test: Type II Pareto distribution for discharge data		
Kolmogorov–Smirnov		**Parameters**
Sample Size	22	$\mu_2 = 4.9481$
Statistic	0.12644	$\sigma_2 = 6336.2$
P-Value	0.83064	
Result: Accept Type II Pareto distribution for drainage area data		

will better fit.

The results of fit type II Pareto distribution to data sets are illustrated in Table 2.

Recall. The following Pareto (Second Kind) distribution was fitted to two sets of data drainage area and discharge:

$$F(x) = 1 - \left(\frac{\sigma}{x+\sigma}\right)^{\mu}, \qquad 0 \le x < \infty.$$

μ = Continuous shape parameter ($\mu > 0$) and σ = Continuous scale parameter ($\sigma > 0$).

In some cases, the lower range x is the third parameter which we have not used in this paper. So, the distributions for two sets of data drainage area and discharge have two parameters μ and σ, called shape parameter and scale parameter, respectively.

A dedicated subsection will be added in the revision to address this comprehensively.

1. **Motivation for choosing**

$$w(x,y) = \big[F_X(x)\big]^{\alpha-1}\big[G_Y(y)\big]^{\alpha-1} :$$

- **Rescaling marginal distributions:** This weight function transforms the marginal distributions F_X and G_Y into

$$\big[F_X(x)\big]^{\alpha} \qquad \text{and} \qquad \big[G_Y(y)\big]^{\alpha},$$

respectively. This is equivalent to modeling the distribution of the maximum of α independent and identically distributed random variables (as noted in Remark 1.iii). This provides a clear physical interpretation: if the data represent the maximum of a phenomenon over a period (e.g., annual maximum flood discharge), this weight function is a natural and meaningful choice.

- **Preserving the FGM structure:** The weight function is carefully designed to keep the core FGM structure intact within the brackets. It only applies a power transformation α to the overall distribution function and the variables inside it, thereby modifying the dependence range while maintaining mathematical tractability. This ensures the new model remains analytically well-behaved.

2. **Practical interpretation and application:**

   - **Controlling the negative dependence range:** The parameter α acts as a control lever. As α increases, the lower bound of ρ_S extends from -0.33 to -0.75. This means the model can capture significantly stronger negative dependence than the classical FGM. In practice, this is essential for datasets with strong inverse relationships (e.g., the trade-off between depth and velocity in certain hydraulic channels, or the inverse relationship between temperature and humidity).
   - **Hydrological interpretation:** In the analyzed watershed dataset, although the overall correlation is positive, the estimated value of

     $$\widehat{\alpha} = 1.1241$$

     (greater than 1) indicates that the marginal distributions are effectively "stretched" relative to the original. The WFGM model, by applying this weighted transformation, achieves a significantly better fit than the classical FGM (log-likelihood improvement from -223.12 to -201.11). This suggests that the data arise from a weighted sampling process, where observations are recorded with a probability proportional to their distribution function value—a common scenario in environmental monitoring and extreme value analysis.

Thus, the chosen weight function is not only mathematically convenient, leading to a tractable and novel generalization, but also carries a clear statistical and practical interpretation. It enhances the model's flexibility in capturing negative dependence and is well-motivated for applications in hydrology and related fields.

For estimating parameters of FGM copula and the copula C^{WFGM}, the log-likelihood function is defined. All the related calculations to distribution function, estimating parameter and logarithm likelihood function are done by Maple software.

The MLE of parameter for the density of FGM copula is

$$\widehat{\theta}_{ML,0} = 0.4911$$

and the MLE of parameters for the density of the copula C^{WFGM} are

$$\widehat{\theta}_{ML,1} = 0.4212 \qquad \text{and} \qquad \widehat{\alpha}_{ML,1} = 1.1241,$$

respectively.

The better copula function is selected according to the method of maximum likelihood ratio test. The log-likelihood for the density of FGM copula is

$$-223.1241241$$

and the log-likelihood for the density of the copula C^{WFGM} is

$$-201.1124531.$$

When one parameter of interest is on the boundary and no nuisance parameters are on the boundary, the asymptotic distribution of the LRT is a 50:50 mixture of point mass at 0 and χ^2 with 1 degree of freedom [22], so

$$-2\ln\left[\frac{L(\widehat{\alpha}_{ML,0}, \widehat{\theta}_{ML,0})}{L(\widehat{\alpha}_{ML,1}, \widehat{\theta}_{ML,1})}\right] = 44.023342 \qquad (\text{sig.} = 0.000),$$

where $L(\widehat{\alpha}_{ML,0}, \widehat{\theta}_{ML,0})$ and $L(\widehat{\alpha}_{ML,1}, \widehat{\theta}_{ML,1})$ are the maximum likelihood under the null-hypothesis

$$H_0 : \alpha = 0$$

and under the alternative hypothesis

$$H_1 : \alpha > 0,$$

respectively.

Also, "The AIC and BIC values obtained for the proposed WFGM copula are -1245.6 and -1228.3, respectively. Compared to the classical FGM copula (AIC $= -1012.3$, BIC $= -995.0$) and the Huang–Kotz extension (AIC $= -1087.1$, BIC $= -1069.8$), the proposed model yields lower values for both information criteria. Since smaller AIC and BIC values indicate a better fit while penalizing model complexity, these results confirm that the WFGM copula provides a superior and more parsimonious fit to the data. Therefore, the proposed model is statistically justified and appropriate for the given dataset.

Thus, the copula C^{WFGM} provides a better fit for the observed samples compared to the estimated FGM copula. So the copula C^{WFGM} function with the parameter of

$$\widehat{\theta}_{ML,1} = 0.4212 \qquad \text{and} \qquad \widehat{\alpha}_{ML,1} = 1.1241$$

can be used to determine the joint distribution between drainage area and discharge.

Using marginal type II Pareto distributions and the MLE of parameters and replacing in the copula C^{WFGM}, we will have the distribution of drainage area and discharge as follows:

$$F^{\mathrm{WFGM}}(x, y) = xy\left[1 + 0.4212\left(1 - x^{1/1.1241}\right)\left(1 - y^{1/1.1241}\right)\right],$$

and the density is provided by

$$f^{\mathrm{WFGM}}(u, v) = 1 + \frac{0.4212}{1.1241^2}\left[(1.1241 + 1)x^{1/1.1241} - 1.1241\right] \times \left[(1.1241 + 1)y^{1/1.1241} - 1.1241\right].$$

Using this distribution helps to obtain important information on the drainage area and discharge, for instance, the probability of a drainage area less than 2.82 and a discharge less than specific 418 is 0.21541.

In addition, using copula can determine conditional distribution followed by acquiring probabilities of how to change a factor according to another controlled factor.

Bekrizadeh et al. [4] fitted Weighted Clayton copula to this data. The probability of a drainage area less than 2.82 and a discharge less than specific 418 is 0.17213. Comparing the probability, we can say that the introduced copula is better than Weighted Clayton copula, and then the copula C^{WFGM} is more suitable for interested data set in comparison with Weighted FGM copula.

6 Conclusion

In this paper, we introduced a new generalized FGM copula, denoted as C^{WFGM}, by incorporating a weighting function based on the marginal distribution functions. The key contributions of

this work are threefold. First, the proposed copula significantly extends the range of negative dependence compared to the classical FGM and many of its existing generalizations, achieving Spearman's rho as low as -0.75 and Kendall's tau as low as -0.50. Second, the model retains the mathematical simplicity and tractability of the original FGM family, with closed-form expressions for its density, dependence measures, and conditional distributions. Third, the practical applicability of the proposed copula was demonstrated using a real hydrological dataset, where it provided a superior fit over the classical FGM copula, as confirmed by a likelihood ratio test. Despite its advantages, the proposed model has certain limitations that should be acknowledged. First, the upper bounds of Spearman's rho and Kendall's tau remain at 0.33 and 0.22, respectively, which are identical to those of the classical FGM copula. Consequently, the C^{WFGM} copula is not suitable for modeling strong positive dependence. Second, the copula is symmetric (exchangeable), which limits its applicability in scenarios where the dependence structure is asymmetric. Third, the current study only considered a single hydrological dataset with a small sample size ($n = 22$). The performance of the model on larger and more diverse datasets remains to be investigated. Several promising directions for future research can be identified. First, the weighting function could be generalized further, for example by introducing separate parameters α and β for each margin, to allow for asymmetric marginal transformations and potentially extend the positive dependence range. Second, extending the model to capture tail dependence, which is absent in the current formulation, would enhance its applicability in extreme value analysis. Third, developing a multivariate extension of the C^{WFGM} copula (beyond the brief mention in Proposition 3) with a full characterization of its parameter space would be a valuable theoretical contribution. Fourth, applying the proposed copula to a wider range of real-world problems in fields such as finance, insurance, and environmental science would further validate its practical utility. Finally, developing efficient computational tools and R/Python packages for the proposed copula would facilitate its adoption by practitioners.

Declarations

Author Contributions

Conceptualization: Hakim Bekrizadeh Methodology: Hakim Bekrizadeh; Software and Validation: Hakim Bekrizadeh; Formal Analysis: Hakim Bekrizadeh; Investigation: Hakim Bekrizadeh; Resources: Hakim Bekrizadeh; Data Curation: Hakim Bekrizadeh; Writing – Original Draft: Hakim Bekrizadeh; Writing – Review and Editing: Hakim Bekrizadeh; Visualization: Hakim Bekrizadeh; Supervision: Corresponding Author; Project Administration: Hakim Bekrizadeh; Funding Acquisition: None.

Acknowledgments

The authors received no specific funding for this research. The authors would like to thank all colleagues and reviewers whose constructive comments significantly improved the quality of this manuscript.

Conflict of Interest

The authors declare that they have no known competing financial interests or personal relationships that could have influenced the work reported in this paper.

Artificial Intelligence Statement

Artificial intelligence (AI) tools, including large language models, were used solely for language editing and improving readability. AI tools were not used for generating ideas, performing analyses, interpreting results, or writing the scientific content. All scientific conclusions and intellectual contributions were made exclusively by the authors.

CPublisher's Note

The publisher remains neutral regarding jurisdictional claims in published maps and institutional affiliations.

References

[1] Arnold, B.C. and Nagaraja, H.N. On some properties of bivariate weighted distributions. *Communications in Statistics: Theory and Methods*, 1991, 20, 1853–1860. https://doi.org/10.1080/03610929108830602.

[2] Bairamov, I. and Kotz, S. Dependence structure and symmetry of Huang–Kotz FGM distributions and their extensions. *Metrika*, 2002, 56, 55–72. https://doi.org/10.1007/s001840200199.

[3] Bekrizadeh, H., Parham, G.A., and Zadkarmi, M.R. The New Generalization of Farlie–Gumbel–Morgenstern Copulas. *Applied Mathematical Sciences*, 2012, 71(6), 3527–3533. https://www.m-hikari.com/ams/ams-2012/ams-69-72-2012/bekrizadehAMS69-72-2012.pdf.

[4] Bekrizadeh, H., Parham, G.A., and Zadkarmi, M.R. Weighted Clayton Copulas and their Characterizations: a application to Probable Modeling of the Hydrology Data. *Journal of Data Science*, 2013, 11(2), 293–303. https://doi.org/10.6339/JDS.2013.11(2).1084.

[5] Bekrizadeh, H. Generalized Family of Copulas: Definition and Properties. *Thailand Statistician*, 2021, 19(1), 163–178. https://doi.org/10.1080/03610918.2022.2032156.

[6] Bekrizadeh, H. Generalized FGM copulas: Properties and applications. *Communications in Statistics: Simulation and Computation*, 2024, 53(2), 744–755. https://doi.org/10.1080/03610918.2022.2032156.

[7] Farlie, D.G.J. The performance of some correlation coefficients for a general bivariate distribution. *Biometrika*, 1960, 47(3–4), 307–323. https://doi.org/10.1093/biomet/47.3-4.307.

[8] Fisher, R.A. The effects of methods of ascertainment upon the estimation of frequencies. *The Annals of Eugenics*, 1934, 6, 13–25. https://doi.org/10.1111/j.1469-1809.1934.tb02105.x.

[9] Gumbel, E.J. Bivariate exponential distributions. *Journal of the American Statistical Association*, 1960, 55, 698–707. https://doi.org/10.1080/01621459.1960.10483368.

[10] Huang, J.S. and Kotz, S. Modifications of the Farlie–Gumbel–Morgenstern distributions, a tough hill to climb. *Metrika*, 1999, 49(2), 135–145. https://doi.org/10.1007/s001840050030.

[11] Joe, H. *Multivariate Models and Dependence Concepts*. London: Chapman and Hall, 1997. https://doi.org/10.1201/9780367803896.

[12] Joag-Dev, K. and Proschan, F. Negative Association of Random Variables with Applications. *Annals of Statistics*, 1983, 11, 286–295. https://doi.org/10.1214/aos/1176346079.

[13] Johnson, N.L. and Kotz, S. *Distributions in Statistics: Continuous Multivariate Distributions*. Wiley, New York, 1972. https://doi.org/10.1002/0471722065.

[14] Lai, C.D. and Xie, M. A new family of positive quadrant dependent bivariate distributions. *Statistics and Probability Letters*, 2000, 46(4), 359–364. https://doi.org/10.1016/S0167-7152(99)00122-4.

[15] Li, X. and Fang, R. A new family of bivariate copulas generated by univariate distributions. *Journal of Data Science*, 2012, 10, 1–17. https://doi.org/10.6339/JDS.2012.10(1).1011.

[16] Mahfoud, M. and Patil, G.P. On weighted distributions. In *Statistics in Theory and Practice: Essays in Honor of C.R. Rao*, G. Kallianpur et al. (eds.), North-Holland, Amsterdam, 1982, 479–492. https://doi.org/10.1002/0471667196.ess2907.pub2.

[17] Makhdoom, I. and Sakhaei, A. On dependence of the weighted Marshall-Olkin bivariate exponential model in the presence of the copula function. *Journal of Statistical Modelling: Theory and Applications*, 2023, 4(1), 157–172. https://doi.org/10.22034/jsmta.2024.21105.1125

[18] Morgenstern, D. Einfache Beispiele zweidimensionaler Verteilungen. *Mitteilungsblatt für Mathematische Statistik*, 1956, 8, 234–235. https://doi.org/10.14490/jjss.36.213.

[19] Nelsen, R.B. *An Introduction to Copulas*. Springer Series in Statistics, Springer, New York, 2006. https://doi.org/10.1007/0-387-28678-0.

[20] Pathak, A.K. and Vellaisamy, P. Various measures of dependence of a new asymmetric generalized Farlie–Gumbel–Morgenstern copulas. *Communications in Statistics: Theory and Methods*, 2015, 45(18), 5299–5317. https://doi.org/10.1080/03610926.2014.942428.

[21] Patil, G.P. and Rao, C.R. Weighted distributions and size-biased sampling with applications to wildlife populations and human families. *Biometrics*, 1978, 34, 179–189. https://doi.org/10.2307/2530008.

[22] Self, S.G. and Liang, K.Y. Asymptotic properties of maximum likelihood estimators and Likelihood ratio tests under nonstandard conditions. *Journal of the American Statistical Association*, 1987, 82(398), 605–610. https://doi.org/10.1080/01621459.1987.10478472.

[23] Rao, C.R. On discrete distributions arising out of methods of ascertainment. In G.P. Patil (Ed.), *Classical and Contagious Discrete Distributions*, Statistical Publishing Society and Pergamum Press, 1965, 320–332. https://www.jstor.org/stable/25049375.

Author(s) Bio-sketches Hakim Bekrizadeh received a Ph.D. in Statistics from Shahid Chamran University of Ahvaz. His research interests include copula, and modeling, and applied statistics. He is currently affiliated with Payame Noor University (PNU) as a faculty member. Corresponding author: Bekrizadeh@pnu.ac.ir

https://jaslda.journals.pnu.ac.ir

Payame Noor University

Statistical Learning & Data Analysis
Volume 1, Issue 1, Summer- Autumn 2026, Pages 46–64
doi:10.30473/jaslda.2026.77814.1000

OPEN ACCESS

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

Research Article

Extended Optimizers in Variational Autoencoders Using Shrinkage Estimation

Heydar Mokhtari Farivar[1,✉], Parviz Nasiri[2]

[1,✉]Iran University of Science and Technology (IUST), Tehran, Iran
[2]Department of Statistics, Payame Noor University, Tehran, Iran

Article Info

Article history:
Received 23 April 2026;
Accepted 15 October 2026;
Available online 15 October 2026.

Abstract. This paper explores the implementation and comparison of various optimization algorithms for training Variational Autoencoders (VAEs). We introduce a shrinkage-based post-hoc weight-update rule and compare it against SGD, Adam, RMSprop, Adagrad, AdamW, and Nadam, using a multi-seed evaluation protocol (5–10 random seeds per configuration) on both a small synthetic dataset and real MNIST digits, together with a per-dimension KL-divergence diagnostic for posterior collapse. At each dataset's default configuration, the shrinkage step appears to have a large and opposite effect: on synthetic data it induces complete posterior collapse in every trained model, while on MNIST it instead avoids the partial posterior collapse exhibited by standard adaptive optimizers, at a substantial cost to reconstruction quality. However, directly testing the robustness of the MNIST finding, by sweeping the learning rate and by testing a nonlinear architecture, shows that this apparent separation between collapsing and non-collapsing optimizers is not stable: SGD collapses at higher learning rates, the adaptive methods' collapse is a non-monotonic function of learning rate that vanishes outside a narrow band, and two of the four shrinkage variants collapse completely under a nonlinear architecture. We conclude that posterior collapse in this setting depends on an interaction between optimizer, learning rate, and architecture that single-configuration comparisons cannot capture, and we report a fully reproducible implementation, including the robustness-check scripts, as a cautionary and diagnostic contribution rather than as a general-purpose optimizer recommendation.

Keywords. Variational Autoencoders; Posterior Collapse; Shrinkage Estimation; Adaptive Optimizers; Reproducibility.

MSC. 68T07, 90C26, 62J07.

How to Cite
Mokhtari Farivar, H., & Nasiri, P. (2026). "Extended Optimizers in Variational Autoencoders Using Shrinkage Estimation." *Journal of Advances in Statistical Learning and Data Analysis*, 1(1), 46–64. https://doi.org/10.30473/jaslda.2026.77814.1000

✉Corresponding author. **E-mail:** mokhtari@iust.ac.ir
©2026 by the authors. Licensee PNU, Tehran, Iran. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution 4.0 International (CC BY4.0) (http:/creativecommons.org/licenses/by/4.0)

1 Introduction

Variational Autoencoders (VAEs) are powerful generative models that learn to represent high-dimensional data in a lower-dimensional latent space. The efficiency of training such models often hinges on the choice of optimizer. This study investigates the impact of different optimization strategies on VAE performance, specifically focusing on a newly introduced shrinkage estimation optimizer.

2 Background

2.1 Variational Autoencoders

Variational Autoencoders (VAEs) are generative models that encode input data into a latent space, from which new data can be sampled and reconstructed, by optimizing the Evidence Lower Bound (ELBO):

$$\mathcal{L}(x;\theta,\phi) = \mathbb{E}_{q_\phi(z|x)}[\log p_\theta(x|z)] - D_{KL}(q_\phi(z|x)\|p(z)), \tag{1}$$

where x is the observed data, z the latent variable, $p_\theta(x|z)$ the decoder likelihood, $q_\phi(z|x)$ the encoder's variational posterior, and $p(z)$ the prior (standard Gaussian). The first term is the reconstruction quality; the second, the KL divergence, regularizes the latent space toward the prior [12]. Throughout this paper, input data $\mathbf{x} \in \mathbb{R}^{10}$ and the latent variable $\mathbf{z} \in \mathbb{R}^5$ (Section 5) or higher dimensions for the MNIST experiments (Section 4.5).

The encoder maps $\mathbf{x}$ to Gaussian parameters $\boldsymbol{\mu} = W_\mu \mathbf{x} + \mathbf{b}_\mu$, $\log \boldsymbol{\sigma}^2 = W_\sigma \mathbf{x} + \mathbf{b}_\sigma$ [21]. The reparameterization trick $\mathbf{z} = \boldsymbol{\mu} + \boldsymbol{\sigma} \odot \boldsymbol{\epsilon}$, $\boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ [1, 20] allows differentiation through the stochastic sampling step. The decoder reconstructs $\mathbf{x}$ from $\mathbf{z}$ as $p_\theta(\mathbf{x}|\mathbf{z}) = \mathcal{N}(\mathbf{x}; \hat{\mathbf{x}}, \boldsymbol{\Sigma})$ [21]. Variants such as InfoVAE [22] offer alternative formulations balancing information maximization and regularization. For the Gaussian encoder and standard-normal prior used throughout, the KL term admits the closed form

$$D_{\mathrm{KL}}(q_\phi(\mathbf{z}|\mathbf{x})\|p(\mathbf{z})) = \frac{1}{2}\sum_{j=1}^{5}\left(1 + \log\sigma_j^2 - \mu_j^2 - \sigma_j^2\right), \tag{2}$$

used throughout the remainder of the paper; the total loss is $L = L_{\text{reconstruction}} + L_{\mathrm{KL}}$, with $L_{\text{reconstruction}} = -\mathbb{E}_{q_\phi(z|x)}[\log p_\theta(x|z)]$ and $L_{\mathrm{KL}} = D_{KL}(q_\phi(z|x)\|p(z))$.

3 Optimizers in Machine Learning

The optimization process is pivotal in training neural networks, including VAEs. Various optimization algorithms have been developed to adjust the weights of the model iteratively based on the gradients of the loss function. Table 1 summarizes the update rule of each base optimizer used in this paper, stated for the decoder parameters θ (the identical rule applies to the encoder parameters ϕ with $\theta \to \phi$ throughout); α is the learning rate and ϵ is a small constant (e.g., 10^{-8}) preventing division by zero.



Figure 1: Left: latent space visualization (first two dimensions). Right: original vs. reconstructed input features.

Optimizer	**Update rule (for θ)**	**Extra hyperparameters**
SGD [5]	$\theta \leftarrow \theta - \alpha \nabla_\theta \mathcal{L}$	—
Momentum [7]	$v_\theta \leftarrow \beta_1 v_\theta + (1-\beta_1)\nabla_\theta \mathcal{L}$ $\theta \leftarrow \theta - \alpha v_\theta$	$\beta_1 \approx 0.9$
Adam [9]	$m_\theta \leftarrow \beta_1 m_\theta + (1-\beta_1)\nabla_\theta \mathcal{L}$ $v_\theta \leftarrow \beta_2 v_\theta + (1-\beta_2)(\nabla_\theta \mathcal{L})^2$ $\theta \leftarrow \theta - \frac{\alpha}{\sqrt{\hat{v}_\theta}+\epsilon}\hat{m}_\theta,\ \ \hat{m}_\theta = \frac{m_\theta}{1-\beta_1^t},\ \hat{v}_\theta = \frac{v_\theta}{1-\beta_2^t}$	β_1=0.9, β_2=0.999
RMSprop [13]	$r_\theta \leftarrow \beta r_\theta + (1-\beta)(\nabla_\theta \mathcal{L})^2$ $\theta \leftarrow \theta - \frac{\alpha}{\sqrt{r_\theta}+\epsilon}\nabla_\theta \mathcal{L}$	$\beta \approx 0.9$
Adagrad [17]	$r_\theta \leftarrow r_\theta + (\nabla_\theta \mathcal{L})^2$ $\theta \leftarrow \theta - \frac{\alpha}{\sqrt{r_\theta}+\epsilon}\nabla_\theta \mathcal{L}$	—

Table 1: Base optimizer update rules ($\mathcal{L} = \mathcal{L}(\theta, \phi)$ throughout).

3.1 A Generic Shrinkage Modification

For each base optimizer above, a shrinkage-regularized variant has been proposed in the literature by adding a term proportional to the gradient of the squared loss norm to the gradient (or velocity) used in the update [8, 10, 14, 18]. For example, for plain SGD this takes the form

$$\theta \leftarrow \theta - \alpha \left(\nabla_\theta \mathcal{L} + \lambda \nabla_\theta \|\mathcal{L}\|^2 \right), \tag{3}$$

and analogously for Momentum, Adam, RMSprop, and Adagrad by substituting the same modified gradient into each optimizer's update rule from Table 1. As discussed in Section 4.3 and flagged in the Limitations, the term $\nabla_\theta \|\mathcal{L}\|^2$ requires a Hessian-vector product and is not resolved to a concrete formula anywhere in this literature; the shrinkage rule actually implemented and evaluated in this paper is instead the fully-specified, post-hoc multiplicative rule introduced in Section 3.3 below.

3.2 Relation to Existing Regularization Techniques

Before introducing the proposed optimizer, it is useful to position the shrinkage step relative to existing regularization strategies for gradient-based training, since several established techniques share a superficial resemblance with the proposed mechanism.

Weight decay (L_2 regularization). Classical weight decay [11] adds a term $\lambda\theta$ directly to the gradient before the update, which is equivalent to multiplying the parameter by a *constant* factor $(1 - \alpha\lambda)$ at every step, independently of the parameter's magnitude. In contrast, the shrinkage step proposed here (Section 3.3) multiplies each parameter by a factor $\left(1 - \lambda \cdot \frac{\theta^2}{\theta^2+\alpha}\right)$ that depends on the magnitude of θ itself: large-magnitude weights are shrunk more strongly than small ones, whereas standard weight decay treats all weights uniformly.

Proximal-gradient and soft-thresholding methods. Proximal-gradient methods minimize a composite objective $f(\theta) + g(\theta)$ by alternating a gradient step on f with a proximal (shrinkage) operator associated with g; for an L_1 penalty this proximal operator is the well-known soft-thresholding function, which sets small coefficients exactly to zero. The operator used in this work is smooth and multiplicative rather than a hard soft-threshold, so it shrinks weights continuously toward zero without inducing exact sparsity in the same way, and it is applied heuristically after the update rather than being derived as the exact proximal map of an explicit penalty term.

Sparse optimization approaches. Methods such as L_1-regularized SGD or iterative hard/soft-thresholding algorithms explicitly target sparse solutions and typically come with convergence guarantees tied to the convexity of the penalty. The present shrinkage operator is motivated instead by the classical shrinkage-estimation literature (e.g., James–Stein-type estimators), where the goal is to trade a small amount of bias for a reduction in variance rather than to enforce sparsity per se.

In summary, the proposed shrinkage step can be viewed as a lightweight, magnitude-adaptive alternative to weight decay that borrows its motivation from shrinkage estimation rather than from proximal optimization theory. A more rigorous comparison, including a formal derivation of the operator as a proximal map of some regularizer, if one exists, is left for future work.

3.3 Shrinkage Estimators

Shrinkage estimators are a class of statistical methods used to improve the estimation of parameters by "shrinking" them towards a target value. This approach is particularly useful in high-dimensional settings where traditional estimators may overfit the data.

The basic concept of a shrinkage estimator can be illustrated through the formulation:

$$\hat{\theta}_{shrink} = (1 - \lambda)\hat{\theta}_{MLE} + \lambda\theta_0 \tag{4}$$

where $\hat{\theta}_{shrink}$ is the shrinkage estimate, $\hat{\theta}_{MLE}$ is the maximum likelihood estimate, θ_0 is the target parameter (often a prior mean or zero), and λ is the shrinkage factor, which controls the degree of shrinkage.

In the context of neural networks, incorporating shrinkage into the optimizer can enhance generalization by controlling the magnitudes of the weights during training, reducing overfitting.

Implementation of the Shrinkage Optimizer. The proposed Shrinkage Optimizer applies a shrinkage step during the weight update process. The mathematical formulation is as follows:

$$\theta_{t+1} = \theta_t - \eta\nabla L(\theta_t) \tag{5}$$

$$\theta_{t+1} = \theta_{t+1} \cdot \left(1 - \lambda \cdot \frac{\theta_{t+1}^2}{\theta_{t+1}^2 + \alpha}\right) \tag{6}$$

where α is a small constant that ensures stability, and the term $\left(1 - \lambda \cdot \frac{\theta_{t+1}^2}{\theta_{t+1}^2+\alpha}\right)$ implements the shrinkage effect.

This shrinkage step helps control the weight magnitudes, promoting sparsity and preventing overfitting, particularly in high-dimensional latent spaces common in VAEs.

3.4 Stability and Convergence Considerations

Because the shrinkage step is applied *after* a standard gradient update rather than folded into the loss function, it does not, by itself, come with a formal convergence guarantee in the sense of classical stochastic-approximation theory. Two properties are nonetheless worth noting. First, the multiplicative factor $\left(1 - \lambda \cdot \frac{\theta^2}{\theta^2+\alpha}\right)$ is bounded in $(1 - \lambda, 1]$ for $\lambda \in (0, 1)$, so the shrinkage step is a contraction: it can only reduce the magnitude of a parameter, never amplify it, which bounds the additional perturbation it introduces at each iteration. Second, as $|\theta| \to 0$ the shrinkage factor also tends to 1 (no shrinkage), so the operator does not destabilize small, already well-regularized weights; the effect is concentrated on large-magnitude parameters. These two properties suggest that the shrinkage step preserves the stability region of the underlying optimizer (SGD in our implementation) rather than expanding it, but a formal proof of convergence for the combined update, analogous to the regret bounds available for Adagrad or the convergence analysis of proximal SGD, has not been derived here and is an important direction for future theoretical work.

4 Methodology

4.1 Model Architecture

The architecture of the VAE used in this study consists of a linear encoder mapping the 10-dimensional input to a 5-dimensional Gaussian latent space ($\mu, \log \sigma^2 \in \mathbb{R}^5$) and a linear decoder that reconstructs the 10-dimensional input from a sampled latent vector, exactly as described in Section 2.1. For the MNIST experiments (Section 4.5) the same architecture is used with the input and latent dimensionalities increased to 784 and 20 respectively.

4.2 Datasets

Two datasets are used in this paper, one synthetic and one real, so that the optimizer comparison can be checked for consistency across both.

Synthetic dataset. A controlled, small-scale dataset of 160 points in $\mathbb{R}^{10}$, generated as described in Section 4.4 below. This dataset has no external source, it is generated on the fly by the accompanying code, and is used for the results in Section 5.1–5.2.

MNIST dataset (real data). To address the reviewers' request for evaluation beyond a synthetic proof-of-concept, we additionally trained on the MNIST handwritten-digit database [23], a standard, publicly available benchmark of 70,000 grayscale images of handwritten digits (60,000 training / 10,000 test, each 28×28 pixels). We used a fixed random subsample of 5,000 images from the standard training split, downloaded programmatically (no manual curation) through one of three standard distribution channels, `torchvision.datasets.MNIST`, `tensorflow.keras.datasets.mnist`, or scikit-learn's OpenML interface, via the `data_loader.py` script included in the supplementary code, which tries each in turn so the pipeline runs regardless of which of the three libraries is installed in the executing environment. Pixel intensities were rescaled from $\{0, \ldots, 255\}$ to $[0, 1]$ and each image was flattened to a 784-dimensional vector; no other preprocessing (cropping, augmentation, denoising) was applied. This is real image data, not a synthetic stand-in, and the results in Section 5.3 are computed directly from it. The results reported in this manuscript were produced by running the supplementary code end-to-end in Google Colab, which has direct internet access for the MNIST download.

4.3 Optimizer Implementation

We implement the Shrinkage Optimizer as the post-hoc multiplicative rule of Eq. (6): a standard gradient step is taken first, and the resulting parameters are then multiplied element-wise by $\left(1 - \lambda \cdot \frac{\theta^2}{\theta^2 + \alpha_{\text{shrink}}}\right)$. This is the only shrinkage rule in Section 3 that is fully specified without requiring a second-order (Hessian-vector) term, and it is the rule used to produce every empirical result in this paper, including the shrinkage-augmented variants of SGD, Adam, RMSprop, and Adagrad reported below.

4.4 Training Procedure and Reproducibility

All results in Section 5 were produced with a from-scratch NumPy implementation of the model above (manual forward pass and analytically-derived backpropagation, verified against finite-difference gradient checks to a relative error below 10^{-8}) together with from-scratch implementations of SGD, Adam, RMSprop, Adagrad, AdamW, and Nadam, each with and without the shrinkage step of Section 4.2 (twelve optimizer configurations in total). This lets us report every optimizer discussed in Section 3, including RMSprop and Adagrad, whose absence from the empirical comparison the reviewers correctly flagged, plus AdamW [24] and Nadam [25], added specifically in response to the request for comparison against more modern optimizers, rather than only SGD and Adam.

Data. The synthetic dataset consists of 160 points in $\mathbb{R}^{10}$, drawn i.i.d. from a standard normal distribution and rescaled per feature to $[0, 1]$, exactly as described previously; the data-generating seed is fixed across all optimizers so that every method is trained on the identical dataset.

Training. Each optimizer was trained for 5 epochs with batch size 16 (10 batches/epoch), learning rate $\alpha = 10^{-3}$ (Adagrad used $\alpha = 10^{-2}$, its conventional default, since its learning rate is not comparable to the other methods on the same scale), Adam's/AdamW's/Nadam's $(\beta_1, \beta_2, \epsilon) = (0.9, 0.999, 10^{-8})$, RMSprop's $(\beta, \epsilon) = (0.9, 10^{-8})$, AdamW's decoupled weight decay coefficient $= 10^{-2}$, and shrinkage hyperparameters $\lambda = 0.1$, $\alpha_{\text{shrink}} = 10^{-4}$. Weights were initialized with Glorot/Xavier-uniform initialization. To obtain reliable estimates of run-to-run variability, as recommended by both reviewers, **every configuration was trained from 10 independent random seeds** (controlling weight initialization, minibatch ordering, and the stochastic reparameterization noise), and we report the mean ± standard deviation over these 10 runs throughout Section 5.

Code availability. The full implementation (model, optimizers, gradient-check unit test, and the experiment/plotting scripts used to generate every table and figure in Sections 5–6) is included as supplementary material with this submission so that all reported numbers can be independently reproduced.

4.5 MNIST Experiment: Quantitative Evaluation

Using the real MNIST data described in Section 4.2, we carried out a full quantitative evaluation directly answering the reviewers' request for a benchmark beyond the small synthetic dataset. The same linear-Gaussian VAE and the same eight from-scratch optimizer implementations used in Section 5 were re-used unchanged (input/latent dimensionality 784/20 as noted above). Each of the eight optimizers was trained on the 5,000-image MNIST subsample from 5 independent random seeds for 100 epochs, batch size 64, using the same learning rates, $\lambda = 0.1$, and $\alpha_{\text{shrink}} = 10^{-4}$ as in Section 4.4. The results are reported in Section 5.3 and discussed in Section 6.1.

The pre-existing qualitative reconstructions in Figures 8–8 (MNIST digits and natural images, provided with the original submission) are retained for illustration but were not regenerated as part of this quantitative evaluation and are not used in any of the numbers reported below.

5 Results

5.1 Results Table

All results below are from the multi-seed NumPy re-implementation described in Section 4.4 (10 seeds per optimizer). Table 2 reports total loss, Tables 3–4 report the reconstruction and KL components, and Table 5 extends the comparison to RMSprop, Adagrad, and their shrinkage-augmented variants, directly addressing the reviewers' request that these methods be included empirically rather than only derived theoretically.

Epoch	Adam Total Loss	SGD Total Loss	Shrinkage Total Loss
0	7.924 ± 2.844	7.858 ± 2.652	4.201 ± 0.997
1	6.962 ± 2.400	6.871 ± 1.982	1.747 ± 0.057
2	6.488 ± 2.234	6.412 ± 1.638	1.519 ± 0.011
3	5.973 ± 1.993	5.959 ± 1.363	1.488 ± 0.003
4	5.375 ± 1.584	5.433 ± 0.984	1.483 ± 0.003

Table 2: Total loss (mean ± std over 10 random seeds) for Adam, SGD, and the Shrinkage Optimizer.

Epoch	Adam Recon Loss	SGD Recon Loss	Shrinkage Recon Loss
0	6.507 ± 2.195	6.460 ± 2.042	3.542 ± 0.722
1	5.697 ± 1.849	5.654 ± 1.531	1.675 ± 0.045
2	5.346 ± 1.745	5.329 ± 1.280	1.510 ± 0.010
3	4.933 ± 1.585	4.987 ± 1.106	1.486 ± 0.003
4	4.419 ± 1.243	4.546 ± 0.799	1.483 ± 0.003

Table 3: Reconstruction loss (mean ± std over 10 seeds) for Adam, SGD, and the Shrinkage Optimizer.

Epoch	Adam KL Loss	SGD KL Loss	Shrinkage KL Loss
0	1.417 ± 0.680	1.397 ± 0.644	0.659 ± 0.305
1	1.265 ± 0.598	1.217 ± 0.508	0.071 ± 0.029
2	1.142 ± 0.526	1.082 ± 0.410	0.009 ± 0.003
3	1.040 ± 0.459	0.972 ± 0.332	0.001 ± 0.000
4	0.956 ± 0.400	0.887 ± 0.273	0.000 ± 0.000

Table 4: KL loss (mean ± std over 10 seeds) for Adam, SGD, and the Shrinkage Optimizer.

Note on an earlier version of these tables. An earlier draft reported single-seed values and included a second, hand-rounded table inconsistent with the measured losses, flagged by a reviewer and since removed. The tables above are the sole, internally consistent source of quantitative results in this revision (Table 2 is exactly the sum of Tables 3 and 4 at every epoch).

- **Adam and SGD:** Both decrease steadily but slowly (from ≈ 7.9 to ≈ 5.4), statistically indistinguishable from each other at every epoch.
- **RMSprop and Adagrad** converge faster (final loss 4.998, 3.348), consistent with per-parameter adaptive rates at this scale.
- **AdamW and Nadam** behave essentially identically to plain Adam (5.371, 5.344 vs. 5.375), decoupled weight decay and Nesterov momentum make little difference here.

Optimizer	Final Total Loss (mean ± std)	Mean # Collapsed Latent Dims (/5)
SGD	5.433 ± 0.984	0.00 ± 0.00
Adam	5.375 ± 1.584	0.00 ± 0.00
RMSprop	4.998 ± 1.425	0.00 ± 0.00
Adagrad	3.348 ± 0.740	0.00 ± 0.00
AdamW	5.371 ± 1.582	0.00 ± 0.00
Nadam	5.344 ± 1.572	0.00 ± 0.00
Shrink-SGD	1.483 ± 0.003	5.00 ± 0.00
Shrink-Adam	1.463 ± 0.003	5.00 ± 0.00
Shrink-RMSprop	1.461 ± 0.003	5.00 ± 0.00
Shrink-Adagrad	1.435 ± 0.004	5.00 ± 0.00
Shrink-AdamW	1.463 ± 0.003	5.00 ± 0.00
Shrink-Nadam	1.463 ± 0.003	5.00 ± 0.00

Table 5: Final-epoch (epoch 5) total loss and posterior-collapse diagnostic (number of latent dimensions with $\mathrm{KL}_j < 0.01$, out of 5) for all twelve optimizers, including AdamW and Nadam, mean ± std over 10 seeds.

- **Shrinkage Optimizer** drops fastest, reaching 1.483 ± 0.003 by epoch 2 with 2–3 orders of magnitude lower variance than the non-shrinkage methods. This is fully explained by complete posterior collapse (Section 6.1): all 5 latent dimensions collapse in every one of the 10 seeds under every shrinkage-augmented optimizer, including Shrink-AdamW/Nadam, never the case for a non-shrinkage optimizer.

5.2 Charts and Analysis

Figures 2–2 show mean ± one standard deviation (shaded band, 10 seeds) for total, reconstruction, and KL loss for the three optimizers highlighted in the original submission (Adam, SGD, Shrinkage); Figure 3 shows the posterior-collapse diagnostic for all twelve optimizers evaluated in Table 5, including AdamW and Nadam, directly addressing the reviewers' request for comparison against more modern optimizers.



Figure 2: Total, reconstruction, and KL loss for SGD, Adam, and the Shrinkage Optimizer (mean ± std, 10 seeds).



Figure 3: Posterior collapse diagnostic (mean number of latent dimensions with $\mathrm{KL}_j < 0.01$ at epoch 5, out of 5) for all twelve optimizers, including AdamW and Nadam, mean ± std over 10 seeds. Every shrinkage-augmented optimizer collapses all 5 latent dimensions in every seed; no non-shrinkage optimizer collapses any dimension.

5.3 MNIST Quantitative Results

Table 6 and Figures 4–4 report the real-MNIST results obtained with the protocol described in Section 4.5 (5,000 training images, 20-dimensional latent space, 100 epochs, 5 seeds, learning rate $\alpha = 10^{-3}$). At this specific configuration, the pattern found on the synthetic dataset does not carry over to MNIST, in several respects it reverses. **We emphasize "at this specific configuration" deliberately**: Section 6.3 shows, with real MNIST experiments, that this reversal is highly sensitive to the learning rate and architecture, so it should not be read as a stable, general property of any optimizer.

Optimizer	Final Total Loss (mean ± std)	Mean # Collapsed Latent Dims (/20)
SGD	23.877 ± 0.085	0.00 ± 0.00
Adam	22.995 ± 0.029	6.80 ± 0.75
RMSprop	23.048 ± 0.021	6.60 ± 1.20
Adagrad	23.073 ± 0.028	7.00 ± 1.10
AdamW	22.995 ± 0.029	6.80 ± 0.75
Nadam	22.988 ± 0.033	6.40 ± 1.62
Shrink-SGD	41.226 ± 0.016	0.00 ± 0.00
Shrink-Adam	35.511 ± 0.058	0.00 ± 0.00
Shrink-RMSprop	35.600 ± 0.061	0.00 ± 0.00
Shrink-Adagrad	41.548 ± 0.048	0.00 ± 0.00
Shrink-AdamW	35.512 ± 0.058	0.00 ± 0.00
Shrink-Nadam	35.505 ± 0.052	0.00 ± 0.00

Table 6: MNIST: final-epoch (epoch 100) total loss and posterior-collapse diagnostic for all twelve optimizers, including AdamW and Nadam, mean ± std over 5 seeds, 5,000 training images, $\alpha = 10^{-3}$.

- **Non-shrinkage optimizers reach a lower total loss.** Adam, RMSprop, Adagrad,

AdamW, and Nadam converge to ≈ 23.0; even SGD reaches 23.9 by epoch 100, all outperform every shrinkage variant (35.5–41.5), the opposite ranking from Section 5.1.

- **AdamW and Nadam behave like Adam**, as on the synthetic dataset: essentially identical loss and collapse count.
- **At $\alpha = 10^{-3}$, shrinkage prevents collapse rather than causing it.** All six shrinkage variants collapse zero dimensions; Adam, RMSprop, Adagrad, AdamW, and Nadam each collapse 6.4–7.0 of 20 (Figure 4). SGD also collapses zero at this rate.
- **Shrinkage trades reconstruction quality for a non-collapsing code:** Shrink-SGD plateaus at reconstruction loss ≈ 40, double Adam/SGD's ≈ 19–20 (Figure 4), capped decoder capacity keeps the code informative but hurts reconstruction.
- **Shrink-Adagrad never converges**: its total loss rises monotonically from 36.0 (epoch 1) to 41.5 (epoch 100), an instability from Adagrad's shrinking effective rate fighting the shrinkage step's constant downward pressure.



Figure 4: MNIST at $\alpha = 10^{-3}$ (mean ± std, 5 seeds, 5,000 training images). *Left:* total loss, all eight base optimizers over 100 epochs (AdamW/Nadam, not shown, track Adam almost exactly). *Middle:* reconstruction loss, Adam vs. SGD vs. Shrink-SGD. *Right:* posterior-collapse diagnostic (mean # of 20 latent dimensions with $\mathrm{KL}_j < 0.01$ at epoch 100). **This pattern is not robust to changes in learning rate or architecture, see Section 6.3.**

6 Discussion

The multi-seed results in Section 5 show the Shrinkage Optimizer reaches a lower total loss, faster, and with far less run-to-run variance than any non-shrinkage method on the synthetic problem. Unlike in the original submission, we no longer read this as positive: the diagnostic below shows the advantage is fully explained by a well-known failure mode, not better ELBO optimization.

6.1 Posterior Collapse

Reviewer 1 raised the concern that a rapidly-vanishing KL term may indicate posterior collapse rather than genuine improvement. This is confirmed on the synthetic dataset but, notably, does *not* generalize to MNIST, the two datasets tell different, complementary stories.

Synthetic dataset (Section 5.1): under every shrinkage-augmented optimizer, all 5 latent dimensions collapse ($\mathrm{KL}_j < 0.01$) in all 10 seeds, with near-zero variance; no non-shrinkage

optimizer collapses any dimension. The Shrinkage Optimizer's "fast convergence" is not a better fit to the data, it is the encoder stopping encoding. Once $q_\phi(z|x) \approx p(z)$, the KL term vanishes by construction, mechanically pulling total loss down regardless of reconstruction quality [19]. A supplementary 30-epoch run (5 seeds) shows Adam continuing to close this gap (total loss 1.70 by epoch 30 vs. 1.48 for Shrink-SGD, already collapsed by epoch 2).

Real MNIST at $\alpha = 10^{-3}$, linear architecture (Section 5.3): the pattern reverses. Adam, RMSprop, Adagrad, AdamW, and Nadam partially collapse (6.4–7.0 of 20 dimensions by epoch 100); every shrinkage-augmented optimizer and plain SGD collapse zero. The shrinkage-augmented optimizers reach substantially worse total and reconstruction loss (Table 6): shrinking the decoder weights caps capacity, keeping the code informative but hurting reconstruction, and Shrink-Adagrad never converges. **However, Section 6.3 shows directly on MNIST that this separation does not survive changes in learning rate or architecture**, SGD collapses at higher α, Adam/RMSprop's collapse disappears at higher α, Adagrad's collapse here is a learning-rate artifact, and Shrink-SGD/Shrink-Adagrad collapse completely under a nonlinear architecture. The mechanism behind the MNIST pattern therefore remains unidentified, and Table 6 should be read as a single-configuration observation, not a general property of these optimizers.

Taken together, neither "shrinkage causes collapse" nor "shrinkage prevents collapse" is universal, the outcome depends on optimizer, learning rate, architecture, and dataset, and can flip within one dataset under modest changes to any of these. Reporting total loss alone, for any of these methods, would have told a misleadingly simple and often directionally wrong story. No single configuration here licenses a general recommendation to use or avoid the shrinkage step, or to prefer one base optimizer for collapse-resistance; a collapse diagnostic should be reported across learning rates and at least one architectural variation, not at one configuration, before drawing such conclusions.

We therefore revise our interpretation from the original submission: the shrinkage step (Eq. (6), $\lambda = 0.1$) cannot be recommended as a general-purpose improvement to VAE training. It reliably destroys the latent code on the synthetic problem; on MNIST it avoids collapse only by sacrificing reconstruction quality, and one variant (Shrink-Adagrad) never converges. Collapse-mitigation techniques, KL annealing, free-bits, β-VAE-style down-weighting [15], would need to be combined with the shrinkage step, and λ tuned per dataset, before any improvement claim could be supported. We see this honest, dataset-dependent diagnosis as a more useful contribution than the original, uncritically positive framing.

6.2 Sensitivity to the Shrinkage Coefficient

All results above use a single shrinkage coefficient, $\lambda = 0.1$. To check how sensitive the collapse behavior is to this choice, we swept $\lambda \in \{0.01, 0.05, 0.1, 0.2, 0.5\}$ for Shrink-SGD and Shrink-Adam on the synthetic dataset, using the same 10-seed protocol as Section 5.1. Figure 6 shows the result: there is a sharp threshold between $\lambda = 0.01$ and $\lambda = 0.05$. At $\lambda = 0.01$, essentially no latent dimensions collapse (mean 0.0–0.1 out of 5) and the final total loss is high and highly variable (2.7–3.0$\pm$0.3–0.4); at $\lambda \geq 0.05$, all 5 dimensions collapse in every seed (mean exactly 5.0, zero variance) and the total loss drops sharply to $\approx$ 1.45–1.51 with very low variance. Beyond this threshold, further increasing λ up to 0.5 has only a small effect on the (already-collapsed) total loss. This confirms that the shrinkage step's behavior on the synthetic dataset is governed by a fairly sharp collapse threshold in λ rather than a gradual trade-off, and that $\lambda = 0.1$ (used throughout Section 5) sits solidly inside the collapsing regime rather than near this threshold.

MNIST λ-sweep (real data). We additionally ran the equivalent sweep on MNIST for Shrink-SGD and Shrink-Adam, same protocol as Section 4.5. Figure 5 shows a qualitatively different picture from the synthetic dataset: across the entire range $\lambda \in \{0.01, \ldots, 0.5\}$, **no collapse occurs** for either optimizer (0.00/20 at every $\lambda \geq 0.05$; a small 0.4 ± 0.5 for Shrink-Adam only at the smallest value $\lambda = 0.01$, likely noise given the large relative standard deviation). Total loss increases monotonically and smoothly with λ for both optimizers (from $\approx$ 27–34 at $\lambda = 0.01$ to $\approx$ 41–43 at $\lambda = 0.5$), with no sharp threshold analogous to the synthetic-dataset case. This is the one robustness check in this paper where the MNIST result *confirms* the qualitative claim made from the linear-architecture main experiment (Section 5.3): under this specific architecture, shrinkage does not induce collapse at any of the five λ values tested. As Section 6.3 shows, however, this same non-collapsing behavior does *not* hold once the architecture is changed.



Figure 5: MNIST: sensitivity to the shrinkage coefficient λ for Shrink-SGD and Shrink-Adam (mean $\pm$ std, 5 seeds, linear architecture). Unlike the synthetic dataset (Figure 6), no sharp collapse threshold appears; collapse remains at zero across the full range tested.



Figure 6: Sensitivity of the synthetic-dataset results to the shrinkage coefficient λ (Shrink-SGD and Shrink-Adam, mean $\pm$ std over 10 seeds). *Left:* final total loss. *Right:* mean number of collapsed latent dimensions (out of 5). A sharp collapse threshold appears between $\lambda = 0.01$ and $\lambda = 0.05$.

6.3 Robustness Checks: The MNIST Collapse Pattern Is Not Stable

The MNIST finding in Table 6 rests on one architecture (linear) and one learning rate ($\alpha = 10^{-3}$). A preliminary synthetic-dataset check suggested this pattern might be a real, if fragile, property of adaptive-optimizer dynamics, so we ran both checks directly on MNIST. **The result is far more cautionary: the clean separation between "collapsing" and "non-collapsing" optimizers does not hold up under either perturbation.**

Learning-rate sensitivity (Figure 7, $\alpha \in \{10^{-4}, 3\times10^{-4}, 10^{-3}, 3\times10^{-3}, 10^{-2}\}$, SGD/Adam/RMSprop/Adagrad) contradicts Table 6 in three ways: (i) **SGD is not immune**, 0 collapsed dimensions at $\alpha = 10^{-3}$, but 4.0 ± 1.4 at 3×10^{-3} and 7.8 ± 0.4 at 10^{-2}, comparable to the worst adaptive methods; (ii) **Adam/RMSprop's collapse is non-monotonic and vanishes at higher** α, rising from $3.2\pm0.4/2.4\pm0.8$ at $\alpha = 10^{-4}$ to a peak of $7.8\pm0.4/6.6\pm1.2$ near $\alpha = 10^{-3}$, then dropping to exactly 0.0 at $\alpha \geq 3\times10^{-3}$; the paper's default sits near this peak, not on a stable plateau; (iii) **Adagrad's collapse is a learning-rate confound**: the main experiment gives it $10\times$ the other optimizers' learning rate (10^{-2}), at which it collapses (7.0 ± 1.1, matching Table 6), but at the *same* rate as the others (10^{-3}) it collapses zero, not an apples-to-apples comparison.

Nonlinear architecture (single tanh hidden layer, $\alpha = 10^{-3}$, gradients verified to 2×10^{-9}; Figure 7, Table 7) changes the picture further: Adam's and RMSprop's collapse roughly doubles ($6.8 \to 11.8$; $6.6 \to 11.2$, of 20); Adagrad's drops to zero ($7.0 \to 0.0$); and, most importantly, **Shrink-SGD and Shrink-Adagrad, zero collapse under every linear-architecture condition tested, collapse completely** (all 20 dimensions, every seed), while Shrink-Adam and Shrink-RMSprop remain at zero.

Optimizer	Collapsed Dims, Linear (/20)	Collapsed Dims, Nonlinear (/20)
SGD	0.00	0.0
Adam	6.80	11.8
RMSprop	6.60	11.2
Adagrad	7.00	0.0
Shrink-SGD	0.00	**20.0**
Shrink-Adam	0.00	0.0
Shrink-RMSprop	0.00	0.0
Shrink-Adagrad	0.00	**20.0**

Table 7: MNIST posterior collapse, linear vs. nonlinear (1 tanh hidden layer) architecture, both at $\alpha = 10^{-3}$, mean over 5 seeds. Two of the four shrinkage variants flip from zero to complete collapse.

Interpretation. We had hoped these checks would corroborate the clean narrative of Section 5.3. Instead, essentially every optimizer tested, including SGD and two of the four shrinkage variants, both described above as collapse-resistant, can be made to collapse under some combination of learning rate and architecture, and Adagrad's collapse in the main table depends on an unmatched learning rate. This does not invalidate Table 6 as a report of what happens at $\alpha = 10^{-3}$ with a linear architecture; it invalidates any general claim that some optimizers are intrinsically more prone to posterior collapse than others. The accurate summary: *posterior collapse here is governed by an interaction between optimizer, learning rate, and architecture for which we have no predictive theory*, and single-configuration comparisons, including our own synthetic-dataset comparison in Section 5.1, are single points in a much larger, only partially explored space, not general evidence about the optimizers.

One check replicated cleanly. The MNIST λ-sweep (Section 6.2, Figure 5) confirmed zero



Figure 7: MNIST robustness checks (linear architecture unless noted, mean, 5 seeds). *Left:* posterior collapse vs. learning rate, no optimizer is uniformly resistant; Adam/RMSprop's collapse is non-monotonic and returns to zero at higher α, while SGD's collapse increases with α. *Right:* linear vs. nonlinear architecture at $\alpha = 10^{-3}$, Shrink-SGD and Shrink-Adagrad go from zero to complete collapse; Adagrad goes from substantial to zero collapse; Adam and RMSprop's collapse roughly doubles.

collapse for Shrink-SGD and Shrink-Adam across $\lambda \in \{0.01, \ldots, 0.5\}$ under the linear architecture, consistent with Table 6, though, as just shown, this breaks down once the architecture changes.

6.4 Limitations

Several limitations remain. First, the synthetic comparison uses only 160 ten-dimensional samples and a linear encoder–decoder; the MNIST experiment (Section 5.3) also uses a linear architecture and a 5,000-image subsample of the full 60,000, so absolute numbers should not be read as representative of a production-scale convolutional VAE. Second, the underlying dataset (synthetic or MNIST subsample) is drawn from a single fixed seed shared across all runs; varying it would further strengthen the statistics. Third, the MNIST reconstructions in Figures 8–8 are the original pre-existing qualitative illustrations, not regenerated to match Section 5.3's quantitative setup. Fourth, the shrinkage-augmented RMSprop/Adagrad variants use the same post-hoc rule as Shrink-SGD rather than the distinct, gradient-norm-based terms sketched generically in Section 3.1, which involve an unspecified second-order term and were not implemented. Fifth, AdamW/Nadam were compared on MNIST only at the default learning rate and linear architecture, where they track Adam almost exactly; whether they also do so under the perturbations of Section 6.3 is untested. Sixth, and most importantly: Section 6.3 shows the clean pattern in Table 6 (SGD/shrinkage resist collapse; Adam/RMSprop/Adagrad do not) is specific to $\alpha = 10^{-3}$ and the linear architecture and does not generalize even within MNIST, at higher α SGD collapses too, at some α Adam/RMSprop's collapse disappears, and under a nonlinear architecture two shrinkage variants collapse completely. This is a central finding of the revision, not a loose end: readers should not draw general conclusions about which optimizers are safe from posterior collapse from Table 6 alone.

7 Conclusion

We introduced a post-hoc multiplicative shrinkage step for VAE training and re-evaluated it with a multi-seed protocol on synthetic data and real MNIST, covering twelve optimizer configurations (SGD, Adam, RMSprop, Adagrad, AdamW, Nadam, each with/without shrinkage) and a per-dimension KL diagnostic for posterior collapse. On synthetic data, shrinkage produces faster, lower-variance convergence fully attributable to complete posterior collapse rather than better density estimation, uniformly across all six base optimizers, and stable once $\lambda \geq 0.05$ (Section 6.2). On MNIST at the default configuration ($\alpha = 10^{-3}$, linear architecture), shrinkage instead appears to *prevent* the partial collapse shown by the adaptive optimizers, but only by degrading reconstruction quality, and Shrink-Adagrad never converges.

The revision's most important finding, however, is that this MNIST pattern is not robust (Section 6.3). SGD collapses just as much as any adaptive method once the learning rate is raised; Adam/RMSprop's collapse is non-monotonic in the learning rate and vanishes outside a narrow band; Adagrad's apparent collapse is a learning-rate confound, not a property of Adagrad; and a nonlinear architecture causes Shrink-SGD and Shrink-Adagrad to collapse completely, the opposite of their linear-architecture behavior. Posterior collapse here is governed by an interaction between optimizer, learning rate, and architecture we cannot yet predict, and neither dataset nor any single configuration supports a general claim about which optimizers resist collapse.

We view this negative, self-correcting finding, including retracting our own cleaner-sounding earlier MNIST narrative, together with the reproducible implementation (NumPy code, MNIST pipeline, and robustness/sensitivity scripts), as more useful than either the original uncritical claim or an untested tidier revision. Natural next steps: (i) combine shrinkage with explicit collapse-mitigation (KL annealing, free-bits); (ii) develop a predictive account of when a given (optimizer, learning rate, architecture) combination induces collapse; (iii) extend this multi-configuration protocol to convolutional architectures and further datasets (Fashion-MNIST, CIFAR-10).

Declarations

Author Contributions
Conceptualization: H. Mokhtari Farivar; Methodology: H. Mokhtari Farivar; Software and Validation: H. Mokhtari Farivar; Formal Analysis: H. Mokhtari Farivar; Investigation: H. Mokhtari Farivar; Writing – Original Draft: H. Mokhtari Farivar; Writing – Review & Editing: both authors; Supervision: P. Nasiri; Funding Acquisition: none.

Acknowledgments
The authors received no specific funding for this research. The authors would like to thank the reviewers whose constructive comments substantially improved this manuscript.

Conflict of Interest
The authors declare that they have no known competing financial interests or personal relationships that could have influenced the work reported in this paper.

Artificial Intelligence Statement
Artificial intelligence (AI) tools, including large language models, were used solely for language editing and improving readability. AI tools were not used for generating ideas, performing analyses, interpreting results, or writing the scientific content. All scientific conclusions and intellectual contributions were made exclusively by the authors.

Publisher's Note
The publisher remains neutral regarding jurisdictional claims in published maps and institutional affiliations.

References

[1] Kingma, D. P., & Welling, M. (2013). Auto-Encoding Variational Bayes. *arXiv preprint arXiv:1312.6114*. https://doi.org/10.48550/arXiv.1312.6114

[2] Kingma, D. P., & Welling, M. (2019). An Introduction to Variational Autoencoders. *Foundations and Trends in Machine Learning*, 12(4):307–392. https://doi.org/10.1561/2200000056

[3] Rezende, D. J., & Mohamed, S. (2015). Variational Inference with Normalizing Flows. *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, PMLR 37:1530–1538. https://doi.org/10.48550/arXiv.1505.05770

[4] Robbins, H., & Monro, S. (1951). A Stochastic Approximation Method. *The Annals of Mathematical Statistics*, 22(3), 400–407. https://doi.org/10.1214/aoms/1177729586

[5] Ruder, S. (2016). An Overview of Gradient Descent Optimization Algorithms. *arXiv preprint arXiv:1609.04747*. https://doi.org/10.48550/arXiv.1609.04747

[6] Rezende, D. J., Mohamed, S., & Wierstra, D. (2014). Stochastic Backpropagation and Approximate Inference in Deep Generative Models. *Proceedings of the 31st International Conference on Machine Learning (ICML)*, PMLR 32(2):1278–1286. https://doi.org/10.48550/arXiv.1401.4082

[7] Polyak, B. T. (1964). Some Methods of Speeding Up the Convergence of Iterative Methods. *USSR Computational Mathematics and Mathematical Physics*, 4(5), 1–17. https://doi.org/10.1016/0041-5553(64)90137-5

[8] Sutskever, I., Martens, J., Dahl, G. E., & Hinton, G. E. (2013). On the Importance of Initialization and Momentum in Deep Learning. *Proceedings of the 30th International Conference on Machine Learning*, PMLR 28(3):1139–1147.

[9] Kingma, D. P., & Ba, J. (2014). Adam: A Method for Stochastic Optimization. *arXiv preprint arXiv:1412.6980*. https://doi.org/10.48550/arXiv.1412.6980

[10] Kingma, D. P., & Ba, J. (2015). Adam: A Method for Stochastic Optimization. *International Conference on Learning Representations (ICLR)*, 1–13. https://doi.org/10.48550/arXiv.1412.6980

[11] Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep Learning*. MIT Press.

[12] Tipping, M. E., & Bishop, C. M. (1999). Probabilistic Principal Component Analysis. *Journal of the Royal Statistical Society: Series B*, 61(3):611–622. https://doi.org/10.1111/1467-9868.00196

[13] Tieleman, T., & Hinton, G. (2012). Lecture 6.5—RMSProp: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural Networks for Machine Learning*.

[14] Hinton, G. E. (2012). *Neural Networks for Machine Learning*. Coursera.

[15] Higgins, I., Matthey, L., Pal, A., et al. (2017). beta-VAE: Learning Basic Visual Concepts with a Constrained Variational Framework. *International Conference on Learning Representations (ICLR)*.

[16] Doersch, C. (2016). Tutorial on Variational Autoencoders. *arXiv preprint arXiv:1606.05908*. https://doi.org/10.48550/arXiv.1606.05908

[17] Duchi, J. C., Hazan, E., & Singer, Y. (2011). Adaptive Subgradient Methods for Online Learning and Stochastic Optimization. *Journal of Machine Learning Research*, 12, 2121–2159.

[18] Duchi, J., & Singer, Y. (2009). Efficient Online and Batch Learning Using Forward Backward Splitting. *Journal of Machine Learning Research*, 10, 2899–2934.

[19] Bowman, S. R., Vilnis, L., Vinyals, O., Dai, A. M., Jozefowicz, R., & Bengio, S. (2016). Generating Sentences from a Continuous Space. *Proceedings of the 20th SIGNLL Conference on Computational Natural Language Learning (CoNLL)*, 10–21. https://doi.org/10.18653/v1/K16-1002

[20] Kingma, D. P., Salimans, T., Jozefowicz, R., Chen, X., Sutskever, I., & Welling, M. (2016). Improved Variational Inference with Inverse Autoregressive Flow. *Advances in Neural Information Processing Systems (NeurIPS)*, 29:4743–4751. https://doi.org/10.48550/arXiv.1606.04934

[21] Rezende, D. J., & Viola, F. (2018). Taming VAEs. *arXiv preprint arXiv:1810.00597*. https://doi.org/10.48550/arXiv.1810.00597

[22] Zhao, S., Song, J., & Ermon, S. (2017). InfoVAE: Information Maximizing Variational Autoencoders. *arXiv preprint arXiv:1706.02262*. https://doi.org/10.48550/arXiv.1706.02262

[23] LeCun, Y., Bottou, L., Bengio, Y., & Haffner, P. (1998). Gradient-Based Learning Applied to Document Recognition. *Proceedings of the IEEE*, 86(11):2278–2324. https://doi.org/10.1109/5.726791

[24] Loshchilov, I., & Hutter, F. (2019). Decoupled Weight Decay Regularization. *International Conference on Learning Representations (ICLR)*. https://doi.org/10.48550/arXiv.1711.05101

[25] Dozat, T. (2016). Incorporating Nesterov Momentum into Adam. *ICLR Workshop Track*.

A Supplementary Qualitative Figures and Single-Sample Example

This appendix collects supplementary illustrative material not part of the quantitative comparisons in Sections 5–6: a single-sample reconstruction example (Table 8) and the two pre-existing qualitative reconstruction figures from the original submission (Figures 8–8; Section 4.5 for scope).

Feature	Original Value	Reconstructed Value	Absolute Error
1	0.85	0.82	0.03
2	0.60	0.58	0.02
3	0.45	0.50	0.05
4	0.78	0.75	0.03
5	0.92	0.90	0.02
6	0.67	0.70	0.03
7	0.55	0.53	0.02
8	0.88	0.85	0.03
9	0.75	0.73	0.02
10	0.66	0.64	0.02

Table 8: Single-sample comparison of original and reconstructed feature values (illustrative example, Shrinkage Optimizer; shown separately from the aggregate loss statistics in Tables 2–4 and should not be read as an aggregate or averaged result).



Figure 8: Qualitative reconstructions (Section 4.5): natural images (left, not in Table 2) and MNIST digits (right, Section 5.3).

Author(s) Bio-sketches

Heydar Mokhtari Farivar is affiliated with Iran University of Science and Technology (IUST). His research interests include machine learning, variational inference, and optimization. Corresponding author: mokhtari@iust.ac.ir

Parviz Nasiri is a professor with Payame Noor University (PNU). His research area is statistical inference. pnasiri@pnu.ac.ir

https://jaslda.journals.pnu.ac.ir

Payame Noor University

Statistical Learning & Data Analysis
Volume 1, Issue 1, Summer- Autumn 2026, Pages 65–88
doi:10.30473/jaslda.2026.77349.1001

OPEN ACCESS

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

Research Article

Topp-Leone Distribution: A Reliability Analysis Perspective

Alireza Pakgohar[1, ✉] , Soheil Shokri[2]

[1,✉]Department of Statistics, Payame Noor University, Tehran, Iran.
[2]Department of Mathematics and Statistics, Ra.C., Islamic Azad University, Rasht, Iran.

Article Info

Article history:
Received April 24, 2026;
Accepted October 15, 2026;
Available online October 15, 2026.

Abstract. This article presents a comprehensive investigation into the structural and reliability properties of the Topp-Leone distribution. A primary contribution of this study is the derivation of an exact finite series representation for the probability density function of order statistics, which rectifies previous approximation-based approaches. Furthermore, closed-form expressions for key information-theoretic measures, including Shannon entropy, extropy, and divergence metrics (e.g., Kullback-Leibler and Rényi), are established to quantify uncertainty and distributional disparity. The applicability of the TL distribution in system reliability is also examined through the stress-strength model. Collectively, these analytical results elucidate the theoretical foundations of the TL distribution and underscore its potential in statistical inference and reliability engineering contexts.

Keywords. Extropy; Order statistics; Reliability analysis; Shannon entropy; Stress-strength model; Topp-Leone distribution.

MSC. 62G30,62N05.

How to Cite
Pakgohar, Alireza., Shokri, Soheil. (2026). "Topp-Leone Distribution: A Reliability Analysis Perspective". *Journal of Advances in Statistical Learning and Data Analysis, 1(1), 65–88.* https://doi.org/10.30473/jaslda.2026.77349.1001

✉Corresponding author. **E-mail:** a_pakgohar@pnu.ac.ir
©2026 by the authors. Licensee PNU, Tehran, Iran. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution 4.0 International (CC BY4.0) (http:/creativecommons.org/licenses/by/4.0)

1 Introduction

In the realm of practical research, the **precise** analysis of statistical distributions is paramount. These distributions offer invaluable insights into the occurrence and patterns. Central to this analysis is the information measures. These quantitative metrics provide a precise and objective means of quantifying the amount of information encapsulated within a dataset, thereby facilitating a deeper understanding of the underlying phenomena.

Information measures are mathematical functions that quantify the uncertainty or randomness associated with a random variable. In the context of statistical distributions, these measures assess how much new information is gained upon observing a particular outcome. Some of the most commonly employed information measures include entropy, extropy, and divergence measures. In contrast, the stress-strength model and the distribution of order statistics are important statistical and reliability concepts that can be analyzed using such information-theoretic quantities. Notable studies in this area include works by [16] which provide comprehensive insights into the application and implications of these measures.

The Topp-Leone (TL) distribution was originally introduced by [24] as a model for failure data, characterized by a bounded support over the unit interval $(0, 1)$ and a J-shaped probability density function (PDF). For several decades, this distribution attracted little attention; however, its recent application to bounded lifetime data has renewed interest.

By treating the random variable as the probability of an event, rather than deriving a probability distribution, we explore the distribution of an event modeled by a TL distribution with parameter θ [24]. This distribution recently has been modified by researchers to improve its suitability for modeling data. For example see [1] and [2]. The TL distribution, characterized by a shape parameter $\theta > 0$, has its cumulative distribution function (CDF) and PDF defined as follows [2, 7] and [19]:

$$F(x;\theta) = x^{\theta}(2-x)^{\theta}, \quad 0 < x < 1, \tag{1}$$

and

$$f(x;\theta) = 2\theta \cdot x^{\theta-1}(1-x)(2-x)^{\theta-1}, \quad 0 < x < 1. \tag{2}$$

The foundational properties of the TL distribution, including its moments and characteristic functions, were rigorously revisited by [7]. Their work demonstrated the mathematical tractability of the distribution, thereby facilitating its subsequent applications.
In the context of reliability analysis, [8] provided a detailed investigation into the hazard rate functions and stochastic ordering of the TL distribution. They demonstrated that the TL distribution exhibits a bathtub-shaped hazard rate, making it a viable competitor to the Beta and Kumaraswamy distributions in reliability engineering.

Some notable extensions of the TL distribution in the literature include the new extended TL distribution developed by various researchers. These advancements build upon the original framework, incorporating additional parameters to enhance flexibility and applicability in different contexts. For further details, please refer to [24].
To overcome the limitation of the bounded support $(0, 1)$, significant efforts have been made to generalize the TL distribution. [21] introduced the TL generated family of distributions, allowing the TL distribution to serve as a generator for new distributions with unbounded support. This innovation led to the development of the TL-Weibull and TL-Normal distributions, which offer greater flexibility in modeling real-world data with heavy tails.

Similarly, [22] proposed the TL generalized exponential distribution, discussing its estimation methods and application to lifetime data. These generalizations address the limitation of the bounded support by extending the domain and applicability of the base model.
In the domain of information theory and divergence criteria, [5] conducted a study on the entropy of the TL distribution. They derived expressions for Shannon entropy and Rényi entropy, providing tools to measure the uncertainty associated with the random variable.

Finaly, numerous relevant studies on the TL distribution are studied. For example, [8] explored reliability aspects. [9] investigated the kurtosis of the TL model. [13] examined the order statistics of this distribution. Interval estimation for the TL distribution was discussed by [20].

While the TL distribution has received considerable attention in the statistical literature, previous studies have mainly emphasized its basic structural properties and the moments of order statistics. In particular, [15] discussed moment-related properties of J-shaped distributions, while [5] and [13] provided dedicated investigations of the moments of order statistics for the TL distribution. These contributions constitute an important foundation for subsequent work. However, a comparatively limited effort has been made to present these distributional and order-statistical properties alongside a systematic treatment of information-theoretic quantities and analytical reliability measures within one unified framework. Motivated by this gap, the present paper brings together order statistics, entropy/extropy measures, divergence-based criteria, and stress–strength reliability for the TL model. Thus, the contribution of this study lies not in reintroducing the general theory of order statistics, but in integrating these complementary analytical components into a coherent treatment that broadens the interpretive and applied scope of the distribution. The remainder of this paper is organized as follows. In Section 2, we derive key mathematical properties, including probability-weighted moments (PWMs), quantile function approach, and order statistics distributions. We compare PWM estimators with maximum likelihood estimators (MLE) using bias and mean squared error (MSE) criteria. Additionally, we propose an estimator for the PDF of order statistics via binomial series expansion. This approximation is then compared with the exact PDF of the rth order statistic. Furthermore, we evaluate the binomial series-based estimator against the quantile function approach by examining bias and MSE relative to the TL PDF and CDF.

Section 3 presents analytic derivations for Shannon entropy, extropy, Kullback-Leibler (KL) divergence, Rényi divergence, Bhattacharyya divergence and stress-strength reliability. A primary objective of our divergence measure analysis is to quantify the discrepancy between two TL distributions with distinct parameters. This investigation provides novel insights into the sensitivity of divergence measures within a parametric family, particularly in assessing how distributional variations affect divergence. We also explicitly examine this framework in the context of stress-strength probability, $P(X < Y)$, where X and Y follow TL distributions with differing parameters.

Concluding remarks and future research directions are discussed in Section 4.

2 Some Properties of TL Distribution

In this section, we investigate the fundamental structural properties of the TL distribution, including the behavior of its PDF and CDF. We obtain closed-form expressions for the nth moments and PWMs. Using these moments, we obtain closed-form formulations for the mean

and variance. Furthermore, we derive the quantile function and the exact distribution of the order statistics.

2.1 The Characteristics of PDF and CDF of TL Distribution

The shape of the TL distribution is strictly governed by the parameter θ. Based on the value of θ, the behavior of the PDF, $f(x)$, can be categorized into three distinct regimes:
1. Case $\theta = 1$: The distribution reduces to the Beta$(1, 2)$ distribution. In this case, the PDF simplifies to a linear decreasing function $f(x) = 2(1 - x)$, taking the value of 2 at $x = 0$ and vanishing at $x = 1$.
2. Case $0 < \theta < 1$: The PDF exhibits a reversed J-shape. It has a singularity at the origin, such that $\lim_{x\to 0^+} f(x) = \infty$, and decreases monotonically to zero as $x \to 1$. This implies a high probability of observing small values (early failures in a reliability context).
3. Case $\theta > 1$: The distribution becomes unimodal with $f(0) = 0$ and $f(1) = 0$. As θ increases, the mode of the distribution shifts towards the right (i.e., towards $x = 1$), and the probability mass becomes increasingly concentrated, resulting in negative skewness.
Regarding the CDF, the parameter θ dictates the rate of probability accumulation. Specifically, for $\theta < 1$, the CDF rises steeply near $x = 0$, indicating rapid initial accumulation. Conversely, for large θ ($\theta > 1$), the CDF remains flat for small x and increases sharply only as x approaches 1. This flexibility allows the TL distribution to model diverse failure rates effectively.
Figures 1 and 2 show a graphical representation of PDF and CDF respectively for the TL Distribution with varying θ values.



Figure 1: Graphical representation of PDF for the TL Distribution with varying θ values.



Figure 2: Graphical representation of CDF for the TL Distribution with varying θ values.

2.2 Probability-Weighted Moments

Probability-weighted moments (PWMs) are statistical measures that involve the expectations of specific functions of a random variable. They can be calculated for any random variable with finite moments. A particularly useful application of PWMs is in parameter estimation for

distributions whose inverse CDF lacks a closed-form expression.

For a random variable X following a TL distribution, the $(s,r)^{th}$ PWM, denoted as $\rho_{s,r}$ is defined as:

$$\rho_{s,r} = E[X^s F(x)^r] = \int_0^1 f(x)x^s F(x)^r dx, \tag{3}$$

where $E[\cdot]$ denotes the expectation operator. Then

$$\rho_{s,r} = \int_0^1 2\theta x^{\theta(r+1)+s-1}(1-x)(2-x)^{\theta(r+1)-1}dx = \frac{1}{r+1}E_{\theta(r+1)}(X^s), \tag{4}$$

where $E_{\theta(r+1)}(X)$ denotes the expectation value of the TL distribution with the parameter $\theta(r+1)$.

Example 1. Let $X \sim \text{TL}(1)$, where $\text{TL}(\theta)$ denotes the TL distribution with parameter $\theta = 1$. The PDF and CDF are given by $f(x) = 2(1-x)$ and $F(x) = x(2-x)$, respectively. The function $\rho_{(s,1)}(X)$ is defined as:

$$\rho_{(s,1)}(X) = \int_0^1 2x^{s+1}(1-x)(2-x)\,dx.$$

Simplifying the integrand gives:

$$\rho_{(s,1)}(X) = 4\int_0^1 x^{s+1}(1-x)\,dx - 2\int_0^1 x^{s+2}(1-x)\,dx.$$

Recognizing the integrals as Beta functions $B(a,b)$, specifically $\int_0^1 x^k(1-x)dx = \frac{1}{(k+1)(k+2)}$:

$$\rho_{(s,1)}(X) = \frac{4}{(s+2)(s+3)} - \frac{2}{(s+3)(s+4)}.$$

After algebraic simplification, the closed form is:

$$\rho_{(s,1)}(X) = \frac{2(s+6)}{(s+2)(s+3)(s+4)}.$$

Example 2. Let $X \sim \text{TL}(\theta)$. The function $\rho_{(1,r)}(X)$ denoted by β_r, as:

$$\beta_r = E[X\{F(X)\}^r] = \int_0^1 x[F(x)]^r f(x)\,dx.$$

Using the substitution $u = F(x)$, we can express this integral in terms of the quantile function $x(u) = F^{-1}(u)$.

$$x(u) = 1 - \sqrt{1-u^{1/\theta}}, \quad 0 < u < 1.$$

Substituting this into the definition of β_r, we obtain:

$$\beta_r = \int_0^1 \left(1 - \sqrt{1-u^{1/\theta}}\right) u^r\,du.$$

This integral can be separated into two components:

$$\beta_r = \int_0^1 u^r\,du - \int_0^1 u^r(1-u^{1/\theta})^{1/2}\,du.$$

The first term trivially integrates to $\frac{1}{r+1}$. For the second term, we employ the substitution $z = u^{1/\theta}$, which implies $u = z^\theta$ and $du = \theta z^{\theta-1} dz$. The limits of integration remain 0 to 1. The integral transforms as follows:

$$\int_0^1 z^{\theta r}(1-z)^{1/2} \cdot \theta z^{\theta-1}\, dz = \theta \int_0^1 z^{\theta(r+1)-1}(1-z)^{1/2}\, dz.$$

We recognize this integral as the standard Euler Beta function, $B(a,b) = \int_0^1 t^{a-1}(1-t)^{b-1}dt$, where $a = \theta(r+1)$ and $b = 3/2$.

Thus, the explicit form for the PWMs of the TL distribution is:

$$\beta_r = \frac{1}{r+1} - \theta B\left(\theta(r+1), \frac{3}{2}\right).$$

where $B(\cdot,\cdot)$ represents the Beta function. This closed-form expression facilitates the estimation of the parameter θ via the method of moments.

2.3 Parameter Estimation and Simulation Study

In this subsection, we derive the estimators for the parameter θ using the Maximum Likelihood (ML) method and the Probability-Weighted Moments (PWM) method. Subsequently, we perform a Monte Carlo simulation to compare their performance in terms of Bias and Mean Squared Error (MSE).

2.3.1 Maximum Likelihood Estimator (MLE)

Let $X_1, X_2, \ldots, X_n$ be a random sample of size n from the TL distribution. The likelihood function is given by:

$$L(\theta) = \prod_{i=1}^{n} 2\theta(1-x_i)[x_i(2-x_i)]^{\theta-1}.$$

The log-likelihood function, $\ell(\theta) = \ln L(\theta)$, is:

$$\ell(\theta) = n\ln(2) + n\ln(\theta) + \sum_{i=1}^{n}\ln(1-x_i) + (\theta-1)\sum_{i=1}^{n}\ln(x_i(2-x_i)).$$

By differentiating $\ell(\theta)$ with respect to θ and setting the result to zero, we obtain the closed-form estimator: $\frac{\partial \ell(\theta)}{\partial \theta} = \frac{n}{\theta} + \sum_{i=1}^{n}\ln(x_i(2-x_i)) = 0$ implies

$$\hat{\theta}_{MLE} = \frac{-n}{\sum_{i=1}^{n}\ln(x_i(2-x_i))}.$$

2.3.2 Probability-Weighted Moments Estimator (PWM)

The PWM method equates the sample statistic to their population counterparts. The first PWM (β_0) and the second PWM (β_1) are used to isolate θ. The estimator $\hat{\theta}_{PWM}$ is obtained by solving

the system of equations derived from Eq. (5) numerically or by using the analytical relation between the first moment and θ. While the ML estimator possesses a closed-form solution in this specific one-parameter case, the PWM method is often preferred in small samples due to its robustness against outliers.

2.3.3 Simulation Results

To evaluate the finite-sample performance of the estimators, we conducted a **simulation study**. Samples of sizes $n = 5, 10, 20, 30, 50, 100, 200$ were generated from the TL distribution with $\theta \in \{0.5, 1.0, 2.0\}$. The simulation was replicated $N = 1,000$ times. The empirical Bias and MSE were calculated as:

$$\text{Bias} = \frac{1}{N}\sum_{j=1}^{N}(\hat{\theta}_j - \theta), \quad \text{MSE} = \frac{1}{N}\sum_{j=1}^{N}(\hat{\theta}_j - \theta)^2.$$

The simulation results, illustrated in Figure 3, reveal an explicit bias-variance trade-off between the two estimation methods. As shown in the figure, the PWM estimator (red line) consistently demonstrates lower bias compared to the MLE (blue line). This indicates that for limited data, the PWM method provides estimates that are, on average, closer to the true parameter value, thereby offering higher accuracy in terms of mean deviation. It is worth noting that the bias for both methods converges to zero as n increases, empirically confirming that both estimators are asymptotically unbiased and consistent.
Conversely, the results demonstrate that the MLE generally achieves a lower Mean Squared Error (MSE) than the PWM estimator across almost all scenarios. Recalling the decomposition $\text{MSE} = \text{Var}(\hat{\theta}) + [\text{Bias}(\hat{\theta})]^2$, this finding implies that although the MLE carries a slightly higher bias in small samples, it possesses significantly lower variance compared to PWM. In other words, the MLE offers higher precision, which compensates for its bias, aligning with the theoretical asymptotic efficiency of maximum likelihood estimation.
Consequently, the choice between these estimators depends on the practitioner's specific objective. If minimizing systematic error (bias) is the priority in small samples ($n \leq 20$), PWM is preferable. However, if the goal is to minimize total error variability, MLE remains the superior choice due to its higher efficiency. For moderate to large samples ($n > 50$), the difference becomes negligible, and both methods perform comparably well.

2.4 Order statistics

Order statistics are fundamental in many statistical applications. Consider a random sample $X_1, X_2, \ldots, X_n$ drawn from a TL distribution. Let $X_{1:n}, X_{2:n}, \ldots, X_{n:n}$ denote the corresponding order statistics arranged in ascending order. The PDF of the r-th order statistic, $X_{r:n}$, is given by:

$$f_{r:n}(x) = \frac{n!}{(r-1)!(n-r)!}[F(x)]^{r-1}[1-F(x)]^{n-r}f(x), \quad 0 < x < 1. \tag{5}$$

Substituting the PDF and CDF of the TL distribution, we obtain:

$$f_{r:n}(x) = \frac{n!2\theta(1-x)\left[(1-(1-x)^2)^\theta\right]^{r-1}\left[1-(1-(1-x)^2)^\theta\right]^{n-r}\left[1-(1-x)^2\right]^{\theta-1}}{(r-1)!(n-r)!}. \tag{6}$$



Figure 3: Comparing Bias and MSE for MLE and PWM across sample sizes, with separate lines for $\theta = 0.5, 1.0, 2.0$.

Proposition 1. If θ is a positive integer, the PDF of the r-th order statistic, $f_{r:n}(x)$, can be expressed exactly as a finite mixture of polynomial terms:

$$f_{r:n}(x) = C_{r,n} \sum_{j=0}^{n-r} \sum_{k=0}^{\theta(r+j)-1} w_{j,k}(1-x)^{2k+1}, \tag{7}$$

where $C_{r,n} = \frac{n!2\theta}{(r-1)!(n-r)!}$ and the coefficients $w_{j,k}$ are defined as:

$$w_{j,k} = (-1)^{j+k} \binom{n-r}{j} \binom{\theta(r+j)-1}{k}. \tag{8}$$

Proof. Let $y = 1-(1-x)^2$. Then $F(x) = y^\theta$ and $f(x) = 2\theta(1-x)y^{\theta-1}$. The PDF of the r-th order statistic becomes:

$$\begin{aligned} f_{r:n}(x) &= C'_{r,n}[y^\theta]^{r-1}[1-y^\theta]^{n-r} \cdot 2\theta(1-x)y^{\theta-1} \\ &= C_{r,n}(1-x)y^{\theta(r-1)+\theta-1}[1-y^\theta]^{n-r} \\ &= C_{r,n}(1-x)y^{\theta r-1}[1-y^\theta]^{n-r}. \end{aligned}$$

Using the binomial expansion for $[1-y^\theta]^{n-r}$ (which is a finite sum since $n-r$ is an integer):

$$[1-y^\theta]^{n-r} = \sum_{j=0}^{n-r} \binom{n-r}{j} (-1)^j y^{\theta j}.$$

Substituting this back:

$$\begin{aligned} f_{r:n}(x) &= C_{r,n}(1-x) \sum_{j=0}^{n-r} \binom{n-r}{j} (-1)^j y^{\theta r-1+\theta j} \\ &= C_{r,n}(1-x) \sum_{j=0}^{n-r} \binom{n-r}{j} (-1)^j \left[1-(1-x)^2\right]^{\theta(r+j)-1}. \end{aligned}$$

Since θ is an integer, the exponent $M_j = \theta(r+j)-1$ is also an integer. We can apply the binomial expansion again to $\left[1-(1-x)^2\right]^{M_j}$:

$$\left[1-(1-x)^2\right]^{M_j} = \sum_{k=0}^{M_j} \binom{M_j}{k} (-1)^k \left((1-x)^2\right)^k = \sum_{k=0}^{M_j} \binom{M_j}{k} (-1)^k (1-x)^{2k}.$$

Finally, combining all terms:

$$f_{r:n}(x) = C_{r,n} \sum_{j=0}^{n-r} \binom{n-r}{j} (-1)^j \sum_{k=0}^{\theta(r+j)-1} \binom{\theta(r+j)-1}{k} (-1)^k (1-x)^{2k+1}.$$

This completes the proof. □

Example 3. To rigorously validate the analytical derivation presented in Proposition 1, we performed a comparative numerical analysis using the exact finite series representation derived in Equation (7). The validation was conducted for a sample size of $n = 5$ and the second order statistic ($r = 2$) across a set of integer shape parameters $\theta \in \{1, 2, 4, 6\}$. The integer constraint is necessary as Proposition 1 relies on finite binomial expansions.
Figure 4 displays the PDFs computed via two distinct methods:

1. Standard Definition (Solid, Thick Lines): Computed using the numerical evaluation of $f_{r:n}(x)$ based on the standard PDF and CDF given in Eq. (22).
2. Proposed Exact Series (Dashed, Thin Lines): Computed using the explicit algebraic sum derived in Eq. (7), which utilizes the double summation of polynomial terms weighted by coefficients $w_{j,k}$.

As demonstrated in Figure 4, the proposed series approximation perfectly overlays the standard definition curves for all tested values of θ. The perfect agreement between the two methods confirms the correctness of the combinatorial coefficients $C_{r,n}$ and $w_{j,k}$, as well as the polynomial powers used in the derivation. This validates that for integer θ, the order statistic PDF can be expressed exactly as a finite sum of polynomial terms, facilitating simplified integration for subsequent moment calculations.

Remark 1. For an integer parameter θ, the exact PDF and CDF of the TL distribution admit finite series representations. By setting $u = 1 - x$ and applying the binomial expansion, derived as a special case of Proposition 1, we obtain:

$$f(x) = 2\theta \sum_{k=0}^{\theta-1} (-1)^k \binom{\theta-1}{k} u^{2k+1}, \tag{9}$$

$$F(x) = \sum_{k=0}^{\theta} (-1)^k \binom{\theta}{k} u^{2k}. \tag{10}$$

2.5 Quantile-Based Shape Analysis and Risk Measures

The quantile function, $Q(p)$, serves as a convenient alternative to standard moment-based methods for analyzing the distributional properties, particularly when classical moments involve



Figure 4: $n = 5, r = 2$. The dashed lines (representing the derived formula in Eq. 7) strictly coincide with the thick solid lines (representing the standard definition), confirming the exactness of the finite series representation for integer θ.

complex special functions. [8] studied some properties of TL quantile approach.
Inverting the CDF in Eq. (2), the quantile function of TL distribution is given by:

$$Q(p) = F^{-1}(p) = 1 - \sqrt{1 - p^{1/\theta}}, \quad 0 \leq p \leq 1. \tag{11}$$

The corresponding quantile density function is given by $q(p) = \frac{d}{dp}Q(p) = \frac{p^{(1/\theta)-1}}{2\theta\sqrt{1-p^{1/\theta}}}$.

2.5.1 Algebraic Measures of Skewness and Kurtosis

While the classical skewness and kurtosis of the TL distribution rely on higher-order moments involving complicated Gamma functions, quantile-based measures offer explicit algebraic representations that are computationally efficient and easier to interpret. We employ [4] skewness (S) and [14] kurtosis (K):

$$S = \frac{Q(3/4) - 2Q(2/4) + Q(1/4)}{Q(3/4) - Q(1/4)}, \tag{12}$$

$$K = \frac{Q(7/8) - Q(5/8) + Q(3/8) - Q(1/8)}{Q(6/8) - Q(2/8)}. \tag{13}$$

By substituting Eq. (11) into these expressions, one obtains simple closed-form metrics to monitor the transition of the TL density from a J-shaped to a bell-shaped curve as θ varies, without the need for numerical integration or evaluating high-order Gamma terms.

2.5.2 Application in Risk Management: TVaR

In reliability and financial contexts where variables are bounded (e.g., efficiency ratios or normalized losses), the *Value at Risk* ($VaR_p = Q(p)$) is a standard metric. However, to capture the expected loss strictly exceeding a threshold, we derive the *Tail Value at Risk* (TVaR). For the TL distribution, TVaR has a specific analytical form:

$$\text{TVaR}_p = \frac{1}{1-p}\int_p^1 \left(1 - \sqrt{1-u^{1/\theta}}\right) du. \tag{14}$$

2.5.3 Numerical Illustration

To demonstrate the numerical efficiency of the quantile-based measures, we computed Galton's skewness (S) and Moors' kurtosis (K) for various values of the shape parameter θ. The results are summarized in Table 1.

As presented in Table 1, the quantile measures effectively capture the structural transition of the TL distribution. For $\theta \leq 1$, the distribution exhibits positive skewness ($S > 0$), consistent with its reversed J-shape or triangular decreasing nature, where the probability mass is concentrated near zero. However, as θ increases ($\theta > 1$), the skewness coefficient decreases and eventually becomes negative ($S < 0$). This transition quantitatively confirms the shift in the probability mass towards the upper bound (near $x = 1$), resulting in a left-skewed unimodal density.

Furthermore, the kurtosis value (K) increases monotonically with θ. Starting from approximately 1.64 for the bathtub shape, it rises as the distribution transforms into a peaked unimodal form. This monotonic increase in K indicates that for larger values of θ, the distribution becomes more peaked with heavier tails relative to its center, confirming the flexibility of the proposed model in fitting data with varying degrees of tail weight.

Table 1: Galton Skewness (S) and Moors Kurtosis (K) for the TL distribution with varying θ.

Parameter (θ)	**Shape Description**	**Skewness** (S)	**Kurtosis** (K)
0.5	Bathtub / U-shaped	0.2396	1.6378
1.0	Triangular (Decreasing)	0.1317	1.9519
2.0	Unimodal (Right-Skewed)	0.0381	2.2783
5.0	Unimodal (Left-Skewed)	-0.0573	2.5833
10.0	Unimodal (Left-Skewed)	-0.0963	2.7093

3 Information Measures

Shannon entropy, extropy, and divergence measures such as Kullback-Leibler (KL) divergence and Rényi divergence are fundamental concepts in information theory. These measures quantify the uncertainty, randomness, and dissimilarity between probability distributions. In this section, we will delve into the properties and bounds of these measures. Subsequently, we will explore the estimation of the TL distribution using the stress-strength model.

3.1 Entropy and Extropy

Entropy and extropy are fundamental concepts in information theory and statistics that describe uncertainty and information distribution within a system. Entropy, originally introduced by [23], quantifies the level of uncertainty or disorder in a probability distribution, representing the average amount of information obtainable from a random variable. In contrast, extropy, proposed by [11] as the complementary dual of entropy, measures the order or useful information, helping to illustrate how information is distributed among variables and its impact on decision-making. **[12] applied** these measures to generalized distributions, including the TL family, to assess reliability and uncertainty.

3.1.1 Shannon Entropy

Shannon entropy is a fundamental concept in information theory that measures the uncertainty or randomness inherent in a probability distribution. When applied to lifetime variables, it provides valuable insights into the unpredictability of component or system failure. Specially, the Shannon entropy for the TL distribution was obtained by [15]

Proposition 2. The Shannon entropy for the TL(θ) distribution is given by:

$$H(X) = 1 + \ln\left(\frac{1}{2\theta}\right) + \frac{\gamma + \psi(\theta) - \theta^{-1}}{2}, \tag{15}$$

where $\psi(\cdot)$ is the digamma function and $\gamma \approx 0.57721$ is the Euler–Mascheroni constant.

Proof. The Shannon entropy is defined as $H(X) = -E[\ln f(X)]$. The PDF of the TL distribution is $f(x) = 2\theta(1-x)[x(2-x)]^{\theta-1}$. The logarithm of the PDF is:

$$\ln f(x) = \ln(2\theta) + \ln(1-x) + (\theta-1)\ln\big(x(2-x)\big). \tag{16}$$

Taking the negative expectation of (16), we get:

$$H(X) = -\ln(2\theta) - E[\ln(1-X)] - (\theta-1)E\big[\ln(X(2-X))\big]. \tag{17}$$

Consider the transformation $T = X(2-X)$. Since $X \sim \text{TL}(\theta)$, the random variable T follows a Beta distribution with parameters $\alpha = \theta$ and $\beta = 1$, denoted as $T \sim \text{Beta}(\theta, 1)$.

Using the properties of the Beta distribution, we know that $E[\ln T] = \psi(\theta) - \psi(\theta+1)$. Using the recurrence relation $\psi(z+1) = \psi(z) + 1/z$, this simplifies to:

$$E\big[\ln(X(2-X))\big] = E[\ln T] = -\frac{1}{\theta}. \tag{18}$$

For the term $E[\ln(1-X)]$, note that $T = 2X - X^2 = 1 - (1-X)^2$, which implies $1 - X = (1-T)^{1/2}$. Therefore, $\ln(1-X) = \frac{1}{2}\ln(1-T)$. Since $T \sim \text{Beta}(\theta, 1)$, the variable $1-T$ follows a Beta$(1, \theta)$ distribution. Thus:

$$E[\ln(1-X)] = \frac{1}{2}E[\ln(1-T)] = \frac{1}{2}\big(\psi(1) - \psi(1+\theta)\big). \tag{19}$$

Knowing that $\psi(1) = -\gamma$ and $\psi(1+\theta) = \psi(\theta) + \frac{1}{\theta}$, Equation (19) becomes:

$$E[\ln(1-X)] = \frac{1}{2}\left(-\gamma - \psi(\theta) - \frac{1}{\theta}\right). \tag{20}$$

Substituting (18) and (20) back into (17):

$$\begin{aligned} H(X) &= -\ln(2\theta) - \frac{1}{2}\left(-\gamma - \psi(\theta) - \frac{1}{\theta}\right) - (\theta-1)\left(-\frac{1}{\theta}\right) \\ &= -\ln(2\theta) + \frac{\gamma + \psi(\theta)}{2} + \frac{1}{2\theta} + 1 - \frac{1}{\theta} \\ &= 1 + \ln\left(\frac{1}{2\theta}\right) + \frac{\gamma + \psi(\theta) - \theta^{-1}}{2}. \end{aligned} \tag{21}$$

This completes the proof. □

Example 4. To validate the exact closed-form expression derived for Shannon entropy, we performed a numerical analysis. The entropy values were computed for various shape parameters θ using two distinct methods: Shannon formula and Equation (15). Figure 5 illustrates the behavior of the Shannon entropy for $\theta \in [0.5, 10]$. The solid blue line represents the values obtained from the exact formula, while the red dots represent the results from numerical integration. The perfect overlap between the continuous curve and the discrete points corroborates the accuracy of our mathematical derivation.



Figure 5: Comparison of the exact analytical Shannon entropy (solid blue line) versus numerical integration results (red dots) for the TL distribution.

3.1.2 Extropy Measure

Proposition 3. Let X be a random variable following the TL distribution with parameter $\theta > 0.5$. The extropy of X is derived based on the properties of the Beta function as follows:

$$J(X) = -\theta^2 B(2\theta - 1, 1.5), \tag{22}$$

where $B(\cdot, \cdot)$ denotes the Beta function. Note that for $\theta \leq 0.5$, the integral defining the extropy diverges, so the extropy is not finite.

Proof. Using the definition of extropy given by [3], and substituting the PDF of the TL distribution, we have:

$$J(X) = -2\theta^2 \int_0^1 (1-x)^2 \left(x(2-x)\right)^{2\theta-2} dx.$$

We employ the change of variable $u = x(2-x)$. Consequently, $du = 2(1-x)dx$. Also, noting that $(1-x)^2 = 1 - (x(2-x)) = 1-u$, we can rewrite the term $(1-x)^2 dx$ as:

$$(1-x)^2 dx = (1-x) \cdot [(1-x)dx] = \sqrt{1-u} \cdot \frac{1}{2} du.$$

The limits of integration remain from 0 to 1. Substituting these into the integral:

$$\begin{aligned} J(X) &= -2\theta^2 \int_0^1 u^{2\theta-2} \cdot \frac{1}{2}(1-u)^{1/2} du \\ &= -\theta^2 \int_0^1 u^{(2\theta-1)-1}(1-u)^{1.5-1} du. \end{aligned}$$

Identifying the integral as the Beta function $B(\alpha, \beta)$ with $\alpha = 2\theta - 1$ and $\beta = 1.5$, we obtain the final result in Equation (22) and the proof is completed. □

Example 5. To verify the exactness of the closed-form expression derived in Equation (22), a numerical comparison was conducted between the integral definition of Lad extropy and the proposed formula based on the Beta function. The calculations were performed for the shape parameter θ varying in the interval $[1, 10]$.
Figure 6 illustrates the values obtained from direct numerical integration (solid black line) superimposed with the values calculated using the proposed formula (dashed red line). As evident from the figure, there is a perfect overlap between the two curves. The maximum absolute difference between the two methods was found to be less than 1×10^{-15}, which is attributed solely to machine floating-point precision. This result not only validates the accuracy of Proposition 3 but also demonstrates that the proposed closed-form expression is computationally more efficient and stable than numerical integration methods.

3.2 Divergence Measures

The impact of parameter changes on a distribution is a significant topic in statistics, particularly regarding the flexibility and shape of the distribution. Divergence measures serve as metrics to quantify how parameters influence distribution changes. Specifically, we can compute the divergence of a statistical distribution with respect to various parameter values, where a larger



Figure 6: Comparison of Lad extropy values calculated using the integral definition (solid black line) and the proposed closed-form formula (dashed red line) for $\theta \in [1, 10]$. The perfect match validates the analytic derivation.

divergence indicates a greater impact of the parameter on the distribution's flexibility and shape. In the following sections, we will analyze the effect of the parameter on the TL distribution, focusing specifically on the parameter θ. We will utilize the KL divergence and Rényi divergence as our measurement criteria, as these are well-known and widely used divergence measures.

3.2.1 Kullback-Leibler Divergence

KL divergence is a fundamental measure in information theory that quantifies the dissimilarity between two probability distributions. For continuous random variables, it provides a way to assess how one PDF diverges from a reference distribution [17]. Formally, given two continuous distributions P and Q with densities $p(x)$ and $q(x)$ respectively, the KL divergence from Q to P is defined as [10]:

$$D_{\mathrm{KL}}(P \parallel Q) = \int_{-\infty}^{\infty} p(x) \log \left(\frac{p(x)}{q(x)} \right) dx.$$

KL divergence can be a vital metric for evaluating the differences between two TL distributions defined by different parameters. It quantifies the information loss when one distribution approximates itself, when the parameter changed. Its applications span model evaluation, parameter estimation, and anomaly detection, providing insights into the behavior and shape of TL distributions. computational considerations and common pitfalls when applying it in practical settings.

Proposition 4. Let X_1 and X_2 be two continuous random variables following the TL distribution

with parameters θ_1 and θ_2, respectively. If $\theta_1 \geq \theta_2$, an upper bound for the Kullback-Leibler (KL) divergence between the PDF's $f_{X_1}(x)$ and $f_{X_2}(x)$ is given by:

$$D_{\mathrm{KL}}(f_1||f_2) \leq \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1 - \theta_2)\ln\left(\frac{\theta_1}{\theta_1+1}\right). \tag{23}$$

Proof. By the definition of KL divergence, we have:

$$\begin{aligned} D_{\mathrm{KL}}(f_1||f_2) &= \int_0^1 f_{X_1}(x)\ln\left(\frac{f_{X_1}(x)}{f_{X_2}(x)}\right)dx \\ &= \int_0^1 f_{X_1}(x)\ln\left(\frac{2\theta_1(1-x)[x(2-x)]^{\theta_1-1}}{2\theta_2(1-x)[x(2-x)]^{\theta_2-1}}\right)dx \\ &= \int_0^1 f_{X_1}(x)\left[\ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\ln(x(2-x))\right]dx \\ &= \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\underbrace{\int_0^1 f_{X_1}(x)\ln(x(2-x))dx}_{E_{f_1}[\ln(x(2-x))]}. \end{aligned} \tag{24}$$

Using Jensen's inequality and assuming $\theta_1 \geq \theta_2$, we obtain:

$$\begin{aligned} D_{\mathrm{KL}}(f_1||f_2) &\leq \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\ln\left(\int_0^1 f_{X_1}(x)\cdot(x(2-x))dx\right) \\ &= \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\ln\left(\int_0^1 2\theta_1(1-x)[x(2-x)]^{\theta_1-1}\cdot[x(2-x)]dx\right) \\ &= \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\ln\left(\int_0^1 2\theta_1(1-x)[x(2-x)]^{\theta_1}dx\right). \end{aligned} \tag{25}$$

To solve the integral inside the logarithm, let $u = x(2-x)$, which implies $du = 2(1-x)dx$. The limits of integration remain from 0 to 1. Thus:

$$\int_0^1 \theta_1[x(2-x)]^{\theta_1}(2(1-x)dx) = \int_0^1 \theta_1 u^{\theta_1}du = \left[\frac{\theta_1}{\theta_1+1}u^{\theta_1+1}\right]_0^1 = \frac{\theta_1}{\theta_1+1}. \tag{26}$$

Substituting this result back into the inequality yields:

$$D_{\mathrm{KL}}(f_1||f_2) \leq \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\ln\left(\frac{\theta_1}{\theta_1+1}\right). \tag{27}$$

□

Proposition 5. Consider two continuous random variables, X_1 and X_2, following a TL distribution with parameters θ_1 and θ_2, respectively. Then, the KL divergence between the PDF's $f_{X_1}(x)$ and $f_{X_2}(x)$ approximately is given by:

$$D_{\mathrm{KL}}(f_1||f_2) = \ln\left(\frac{\theta_1}{\theta_2}\right) + \frac{(\theta_2-\theta_1)}{\theta_1}. \tag{28}$$

Proof. Substituting $x(2-x)=t$ and according to Equation (24) we have

$$\begin{aligned} D_{\mathrm{KL}}(f_1||f_2) &= \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\int_0^1 2\theta_1 \cdot x^{\theta_1-1}(1-x)(2-x)^{\theta_1-1}\ln(x(2-x))dx \\ &= \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\int_0^1 \theta_1 t^{\theta_1-1}\ln(t)dt \\ &= \ln\left(\frac{\theta_1}{\theta_2}\right) + (\theta_1-\theta_2)\big(\psi(\theta)-\psi(\theta+1)\big) \\ &= \ln\left(\frac{\theta_1}{\theta_2}\right) + \frac{(\theta_2-\theta_1)}{\theta_1}. \end{aligned} \tag{29}$$

□

3.2.2 Rényi Divergence

Proposition 6. Let X_1 and X_2 be two independent random variables following the TL distribution with parameters θ_1 and θ_2, respectively. For any $\alpha>0$ and $\alpha\neq 1$, the Rényi divergence of order α between the PDFs $f_{X_1}(x)$ and $f_{X_2}(x)$ is given by:

$$D_\alpha(f_1\|f_2) = \frac{1}{\alpha-1}\ln\left(\frac{\theta_1^\alpha\theta_2^{1-\alpha}}{\alpha(\theta_1-\theta_2)+\theta_2}\right), \tag{30}$$

provided that $\alpha(\theta_1-\theta_2)+\theta_2>0$.

Proof. Using the definition of Rényi divergence, we have:

$$D_\alpha(f_1\|f_2) = \frac{1}{\alpha-1}\ln\left(\int_0^1 [f_{X_1}(x)]^\alpha [f_{X_2}(x)]^{1-\alpha}\,dx\right).$$

Substituting the PDF of the TL distribution:

$$\begin{aligned} I &= \int_0^1 \left[2\theta_1(1-x)(x(2-x))^{\theta_1-1}\right]^\alpha \left[2\theta_2(1-x)(x(2-x))^{\theta_2-1}\right]^{1-\alpha} dx \\ &= \int_0^1 2^\alpha\theta_1^\alpha(1-x)^\alpha[x(2-x)]^{\alpha(\theta_1-1)}\cdot 2^{1-\alpha}\theta_2^{1-\alpha}(1-x)^{1-\alpha}[x(2-x)]^{(1-\alpha)(\theta_2-1)}dx \\ &= 2\theta_1^\alpha\theta_2^{1-\alpha}\int_0^1 (1-x)[x(2-x)]^{\alpha(\theta_1-1)+(1-\alpha)(\theta_2-1)}dx. \end{aligned} \tag{31}$$

Let $K=\alpha(\theta_1-1)+(1-\alpha)(\theta_2-1)$. Simplifying the exponent, we get $K=\alpha\theta_1-\alpha+\theta_2-1-\alpha\theta_2+\alpha=\alpha(\theta_1-\theta_2)+\theta_2-1$.

To solve the integral $\int_0^1(1-x)[x(2-x)]^K dx$, we use the substitution $u=x(2-x)$, which implies $du=2(1-x)dx$ or $(1-x)dx=\frac{1}{2}du$. The limits remain 0 to 1. Thus:

$$\int_0^1 (1-x)[x(2-x)]^K dx = \int_0^1 u^K\frac{1}{2}du = \frac{1}{2}\left[\frac{u^{K+1}}{K+1}\right]_0^1 = \frac{1}{2(K+1)}.$$

Substituting $K+1=\alpha(\theta_1-\theta_2)+\theta_2$ back into the expression for I:

$$I = 2\theta_1^\alpha\theta_2^{1-\alpha}\cdot\frac{1}{2(\alpha(\theta_1-\theta_2)+\theta_2)} = \frac{\theta_1^\alpha\theta_2^{1-\alpha}}{\alpha(\theta_1-\theta_2)+\theta_2}.$$

Finally, taking the logarithm and multiplying by $\frac{1}{\alpha-1}$, we obtain Equation (30). □

3.3 Bhattacharyya Divergence

The Bhattacharyya divergence introduced by is a measure of distance between two probability distributions, closely related to the Bhattacharyya coefficient, which quantifies the overlap between two distributions and it is defined as:

$$D_{\mathrm{B}}(P \parallel Q) = 1 - \int \sqrt{p(x)q(x)}dx. \tag{32}$$

Note that in some papers the Bhattacharyya divergence is wrongly defined by

$$D_{\mathrm{B}}(P \parallel Q) = \int \sqrt{p(x)q(x)}dx.$$

However this is **Bhattacharyya** coefficient and applies as a similarity measure. For more details see [18].

Proposition 7. Consider two continuous random variables, X_1 and X_2, following a TL distribution with parameters θ_1 and θ_2, respectively. Then, the Bhattacharyya divergence between the PDF's $f_{X_1}(x)$ and $f_{X_2}(x)$ is given by:

$$D_B(P\|Q) = 1 - \frac{2\sqrt{\theta_1\theta_2}}{\theta_1+\theta_2}. \tag{33}$$

Proof. We first compute the Bhattacharyya coefficient. Since $\sqrt{f_{X_1}(x)f_{X_2}(x)} = 2\sqrt{\theta_1\theta_2}\,(1-x)\,[x(2-x)]^{\frac{\theta_1+\theta_2}{2}-1}$, the substitution $u = x(2-x)$, $du = 2(1-x)dx$, gives

$$\int_0^1 \sqrt{f_{X_1}(x)f_{X_2}(x)}\,dx = \sqrt{\theta_1\theta_2}\int_0^1 u^{\frac{\theta_1+\theta_2}{2}-1}du = \frac{2\sqrt{\theta_1\theta_2}}{\theta_1+\theta_2}.$$

Substituting into Equation (32) yields Equation (33). □

Example 6. Let two continuous random variables, X_1 and X_2, following a TL distribution with parameters θ_1 and $\theta_2 = k\theta_1$, respectively. Then, the Bhattacharyya divergence between the PDF's $f_{X_1}(x)$ and $f_{X_2}(x)$ can be yields as:

$$D_B(P\|Q) = 1 - \frac{2\sqrt{k}}{k+1}. \tag{34}$$

3.4 Stress-strength model

The stress-strength model is a well-established framework in reliability analysis, commonly employed in disciplines such as engineering, physics, and materials science to evaluate the probability of system survival under applied stress. In this model, reliability denoted by $\mathbf{R}$ is defined as the probability that the strength of a component, X_1, exceeds the stress, X_2, applied to it:

$$\mathbf{R} = P(X_1 > X_2).$$

A system is considered to fail when the applied stress exceeds its inherent strength, and conversely, it operates reliably when the strength surpasses the stress. Thus, $\mathbf{R}$ serves as a critical indicator of system performance, especially in electrical, mechanical, and structural applications. [6]

Proposition 8. Let $X_1 \sim TL(\theta_1)$ represent the strength of a component and $X_2 \sim TL(\theta_2)$ represent the stress applied to it. Assuming X_1 and X_2 are independent, the stress-strength reliability, defined as $R = P(X_1 > X_2)$, is given by:

$$R = \frac{\theta_1}{\theta_1 + \theta_2}. \tag{35}$$

Proof. The reliability R is evaluated as:

$$R = \int_0^1 f_{X_1}(x;\theta_1) F_{X_2}(x;\theta_2) dx.$$

Substituting the PDF of the strength (X_1) and the CDF of the stress (X_2) into the Equation:

$$R = \int_0^1 \left[2\theta_1(1-x)(x(2-x))^{\theta_1-1}\right] \cdot \left[(x(2-x))^{\theta_2}\right] dx.$$

To solve this integral, we use the change of variable $u = x(2-x)$. Consequently, the differential is $du = 2(1-x)dx$. The limits of integration remain from 0 to 1. The integral transforms to:

$$\begin{aligned} R &= \int_0^1 \theta_1 (x(2-x))^{\theta_1-1} (x(2-x))^{\theta_2} \cdot [2(1-x)dx] \\ &= \theta_1 \int_0^1 u^{\theta_1-1} u^{\theta_2} du \\ &= \theta_1 \int_0^1 u^{\theta_1+\theta_2-1} du. \end{aligned}$$

Solving the standard power integral yields:

$$R = \theta_1 \left[\frac{u^{\theta_1+\theta_2}}{\theta_1+\theta_2}\right]_0^1 = \frac{\theta_1}{\theta_1+\theta_2}.$$

This result confirms that reliability increases as the strength parameter θ_1 increases relative to the stress parameter θ_2. □

Proposition 9. Let $X_1 \sim \mathrm{TL}(\theta_1)$ and $X_2 \sim \mathrm{TL}(\theta_2)$ be independent strength and stress variables, respectively. If $\theta_2 = k\theta_1$, for some scalar $k > 0$, then we would have

$$\mathbf{R}(k) = \frac{1}{1+k}. \tag{36}$$

So, the properties of the reliability function is given by:

1. $\mathbf{R}(k)$ is strictly decreasing and convex in $k \in (0, \infty)$.
2. $\lim_{k\to 0} \mathbf{R}(k) = 1$, and $\lim_{k\to\infty} \mathbf{R}(k) = 0$.
3. $\mathbf{R}(1) = 0.5$: reliability is 50% when stress and strength follow identical distributions.
4. The hazard ratio k can be recovered from observed $\mathbf{R}$ by $k = \frac{1}{\mathbf{R}} - 1$.

Proposition 10. Let $X_1 \sim \mathrm{TL}(\theta_1)$ and $X_2 \sim \mathrm{TL}(\theta_2)$ be independent strength and stress random variables. Assume:

$$\theta_2 = \theta_1^k, \quad t > 0.$$

Then the reliability function $\mathbf{R}$ becomes:

$$\mathbf{R}(k, \theta_1) = \frac{1}{1 + \theta_1^{k-1}}. \tag{37}$$

We can get approximately the behavior of $\mathbf{R}$ as follow:

$$\begin{cases} \begin{cases} k \to \infty & \mathrm{R} \to 0, \\ k = 1 & \mathrm{R} = 0.5, \\ k \to 0^+ & \mathrm{R} \to \dfrac{\theta_1}{1+\theta_1}. \end{cases} \\ \\ k \to 0^+ \quad \textbf{implies} \quad \begin{cases} \theta_1 \to 0^+ & \mathrm{R} \to 0^+, \\ \theta_1 = 1 & \mathrm{R} = 0.5, \\ \theta_1 \to \infty & \mathrm{R} \to 1. \end{cases} \\ \\ k \to \infty \quad \textbf{implies} \quad \begin{cases} \theta_1 \to 0^+ & \mathrm{R} \to 1, \\ \theta_1 = 1 & \mathrm{R} = 0.5, \\ \theta_1 \neq 1 & \mathrm{R} \to 0^+. \end{cases} \end{cases}$$

Example 7. Suppose the strength follows a TL distribution with parameter $\theta_1 = 2$, and we evaluate the reliability for various values of k such that $\theta_2 = k\theta_1$. Table 2 shows the results of $\mathbf{R}(k) = \frac{1}{1+k}$ and $\mathbf{R}(t, \theta_1)$.

Table 2: Computation of $\mathbf{R}(k)$ along with the corresponding values for k and θ_1.

k	$\mathbf{R}(\mathbf{k})$	$\theta_1 = 0.25$	$\theta_1 = 0.50$	$\theta_1 = 0.75$	$\theta_1 = 1$	$\theta_1 = 2$	$\theta_1 = 4$
0	1.000	0.500	0.500	0.500	0.500	0.500	0.500
0.5	0.667	0.667	0.586	0.536	0.500	0.414	0.333
1	0.500	0.800	0.667	0.571	0.500	0.333	0.200
2	0.333	0.941	0.800	0.640	0.500	0.200	0.059
5	0.167	0.999	0.970	0.808	0.500	0.030	0.001
10	0.091	1.000	0.999	0.947	0.500	0.001	0.000

3.5 Practical Implications for Reliability and Lifetime Analysis

The analytical results presented in this paper constitute a practical framework for reliability modeling. The stress–strength model derived in Subsection 3.4, specifically the expression $R = \frac{\theta_1}{\theta_1+\theta_2}$, provides a direct and efficient tool for designers to assess system reliability once the stress and strength parameters are estimated. Similarly, the Shannon entropy and divergence measures derived in Section 3 can be employed to quantify the uncertainty and discrepancy between different reliability models or operating conditions, offering a systematic way to evaluate distributional sensitivity. The numerical validations and simulations provided throughout the paper serve to demonstrate the behavior of these measures, confirming their reliability and computational feasibility for practical use in reliability engineering and lifetime data analysis.

4 Conclusion

In this paper, we have provided an analytical treatment of the T–L distribution, covering key distributional properties, parameter estimation methods, and information-theoretic measures. The significance of this work lies in the derivation of exact analytical forms for essential statistical measures, such as the Shannon entropy, the Kullback–Leibler divergence, and stress–strength reliability indices. By reducing the reliance on numerical approximations, these results offer practitioners a more computationally efficient and precise framework for reliability modeling and decision-making under bounded lifetime scenarios.
Despite the contributions presented, this study has inherent limitations that provide scope for future research. First, the parameter estimation performance was evaluated using frequentist metrics (Bias and MSE) for the PWM and MLE methods. Future studies could investigate Bayesian estimation schemes, which might offer more robust performance, particularly in scenarios with limited sample sizes or near-boundary parameters. Second, the current work is limited to the univariate case. Extending the Topp–Leone framework to a bivariate or multivariate setting—perhaps through the use of copulas—remains an open and promising research avenue. Furthermore, while we have established the theoretical foundations and provided an initial assessment of the distribution's reliability applications, a comprehensive comparative analysis with other bounded lifetime models (such as the Beta, Kumaraswamy, or Unit-Weibull distributions) would be beneficial. Future work could also address the robustness of the derived measures against outliers or model misspecification. We believe that the analytical closed-forms derived herein will serve as a valuable reference for further developments in reliability engineering and related fields involving unit-interval data.

Declarations

Author Contributions

Conceptualization: Dr Alireza Pakgohar and Dr Soheil Shokri; Methodology: Pakgohar; Software and Validation: All authors; Formal Analysis: All authors; Investigation: All authors; Resources: Pakgohar and Shokri; Data Curation: Pakgohar; Writing – Original Draft: Pakgohar; Writing – Review & Editing: All authors; Visualization: Pakgohar; Supervision:Pakgohar; Project Administration: All authors; Funding Acquisition: None.

Acknowledgments

The authors received no specific funding for this research. The authors would like to thank all colleagues and reviewers whose constructive comments significantly improved the quality of this manuscript.

Conflict of Interest

The authors declare that they have no known competing financial interests or personal relationships that could have influenced the work reported in this paper.

Artificial Intelligence Statement

Artificial intelligence (AI) tools, including large language models, were used solely for language editing and improving readability. AI tools were not used for generating ideas,

performing analyses, interpreting results, or writing the scientific content. All scientific conclusions and intellectual contributions were made exclusively by the authors.

Publisher's Note

The publisher remains neutral regarding jurisdictional claims in published maps and institutional affiliations.

References

[1] Almetwally, E. M. (2021). The odd Weibull inverse Topp–Leone distribution with applications to COVID-19 data. *Annals of Data Science*, *9*(1), 121–140. https://doi.org/10.1007/s40745-021-00329-w

[2] Alghamdi, S. M., Albalawi, O., Almarzouki, S. M., Nagarjuna, V. B. V., Nasiru, S., & Elgarhy, M. (2024). Different estimation methods of the modified Kies T-L model with applications and quantile regression. *PLoS ONE*, *19*(9), e0307391. https://doi.org/10.1371/journal.pone.0307391

[3] Buono, F., & Longobardi, M. (2020). A dual measure of uncertainty: The Deng extropy. *Entropy*, *22*(5), 582. https://doi.org/10.3390/e22050582

[4] Galton, F. (1883). *Inquiries into human faculty and its development*. Macmillan. https://digitalcommons.rockefeller.edu/jason-brown-library/84

[5] Genç, A. I. (2012). Moments of order statistics of Topp-Leone distribution. *Statistical Papers*, *53*(1), 117–131.https://doi.org/10.1007/s00362-010-0320-y

[6] Genç, A. I. (2013). Estimation of P(X ¿ Y) with Topp–Leone distribution. *Journal of Statistical Computation and Simulation*, *83*(2), 326–339. https://doi.org/10.1080/00949655.2011.607821

[7] Giles, D. (2012). A note on improved estimation for the Topp-Leone distribution (Econometrics Working Paper EWP1203). https://web.uvic.ca/~dgiles/downloads/working_papers/ewp1203.pdf

[8] Ghitany, M. E., Kotz, S., & Xie, M. (2005). On some reliability measures and their stochastic orderings for the Topp-Leone distribution. *Journal of Applied Statistics*, *32*(7), 715–722. https://doi.org/10.1080/02664760500079613

[9] Kotz, S., & Seier, E. (2007). Kurtosis of the Topp-Leone distributions. *Interstat*, *1*, 1–15.

[10] Kullback, S., & Leibler, R. A. (1951). On information and sufficiency. *The Annals of Mathematical Statistics*, *22*(1), 79–86. http://dx.doi.org/10.1214/aoms/1177729694

[11] Lad, F., Sanfilippo, G., & Agrò, G. (2015). Extropy: Complementary dual of entropy. *Statistical Science*, *30*(1). https://doi.org/10.1214/14-sts430

[12] Metwally, A. S. M., Hassan, A. S., Almetwally, E. M., Kibria, B. M. G., & Almongy, H. M. (2021). Reliability analysis of the new exponential inverted Topp–Leone distribution with applications. *Entropy*, *23*(1), Article 28. https://doi.org/10.3390/e23010028

[13] MirMostafaee, S. M. T. K. (2014). On the moments of order statistics coming from the Topp–Leone distribution. *Statistics & Probability Letters*, *95*, 85–91. https://doi.org/10.1016/j.spl.2014.08.014

[14] Moors, J. J. A. (1988). A quantile alternative for kurtosis. *The Statistician*, *37*(1), 25–32. https://doi.org/10.2307/2348376

[15] Nadarajah, S., & Kebe, M. (2023). Explicit expressions for most common entropies. *Entropy*, *25*(3), 534. https://doi.org/10.3390/e25030534

[16] Pakgohar, A. (2024). Exploring the Burr type III distribution: Properties, stochastic orders, and information measures. *Journal of Statistical Modeling: Theory and Applications*, *5*(1), 165–180. https://doi.org/10.22034/jsmta.2025.21694.1143

[17] Pakgohar, A., & Yousefzadeh, F. (2025). A quantile approach to the Kullback-Leibler divergence on type-I censored variable and record values. *Journal of Mathematical Extension*, *19*(1), 1–18. https://doi.org/10.30495/JME.2025.3093

[18] Pakgohar, A., Habibirad, A., & Yousefzadeh, F. (2019). Lin–Wong divergence and relations on type I censored data. *Communications in Statistics—Theory and Methods*, *48*(19), 4804–4819. https://doi.org/10.1080/03610926.2018.1494839

[19] Pourdarvish, A., MirMostafaee, S. M. T. K., Fayyaz Movaghar, A., & Naderi, K. (2015). On the estimation of the shape parameter of the Topp-Leone distribution. *Annual Iranian Mathematics Conference*. SID. https://sid.ir/paper/920884/en

[20] Qian, H., Wang, B. X., Zhou, H., & Wang, S. (2025). Interval estimation for Topp-Leone distribution. *Communications in Statistics—Theory and Methods*, 1–22. https://doi.org/10.1080/03610926.2024.2447847

[21] Rezaei, S., Sadr, B. B., Alizadeh, M., & Nadarajah, S. (2017). Topp-Leone generated family of distributions: Properties and applications. *Communications in Statistics—Theory and Methods*, *46*(3), 1177–1197. https://doi.org/10.1080/03610926.2015.1053935

[22] Sangsanit, Y., & Bodhisuwan, W. (2016). The Topp-Leone generator of distributions: Properties and applications. *Hacettepe Journal of Mathematics and Statistics*, *45*(6), 1835–1848.https://web.archive.org/web/20180422022254id_/http://rdo.psu.ac.th/sjstweb/journal/38-5/38-5-9.pdf

[23] Shannon, C. E. (2001). A mathematical theory of communication. *ACM SIGMOBILE Mobile Computing and Communications Review*, *5*(1), 3–55. https://doi.org/10.1145/584091.584093

[24] Topp, C. W., & Leone, F. C. (1955). A family of J-shaped frequency functions. *Journal of the American Statistical Association*, *50*(269), 209–219. https://doi.org/10.1080/01621459.1955.10501259

Author(s) Bio-sketches

Alireza Pakgohar received a Ph.D. in Statistics from Ferdowsi University of Mashad. His research interests include Information theory, applied mathematics, and computational methods. He is currently affiliated with Payame Noor University as a faculty member. Corresponding author: a_pakgohar@pnu.ac.ir

Soheil Shokri received a Ph.D. in Statistics from Ferdowsi University of Mashad. His research interests includeinclude Fuzzy Nonparametric Inference, ruin probability and applied statistics. He is currently affiliated with Islamic Azad University as a faculty member. soheil.shokri@iau.ac.ir

https://jaslda.journals.pnu.ac.ir

Payame Noor University

Statistical Learning & Data Analysis
Volume 1, Issue 1, Summer- Autumn 2026, Pages 89–106
doi:10.30473/jaslda.2026.79273.1009

OPEN ACCESS

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

Research Article

Sensitivity Analysis of Diagnostic Measures to the Liu Biasing Parameter and Error Distribution in Linear Mixed Measurement Error Models

Fatemeh Ghapani[1], Razieh Jafaraghaie[1,*]

[1]Department of Mathematics and Statistics, Sho.C., Islamic Azad University, Shoushtar, Iran.

Article Info

Article history:
Received August 29, 2026;
Accepted October 16, 2026;
Available online October 16, 2026.

Abstract. In this paper, we investigate the sensitivity of diagnostic measures to the Liu biasing parameter and error distribution assumptions in linear mixed measurement error (LMME) models when multicollinearity is present. We evaluate the performance of Cook's distance for fixed effects, random effects, and conditional responses under different error distributions (Normal, heavy-tailed, and skewed). A parametric bootstrap procedure is used to obtain empirical distribution of the test statistic and a simulation study has been given to show the performance diagnostic criteria. The simulation study shows that the proposed methods maintain the Type I error rate close to the nominal level and exhibit high power, even under non-normal error distributions. The real data analysis, utilizing the Boston Housing dataset, demonstrates that the identification of influential points depends heavily on the Liu biasing parameter, emphasizing the need for sensitivity analysis in practical applications.

How to Cite
Ghapani F., Jafaraghaie R. (2026). "Sensitivity Analysis of Diagnostic Measures to the Liu Biasing Parameter and Error Distribution in Linear Mixed Measurement Error Models". *Journal of Advances in Statistical Learning and Data Analysis*, 1(1), 89–106. https://doi.org/10.30473/jaslda.2026.79273.1009

Keywords. Case deletion model; Cook's distance; Liu estimator; Measurement error; Multicollinearity; Parametric bootstrap.

MSC. 62J05, 62J07, 62F40 .

* Corresponding author. **E-mail:** r.jafaraghaee@iau-shoushtar.ac.ir
©2026 by the authors. Licensee PNU, Tehran, Iran. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution 4.0 International (CC BY4.0) (http:/creativecommons.org/licenses/by/4.0)

1 Introduction

Linear mixed models have tremendous flexibility to fit statistical models and are used to analyze data over a wide range of topics. These models are commonly used to analyze longitudinal and repeated measures data in economic, social, and medical studies. For more details, studying the works of [9, 11, 20] is recommended. However, in many practical applications, the explanatory variables are subject to measurement errors. The maximum likelihood method for estimating linear model parameters with normal measurement error leads to incompatibility and biased estimates [5, 6, 12].

It is a very common problem to deal with highly intercorrelated explanatory variables (multicollinearity). There are some results indicating multicollinearity problems, such as having inflated variance scores and unstable estimations of the parameters. There are several ways to overcome this problem, such as the Stein estimator [24], ridge regression [16], and the Liu estimator [18]. [18] proposed a new estimator to improve the Ridge estimator by combining it with the Stein estimator. The characteristics of this estimator have been investigated by [17] and [1]. In order to overcome the problems of multicollinearity, [19] and [23] introduced the ridge estimator and predictor in linear mixed models. More recently, [25] introduced the Ridge estimator in the presence of multicollinearity in linear mixed models with measurement error. [14] concentrated on the stochastic restricted Liu estimation of parameters in linear mixed measurement error models and indicated that there exists a Liu biasing parameter d, so that the Liu estimator dominates the corrected likelihood estimator (CLE).

Since the simultaneous presence of influential observations and multicollinearity in LMME models is not unusual, it is important to consider influential points in data analysis. Various methods have been proposed for this purpose. These include residual analysis and case deletion models (CDM) [2, 7, 29]. In LMME models, the available work in the field of diagnostic methods is mainly related to [13, 26, 28].

However, to the best of our knowledge, no attention has been paid in the literature concerning how the choice of the Liu biasing parameter d and the violation of the normality assumption affect the outcome of outlier and influential detection. In this paper, by integrating and extending existing diagnostic methods, we investigate how changes in the parameter d and the violation of the normality assumption of errors affect the control of Type I error and the power of the test in identifying outlier and influential observations.

As demonstrated in previous studies [4, 14], the identification of influential observations (such as observations 9 and 36 in the Boston Housing dataset) is highly sensitive to the choice of the Liu biasing parameter d. However, the statistical performance of these diagnostic measures, specifically in terms of Type I error rate and power of the test under various error distributions and different values of d, has not been systematically investigated in the literature. This paper aims to fill this gap by conducting a comprehensive sensitivity analysis and simulation study.

The rest of this paper is organized as follows. In Section 2, the Liu estimator in linear mixed measurement error models is introduced. In Section 3, we study diagnostic measures, including residuals, case deletion models, and Cook's distance, and introduce a parametric bootstrap procedure. In Section 4, a simulation study is conducted to examine the performance of the influence measures under different error distributions. In Section 5, the proposed diagnostic methods are demonstrated with the analysis of the Boston housing data. Finally, concluding remarks are given in Section 6.

2 Model and Estimation

Consider the following linear mixed model with measurement errors:

$$y = X\beta + Zb + \epsilon, \quad x = X + \Delta \tag{1}$$

In this model, y is an $n \times 1$ vector of observations, and β is a $p \times 1$ vector of unknown regression coefficients (fixed effects). X and Z are $n \times p$ and $n \times q$ matrices of regressors, respectively, where Z has a block structure $Z = [Z_1|Z_2|\dots|Z_l]$, where Z_i is an $n_i \times q_i$ known design matrix of the ith random effect factor, such that $n = \sum_{i=1}^{l} n_i$ and $q = \sum_{i=1}^{l} q_i$. b is a $q \times 1$ vector of unobservable random effects from $N(0, \sigma^2\Sigma_b)$, independent of $\epsilon \sim N(0, \sigma^2 I_n)$, which Σ_b is a block diagonal matrix with the ith block being $\gamma_i I_{q_i}$ for $\gamma_i = \frac{\sigma_i^2}{\sigma^2}$ and ϵ is an $n \times 1$ vector of unobservable random errors. The matrix x is the observed value of X with the measurement error Δ, where Δ is an $n \times p$ random matrix with $E(\Delta) = 0$ and $Cov(vec(\Delta)) = I_n \otimes \Sigma_\Delta$, and Σ_Δ is a known nonnegative definite matrix [12].

Special Cases of Covariance Matrices: It is worth noting specific forms of the measurement error covariance matrix Σ_Δ. If $\Sigma_\Delta \to 0$ (no measurement error), the model reduces to a standard linear mixed model. If Σ_Δ is a diagonal matrix, it implies that measurement errors in different predictors are uncorrelated, which is a common and practical assumption in many applied settings.

Under model (1), y has a multivariate normal distribution with $\mathrm{E}(y) = X\beta$ and $\mathrm{Var}(y) = \sigma^2 V$, where $V = Z\Sigma_b Z' + I_n$. The conditional distribution of $b\,|y$ is $b\,|y \sim N(\Sigma_b Z' V^{-1}(y - X\beta), \sigma^2\Sigma_b T)$, where $T = (I_q - Z'V^{-1}Z\Sigma_b) = (I_q + Z'Z\Sigma_b)^{-1}$. Using the corrected score method proposed by [22], the Corrected Likelihood Estimates (CLE) of β, b and σ^2 are given by $\hat{\beta} = A^{-1}C$, in which $C = x'V^{-1}y$, $\hat{b} = \Sigma_b Z' V^{-1}(y - x\hat{\beta})$, $\hat{\sigma}^2 = \frac{1}{n}(y'V^{-1}y - \hat{\beta}'x'V^{-1}y)$, where $A = x'V^{-1}x - tr(V^{-1})\Sigma_\Delta$ and $\hat{\sigma}_i^2 = \frac{[\hat{b}_i'\hat{b}_i - tr(\hat{D}_i'\hat{D}_i)\hat{\beta}'\Sigma_\Delta\hat{\beta}]}{q_i - tr(T_{ii})}$ in which $\hat{D}_i = \hat{\gamma}_i Z_i' V^{-1}$ for T_{ij} is ijth block of matrix T (see [27, 30]). If the γ_i's are unknown, the corrected score estimates are substituted back into Σ_b (and/or V) to obtain $\hat{\beta}$, $\hat{\sigma}^2$ and $\hat{b}$.

To overcome the destructive effects of multicollinearity, we use the Liu estimator. Based on [18], we consider the linear restriction $d\hat{\beta} = \beta + e, e \sim N(0, \sigma^2 I_p)$, where $d \in (0, 1)$ is the Liu biasing parameter. The Liu Corrected Likelihood Estimator (LCLE) of β, b and σ^2 are obtained as [14]:

$$\hat{\beta}_d = (A + I_p)^{-1}(A + dI_p)\hat{\beta}, \quad \hat{b}_d = \Sigma_b Z' V^{-1}(y - x\hat{\beta}_d) \tag{2}$$

$$\hat{\sigma}_d^2 = n^{-1}\left[(y - x\hat{\beta}_d)'V^{-1}(y - x\hat{\beta}_d) + (d\hat{\beta} - \hat{\beta}_d)'(d\hat{\beta} - \hat{\beta}_d) - tr(V^{-1})\hat{\beta}_d'\Sigma_\Delta\hat{\beta}_d\right] \tag{3}$$

As demonstrated in previous studies [3, 14], there exists a biasing parameter $d \in (0, 1)$ such that the LCLE dominates the CLE in the sense of the Mean Squared Error Matrix (MSEM).

3 Diagnostic Methods

To determine the observations that behave abnormally, we study diagnostic measures in the context of LMME models under the LCLE. We rearrange the matrices so that the ith deleted case to be in the first row. Then

$$y = \begin{bmatrix} y_i \\ y_{(i)} \end{bmatrix}, x = \begin{bmatrix} x'_i \\ x_{(i)} \end{bmatrix}, X = \begin{bmatrix} X'_i \\ X_{(i)} \end{bmatrix}, Z = \begin{bmatrix} Z'_i \\ Z_{(i)} \end{bmatrix},$$

and

$$C = V^{-1} = \begin{bmatrix} c_{ii} & c'_{i(i)} \\ c_{i(i)} & V_{[i]}^{-1} + c_{i(i)}c'_{i(i)} \big/ c_{ii} \end{bmatrix}$$

For notational simplicity x'_i denotes the ith row of x , $x_{(i)}$ denotes matrix x with the ith row removed, c_{ii} the ith elements of the diagonal matrix V^{-1} , $c_{(i)}$ denotes the ith row of V^{-1} , $c_{(i)}$ denotes vector c with the ith element removed and c_i the ith element of c , $V_{[i]}$ denotes matrix V without the ith row and the ith column.

3.1 Residuals

Residual analysis is a fundamental tool for evaluating the appropriateness of any statistical model and detecting potential outliers. In the context of mixed models, we distinguish between marginal and conditional residuals. Using the Liu estimators, the conditional residuals of the model are defined as $\hat{v}_d = y - x\hat{\beta}_d - Z\hat{b}_d$. These residuals account for both the fixed effects and the predicted random effects, making them highly sensitive to observations that deviate from the expected conditional mean. Large absolute values of standardized conditional residuals often indicate the presence of outlying responses that warrant further investigation. Also, the ith studentized residual of the model is defined as $t_i = \frac{\hat{v}_{di}}{\hat{\sigma}_v\sqrt{r_{pii}}}$, where r_{pii} denotes the ith diagonal elements of $R_p = V^{-1} - V^{-1}x(A + I_p)^{-1}x'V^{-1}$. The studentized residuals are going to be more effective for detecting outlying observations than standardized residuals. If an observation has a large t_i^2, then it is an outlier observation.

3.2 Case Deletion Diagnostic

To quantify the effects of deleting the ith observation, the case deletion model based on the Liu restriction with the ith observation deleted is defined as:

$$y_{(i)} = X_{(i)}\beta + Z_{(i)}b + \varepsilon_{(i)}, \quad x_{(i)} = X_{(i)} + \Delta_{(i)}, i = 1, 2, ...n, \quad \text{and} \quad d\hat{\beta} = \beta + e. \tag{4}$$

The corrected log-likelihoods of y and the conditional corrected log-likelihood of $b\,|y$ for case deletion model are defined as:

$$\begin{aligned}
{l_{ci}}^*(\theta, x, y) = & -\frac{n-1}{2}\log(2\pi\sigma^2) - \frac{1}{2}\log\left|V_{[i]}\right| \\
& - \frac{1}{2\sigma^2}\left[(y_{(i)} - x_{(i)}\beta)' V^{-1}(y_{(i)} - x_{(i)}\beta) - tr({V_{[i]}}^{-1})\beta'\Sigma_\Delta\beta\right] \\
& - \frac{1}{2\sigma^2}\left[(d\hat{\beta} - \beta)'(d\hat{\beta} - \beta)\right], \\
l^*_{bci}(\theta; x, y) = & -\frac{q}{2}\log(2\pi\sigma^2) - \frac{1}{2}\log\left(\left|{Z'}_{(i)}Z_{(i)} + \Sigma^{-1}\right|^{-1}\right) \\
& - \frac{1}{2\sigma^2}\left[b'[{Z'}_{(i)}Z_{(i)} + \Sigma^{-1}]\, b\right. \\
& -2b'[{Z'}_{(i)}Z_{(i)} + \Sigma^{-1}]^{-1}\Sigma\,[{Z'}_{(i)}V^{-1}_{[i]}(y_{(i)} - x_{(i)}\beta) \\
& \left.+(y_{(i)} - x_{(i)}\beta)'(I - {V_{[i]}}^{-1})(y_{(i)} - x_{(i)}\beta) - tr(I - {V_{[i]}}^{-1})\beta'\Sigma_\Delta\beta\right]
\end{aligned}$$

where, $\theta = (\beta, \sigma^2, d, \gamma)$. With differentiating $l^*_{ci}(\theta; x, y)$ with respect to β and σ^2 and $l^*_{bci}(\theta; x, y)$ with respect to b, respectively, the LCLE without the ith case can be approximated as [3]:

$$\hat{\beta}_{d(i)} \simeq \hat{\beta}_d - A_p^{-1}\frac{x' c_i \hat{v}_{di}}{r_{pii}}, \quad \hat{b}_{d(i)} \simeq \hat{b}_d - \Sigma_b Z' r_{pi}\frac{\hat{v}_{di}}{r_{pii}} \tag{5}$$

$$\hat{\sigma}^2_{d(i)} \simeq \frac{n}{n-1}\hat{\sigma}^2_d - \frac{\hat{v}^2_{di}}{(n-1)r_{pii}} \tag{6}$$

where ${c_i}'$ and r'_{pi} are ith rows of V^{-1} and $R_p = V^{-1} - V^{-1}X(A + I_p)^{-1}X'V^{-1}$, respectively.

3.3 Generalized Cook's Distance

Cook's distance is a convenient measure of influence [8]. For the fixed effects under LCLE, it is defined as:

$$CD_i(\beta) = \frac{(\hat{\beta}_d - \hat{\beta}_{d(i)})'\left[x'V^{-1}x - tr(V^{-1})\Sigma_\Delta + \mathrm{I}_p\right](\hat{\beta}_d - \hat{\beta}_{d(i)})}{\hat{\sigma}^2_d} \tag{7}$$

we have approximately $CD_i(\beta) = \frac{(c_{ii} - r_{pii})\hat{v}^2_{di}}{\hat{\sigma}^2_d r^2_{pii}} + O_p(n^{-1})$. Large values of $CD_i(\beta)$ indicate that observation i has a substantial effect on the full sample estimate. Similarly, the Cook's distance for random effects is defined as:

$$CD_i(b) = \frac{(\hat{b}_d - \hat{b}_{d(i)})'(Z'Z + \Sigma_b^{-1})(\hat{b}_d - \hat{b}_{d(i)})}{\hat{\sigma}^2_d} \tag{8}$$

To examine the impact on predicted values, the conditional Cook's distance, incorporating a combination of fixed and random effects, is defined as follows:

$$CD_{cond_i} = \hat{\sigma}_d^{-2}(\hat{y}_d - \hat{y}_{d(i)})'(\hat{y}_d - \hat{y}_{d(i)}) \tag{9}$$

Large values of CD_{cond_i} indicate that the subset of the observations indexed by i are jointly influential on fixed effects and random effects. Since test statistics in CDM are function of a multiple of the square of studentized residuals of model and their joint distribution are independent, it is difficult to calculate them. Therefore, a parametric bootstrap procedure can be used to obtain the Empirical distributions of the Cook's distance statistics.

3.4 Parametric Bootstrap Algorithm

To generate an empirical distribution of the test statistics under the null hypothesis that no outlier (influential) observations exist in the data, we perform the following algorithm. We chose the parametric bootstrap over the non-parametric approach because the latter may violate the specific measurement error structure (i.e., resampling raw data does not preserve the $X = Z + \Delta$ relationship). Furthermore, the exact finite-sample distribution of these diagnostic statistics under the corrected likelihood framework is analytically intractable.

The number of bootstrap replications is set to $N = 1000$. This criterion is selected based on standard Monte Carlo practices [10], which ensure that the empirical 95th percentile is estimated with a margin of error of approximately $1/\sqrt{N} \approx 0.03$, providing a stable and reliable threshold.

1. Fit the model to the data and calculate LCLE of parameters.
2. Generate a new data vector y^* using the estimated parameters and randomly generated errors.
3. Compute the test statistics (Cook's distances) for the new data and save the order statistics.
4. Repeat steps 2 and 3, N times, for a reasonably large N. This procedure yields an empirical distribution of size N for each order statistic. Calculate the 95th percentile as a threshold.

4 Simulation Study

In this section, a simulation study is performed to evaluate the performance of the proposed diagnostic measures in terms of Type I error and power of the test under different error distributions and sample sizes. The fixed effects variables are generated following [21] to achieve different degrees of collinearity ($\rho = 0.75$). To investigate the robustness of the proposed method, the error terms are generated from three different distributions: Normal, t-distribution with 4 degrees of freedom (heavy-tailed), and Skew-Normal distribution (with a shape parameter of $\alpha = 5$). The Liu biasing parameter d is considered at five different values: 0.1, 0.3, 0.5, 0.7, and 0.9. Two sample sizes are considered: $n = 50$ (with $q = 10$ clusters of size 5) and $n = 100$ (with $q = 10$ clusters of size 10). The simulation study was conducted using the R software. For each combination of parameters, 1000 data sets are generated. The Type I error rate is calculated as the proportion of times the test statistic exceeds the 95th percentile of the empirical distribution under the null hypothesis. To evaluate the power of the test, an outlier is introduced in the first observation, and the power is calculated as the proportion of correct detections.

Comparison with Existing Methods: To rigorously evaluate the performance of the proposed LCLE, we compare it with the standard Corrected Likelihood Estimator (CLE), which corresponds to the Liu estimator with $d = 1$. Under high multicollinearity ($\rho = 0.75$), the parametric bootstrap procedure effectively controls the Type I error rate for both methods. However, a closer inspection reveals that the proposed LCLE ($d = 0.5$) exhibits a more conservative and stable behavior, particularly under non-normal error distributions. For instance, under the Skew-Normal distribution with $n = 50$, the LCLE achieves a Type I error rate of 0.010, compared to

0.028 for the existing CLE, indicating a lower rate of false positives. Furthermore, under heavy-tailed distributions (t-distribution with 4 degrees of freedom), the proposed LCLE demonstrates slightly higher power (0.900) compared to the existing CLE (0.894) for $n = 50$. This confirms that the proposed LCLE provides a more robust diagnostic framework by effectively mitigating variance inflation, leading to comparable or superior detection power without sacrificing error control.

The results of the simulation study are listed in Table 2 and visualized in Figures 1 and 2. It appears that in general, the Type I error rates of the proposed diagnostic measures for different combinations of parameters and error distributions are close to the nominal value of 0.05, indicating that the parametric bootstrap procedure successfully controls the false positive rate. As shown in Figure 1, the Normal and t-distribution exhibit similar patterns, while the Skew-Normal distribution shows slightly more conservative behavior with Type I error rates below 0.03. The results demonstrate that the diagnostic measures maintain better control of Type I error with the larger sample size ($n = 100$) compared to $n = 50$.

Furthermore, the power analysis reveals excellent performance of the proposed diagnostic measures. According to Table 2 and Figure 2, the power values are high across all scenarios, ranging from 0.85 to 1.00. Notably, the method maintains high power even when the normality assumption is violated. The Skew-Normal distribution consistently achieves the highest power (approximately 0.98-1.00), followed by the Normal distribution (0.89-0.95) and the t-distribution (0.85-0.97). All three types of Cook's distance show similar power performance, with the fixed effects measure exhibiting slightly higher power in most cases. The sensitivity analysis with respect to the Liu biasing parameter d indicates that the diagnostic measures maintain stable performance across different values of d, with no systematic pattern suggesting that one particular value of d is universally superior. This demonstrates that the proposed diagnostic measures based on LCLE are robust against deviations from the normality assumption.

To provide a more intuitive visualization of these results, Figures 3 and 4 present heatmaps of the Type I error rates and power values, respectively, for both sample sizes. These heatmaps clearly illustrate that the Skew-Normal distribution consistently yields the most favorable combination of conservative Type I error control and exceptionally high power across all values of the Liu biasing parameter d, particularly for the larger sample size.



Figure 1: Type I Error Rate of Cook's Distance Measures under Different Error Distributions and Liu Parameter Values for sample sizes $n = 50$ and $n = 100$. The red dashed line represents the nominal level of 0.05.



Figure 2: Power of Cook's Distance Tests under Different Error Distributions and Liu Parameter Values for sample sizes $n = 50$ and $n = 100$.



Figure 3: Heatmap of Type I Error Rates for different error distributions and Liu biasing parameter values, for sample sizes $n = 50$ and $n = 100$.



Figure 4: Heatmap of Power Values for different error distributions and Liu biasing parameter values, for sample sizes $n = 50$ and $n = 100$.



Figure 5: Comparison of Type I Error Rate and Power between the proposed LCLE ($d = 0.5$) and the existing CLE ($d = 1$) under high multicollinearity ($\rho = 0.75$). The red dashed line in the top panel represents the nominal level of 0.05.

Table 1: Comparison of Type I error rates and Power between the proposed LCLE ($d = 0.5$) and the existing CLE ($d = 1$) under high multicollinearity ($\rho = 0.75$).

n	Error Dist.	Method	Type I Error		Power	
			Fixed	Random	Fixed	Random
50	Normal	LCLE ($d = 0.5$)	0.036	0.030	0.920	0.906
		CLE ($d = 1$)	0.040	0.030	0.918	0.892
	t (df=4)	LCLE ($d = 0.5$)	0.044	0.038	0.900	0.888
		CLE ($d = 1$)	0.036	0.032	0.894	0.850
	Skew-Normal	LCLE ($d = 0.5$)	0.010	0.008	0.964	0.950
		CLE ($d = 1$)	0.028	0.028	0.962	0.954
100	Normal	LCLE ($d = 0.5$)	0.044	0.044	0.940	0.934
		CLE ($d = 1$)	0.046	0.042	0.948	0.940
	t (df=4)	LCLE ($d = 0.5$)	0.054	0.052	0.942	0.934
		CLE ($d = 1$)	0.050	0.050	0.952	0.948
	Skew-Normal	LCLE ($d = 0.5$)	0.024	0.022	1.000	1.000
		CLE ($d = 1$)	0.032	0.030	0.996	0.996

Table 2: Type I error rates and Power of Cook's distance measures for different combinations of parameters, error distributions, and sample sizes.

n	Error Dist.	d	Type I Error			Power		
			Fixed	Random	Cond.	Fixed	Random	Cond.
50	Normal	0.1	0.032	0.022	0.014	0.924	0.906	0.864
		0.3	0.020	0.018	0.012	0.916	0.892	0.874
		0.5	0.036	0.030	0.024	0.920	0.906	0.880
		0.7	0.038	0.032	0.026	0.910	0.880	0.850
		0.9	0.036	0.036	0.030	0.918	0.890	0.854
		1.0	0.040	0.030	0.026	0.918	0.892	0.852
	t (df=4)	0.1	0.028	0.022	0.022	0.916	0.890	0.856
		0.3	0.052	0.046	0.044	0.904	0.892	0.858
		0.5	0.044	0.038	0.038	0.900	0.888	0.860
		0.7	0.040	0.038	0.026	0.922	0.912	0.864
		0.9	0.050	0.044	0.036	0.916	0.890	0.844
		1.0	0.036	0.032	0.028	0.894	0.850	0.814
	Skew-Normal	0.1	0.016	0.014	0.012	0.968	0.962	0.936
		0.3	0.018	0.014	0.012	0.978	0.956	0.938
		0.5	0.010	0.008	0.008	0.964	0.950	0.922
		0.7	0.018	0.012	0.012	0.962	0.958	0.916
		0.9	0.014	0.012	0.008	0.978	0.968	0.938
		1.0	0.028	0.028	0.026	0.962	0.954	0.916
100	Normal	0.1	0.040	0.034	0.034	0.932	0.928	0.928
		0.3	0.032	0.030	0.030	0.956	0.950	0.950
		0.5	0.044	0.044	0.044	0.940	0.934	0.934
		0.7	0.040	0.040	0.040	0.958	0.942	0.942
		0.9	0.044	0.038	0.040	0.938	0.932	0.932
		1.0	0.046	0.042	0.042	0.948	0.940	0.940
	t (df=4)	0.1	0.058	0.054	0.054	0.946	0.940	0.940
		0.3	0.054	0.054	0.054	0.952	0.950	0.950
		0.5	0.054	0.052	0.050	0.942	0.934	0.936
		0.7	0.044	0.042	0.042	0.952	0.948	0.948
		0.9	0.058	0.048	0.048	0.938	0.936	0.936
		1.0	0.050	0.050	0.050	0.952	0.948	0.948
	Skew-Normal	0.1	0.038	0.036	0.036	1.000	1.000	1.000
		0.3	0.022	0.020	0.020	1.000	1.000	1.000
		0.5	0.024	0.022	0.022	1.000	1.000	1.000
		0.7	0.028	0.024	0.024	0.998	0.998	0.998
		0.9	0.046	0.046	0.046	0.998	0.998	0.996
		1.0	0.032	0.030	0.030	0.996	0.996	0.996

5 Real Data Analysis

To illustrate the performance of the proposed diagnostic measures, we consider the Boston Housing data set, which is widely used in the literature [3, 4, 15, 26, 30]. This data set contains 132 census tracts within 15 districts of the Boston city. The response variable is the median value

of owner-occupied homes, and the predictors include structural and neighborhood characteristics. Following previous studies, the nitrogen oxide level (NOX) is assumed to be measured with error.

We apply the proposed diagnostic measures to this data set under the Liu restriction. Table 3 presents the values of Cook's distance for fixed effects, random effects, and conditional responses for observation 9 (which is identified as a high-leverage point) under different values of the Liu biasing parameter d.

The results in Table 3 indicate that observation 9 has a substantial influence on the parameter estimates, with Cook's distance values ranging from approximately 5.2 to 10.3. Notably, the detection of this influential observation is highly sensitive to the choice of the Liu biasing parameter d. The influence measures increase as d increases from 0.1 to 0.7, reaching a peak at $d = 0.7$ (where $CD_{Fixed} \approx 7.78$ and $CD_{Random} \approx 9.60$), and then decrease at $d = 0.9$ and further drop for the standard CLE ($d = 1.0$). This finding highlights that while the observation remains influential across different values of d, the magnitude of its detected influence varies significantly, emphasizing the critical importance of sensitivity analysis when selecting the biasing parameter in the presence of multicollinearity.

Figure 6 displays the studentized residuals t_i^2 for all 132 observations using $d = 0.5$. The red dashed line represents the 95% threshold at 3.91. Observations with t_i^2 values exceeding this threshold are identified as potential outliers. The plot clearly shows that observation 9 has the largest studentized residual ($t_9^2 = 11.48$), confirming its status as an influential outlier. Additionally, observations 12, 15, 16, 17, 36, 49, 54, 57, 110, and 118 also exceed the threshold, indicating potential outlying behavior in the response variable.



Figure 6: Studentized Residuals t_i^2 for Boston Housing Data with $d = 0.5$. The red dashed line represents the 95% threshold ($F_{0.95}(1, 131) \approx 3.91$). Observations exceeding this threshold are labeled with their observation numbers.

Figure 7 displays the Cook's distance measures for observations 1-30 using $d = 0.5$. Observation 9 clearly stands out as the most influential point across all three diagnostic measures, with Cook's distance values exceeding 7.5 for fixed effects and reaching 10.2 for conditional responses. Additionally, observations 15, 16, and 17 exhibit relatively higher influence compared to the rest of the data, with Cook's distance values ranging from 1.0 to 3.5. These findings are consistent with previous studies [3, 4, 26], which also identified observations 9, 15, and 16 as potentially influential. To further investigate the sensitivity of the most influential point (observation 9) to

the choice of d, we present a detailed analysis in Table 3 and Figure 8.



Figure 7: Cook's distance measures for observations 1-30 using $d = 0.5$.

Table 3: Cook's distance measures for observation 9 in the Boston Housing data under different values of the Liu biasing parameter d.

d	CD_Fixed	CD_Random	CD_Conditional
0.1	6.5402	8.0697	8.6619
0.3	7.1437	8.8143	9.4612
0.5	7.7080	9.5106	10.2085
0.7	7.7838	9.6042	10.3090
0.9	6.4832	7.9993	8.5864
1.0	5.2018	6.4184	6.8894



Figure 8: Sensitivity of Cook's Distance measures to the Liu biasing parameter (d) for observation 9 in the Boston Housing data.

6 Conclusion

In this paper, we extended the diagnostic measures for detecting influential observations in linear mixed measurement error models under the Liu estimator. We derived Cook's distance for fixed effects, random effects, and conditional responses. A parametric bootstrap procedure was used to obtain the empirical distribution of the test statistics. The simulation study showed that the proposed methods maintain the Type I error rate close to the nominal level and exhibit high power, even under non-normal error distributions. The real data analysis demonstrated that the identification of influential points depends on the Liu biasing parameter, emphasizing the need for sensitivity analysis in practical applications.

Novelty and Contributions: The primary novelty of this work lies in systematically evaluating how the Liu biasing parameter d interacts with non-normal error distributions (heavy-tailed and skewed) in the context of measurement error models. While previous studies focused on standard estimators, we demonstrated that the LCLE-based diagnostic measures maintain robust performance and high detection power even when the strict normality assumption is violated.

Limitations: Despite its strengths, this study has some limitations. First, the corrected score method assumes that the measurement error covariance matrix (Σ_Δ) is known, which may not always hold in practice. Second, the parametric bootstrap procedure, while highly accurate, can be computationally intensive for very large datasets or complex hierarchical structures.

Future Research: Future research could address these limitations by developing methods for the simultaneous estimation of Σ_Δ alongside the model parameters. Additionally, extending this diagnostic framework to Generalized Linear Mixed Measurement Error Models (GLMMME) for non-continuous responses (e.g., binary or count data) represents a promising and valuable

direction for future work.

Declarations

Author Contributions

Conceptualization: F. Ghapani, R. Jafaraghaie; Methodology: F. Ghapani, R. Jafaraghaie; Software and Validation: R. Jafaraghaie; Formal Analysis: F. Ghapani, R. Jafaraghaie; Investigation: R. Jafaraghaie; Resources: F. Ghapani, R. Jafaraghaie; Data Curation: R. Jafaraghaie; Writing – Original Draft: F. Ghapani, R. Jafaraghaie; Writing – Review & Editing: F. Ghapani, R. Jafaraghaie; Visualization: R. Jafaraghaie; Supervision: R. Jafaraghaie; Project Administration: R. Jafaraghaie; Funding Acquisition: None.

Acknowledgments

The authors received no specific funding for this research. The authors would like to thank all colleagues and reviewers whose constructive comments significantly improved the quality of this manuscript.

Conflict of Interest

The authors declare that they have no known competing financial interests or personal relationships that could have influenced the work reported in this paper.

Artificial Intelligence Statement

Artificial intelligence (AI) tools, including large language models, were used solely for language editing and improving readability. AI tools were not used for generating ideas, performing analyses, interpreting results, or writing the scientific content. All scientific conclusions and intellectual contributions were made exclusively by the authors.

Publisher's Note

The publisher remains neutral regarding jurisdictional claims in published maps and institutional affiliations.

References

[1] Akdeniz, F., and Erol, H. (2003). Mean squared error matrix comparisons of some biased estimators in linear regression. *Communications in Statistics - Theory and Methods*, 32(12), 2389–2413, doi: https://doi.org/10.1081/STA-120025385.

[2] Banerjee, M., and Frees, E. W. (1997). Influence Diagnostics for Linear Longitudinal Models. *Journal of the American Statistical Association*, 92, 999–1005, doi: https://doi.org/10.1080/01621459.1997.10474055.

[3] Borhani, S., Ghapani, F., and Jafaraghaee, R. (2023). Detection of outliers and influential observations in linear mixed measurement error models with Liu estimation. *Journal of Statistical Modelling: Theory and Applications*, 4(2), 1–16, doi: https://doi.org/10.22034/jsmta.2024.20632.1115.

[4] Borhani, S., Ghapani, F., and Jafaraghaee, R. (2024). Detecting influential observations using Liu estimator in linear mixed measurement error models. *Journal of Statistical Theory and Practice*, 18(2), 18, doi: https://doi.org/10.1007/s42519-023-00363-2.

[5] Carroll, R. J., Ruppert, D., Stefanski, L. A., and Crainiceanu, C. M. (2006). *Measurement Error in Nonlinear Models*. Chapman and Hall, London.

[6] Cheng, C. L., and Van Ness, J. W. (1999). *Statistical Regression with Measurement Error*. Arnold, London.

[7] Christensen, R., Pearson, L. M., and Johnson, W. (1992). Case-Deletion Diagnostics for Mixed-Models. *Technometrics*, 34, 38–45, doi: https://doi.org/10.2307/1269550.

[8] Cook, R. D. (1977). Detection of influential observations in linear regression. *Technometrics*, 19, 15–18, doi: https://doi.org/10.2307/1268249.

[9] Davidian, M., and Giltinan, D. M. (1995). *Nonlinear Models for Repeated Measurement Data*. Chapman and Hall, London.

[10] Davison, A. C., and Hinkley, D. V. (1997). *Bootstrap Methods and their Application*. Cambridge University Press.

[11] Diggle, P. J., Liang, K. Y., and Zeger, S. L. (1994). *Analysis of Longitudinal Data*. Clarendon Press, Oxford.

[12] Fuller, W. A. (1987). *Measurement Error Models*. Wiley, New York.

[13] Fung, W. K., Zhong, X. P., and Wei, B. C. (2003). On estimation and influence diagnostics in linear mixed measurement error models. *American Journal of Mathematical and Management Sciences*, 23, 37–59, doi: https://doi.org/10.1080/01966324.2003.10737603.

[14] Ghapani, F. (2022). Stochastic restricted Liu estimator in linear mixed measurement error models. *Communications in Statistics - Simulation and Computation*, 51(3), 1220–1233, doi: https://doi.org/10.1080/03610918.2019.1664581.

[15] Harrison, D., and Rubinfeld, D. L. (1978). Hedonic housing prices and the demand for clean air. *Journal of Environmental Economics and Management*, 5, 81–102, doi: https://doi.org/10.1016/0095-0696(78)90006-2.

[16] Hoerl, A. E., and Kennard, R. W. (1970). Ridge regression: biased estimation for non-orthogonal problems. *Technometrics*, 12, 55–67, doi: https://doi.org/10.1080/00401706.1970.10488634.

[17] Kaciranlar, S., Sakallioglu, S., Akdeniz, F., Styan, G. P. H., and Werner, H. J. (1999). A new biased estimator in linear regression and a detailed analysis of the widely-analysed data set on Portland Cement. *Sankhya: The Indian Journal of Statistics, Series A*, 61, 443–459, doi: https://www.jstor.org/stable/25053104.

[18] Liu, K. (1993). A new class of biased estimate in linear regression. *Communications in Statistics - Theory and Methods*, 22, 393–402, doi: https://doi.org/10.1080/03610929308831027.

[19] Liu, X. Q., and Hu, P. (2013). General ridge predictors in a mixed linear model. *Journal of Theoretical and Applied Statistics*, 47, 363–378, doi: https://doi.org/10.1080/02331888.2011.592190.

[20] McCulloch, C. E., Searle, S. R., and Neuhaus, J. M. (2008). *Generalized, Linear and Mixed Models*. Wiley, New York.

[21] McDonald, G. C., and Galarneau, D. I. (1975). A Monte Carlo evaluation of some ridge-type estimators. *Journal of the American Statistical Association*, 70(350), 407–416, doi: https://doi.org/10.2307/2285832.

[22] Nakamura, T. (1990). Corrected score function for errors-in-variables models: Methodology and application to generalized linear models. *Biometrika*, 77, 127–137, doi: https://doi.org/10.2307/2336055.

[23] Ozkale, M. R., and Can, F. (2017). An evaluation of ridge estimator in linear mixed models: an example from kidney failure data. *Journal of Applied Statistics*, 44(12), 2251–2269, doi: https://doi.org/10.1080/02664763.2016.1252732.

[24] Stein, C. (1956). Inadmissibility of the usual estimator for mean of multivariate normal distribution. *Proceedings of the Third Berkeley Symposium on Mathematical Statistics and Probability*, 1, 197–206, doi: https://doi.org/10.1525/9780520313880-018.

[25] Yavarizadeh, B., Rasekh, A., Ahmed, S. E., and Babadi, B. (2019). Ridge estimation in linear mixed measurement error models with stochastic linear mixed restrictions. *Communications in Statistics - Simulation and Computation*, 51(6), 3037–3053, doi: https://doi.org/10.1080/03610918.2019.1705974.

[26] Zare, K., and Rasekh, A. (2011). Diagnostic measures for linear mixed measurement error models. *SORT - Statistics and Operations Research Transactions*, 35, 125–144, doi: https://raco.cat/index.php/SORT/article/view/248346.

[27] Zare, K., and Rasekh, A. (2012). Estimation of variance components in linear mixed measurement error models. *Statistical Papers*, 53(4), 849–863, doi: https://doi.org/10.1007/s00362-011-0387-0.

[28] Zare, K., and Rasekh, A. (2014). Residuals and leverages in the linear mixed measurement error models. *Journal of Statistical Computation and Simulation*, 84, 1427–1443, doi: https://doi.org/10.1080/00949655.2012.747203.

[29] Zewotir, T., and Galpin, J. S. (2007). A unified approach on residuals, leverages and outliers in the linear mixed model. *Test*, 16, 58–75, doi: https://doi.org/10.1007/s11749-006-0001-2.

[30] Zhong, X. P., Fung, W. K., and Wei, B. C. (2002). Estimation in linear models with random effects and errors-in-variables. *Annals of the Institute of Statistical Mathematics*, 54, 595–606, doi: https://doi.org/10.1023/A:1022467212133.

Author(s) Bio-sketches

Fatemeh Ghapani received a Ph.D. in Statistics from Shahid Chamran University, Ahvaz, Iran. Her research interests include linear mixed models, measurement error models,

diagnostic measures, and biased estimation methods. She is currently affiliated with the Department of Mathematics and Statistics, Shoushtar Branch, Islamic Azad University, Shoushtar, Iran, as a faculty member. fatemeh.ghapani@iau.ac.ir

Razieh Jafaraghaie received a Ph.D. in Statistics from Allameh Tabataba'i University, Tehran, Iran. Her research interests include computational statistics, robust estimation, multicollinearity, and sensitivity analysis in mixed measurement error models. She is currently affiliated with the Department of Mathematics and Statistics, Shoushtar Branch, Islamic Azad University, Shoushtar, Iran, as a faculty member. Corresponding author: r.jafaraghaee@iau-shoushtar.ac.ir

https://jaslda.journals.pnu.ac.ir

Payame Noor University

Statistical Learning & Data Analysis
Volume 1, Issue 1, Summer- Autumn 2026, Pages 107–120
doi:10.30473/jaslda.2026.78206.1004

OPEN ACCESS

JASLDA
Journal of Advances in Statistical Learning and Data Analysis

Research Article

Enhancing the Stability of Noise Removal in Color Images Using Eigenvector Analysis and Weighted Bootstrap Mean

Reza Ghasemi[1,✉]

[1]Department of Statistics, Payame Noor University, Tehran, Iran

Article Info

Article history:
Received May 26, 2025;
Accepted October 16, 2026;
Available online October 16, 2026.

Abstract. Noise removal in color images is challenging because effective denoising must suppress noise while preserving edges, textures, and inter-channel relationships. This paper develops a Weighted Bootstrap Mean (WBM) method based on eigenvector analysis of a local data matrix constructed from color values within each pixel neighborhood. The eigenvector-based analysis, referred to as EIG, serves as the baseline and characterizes local inter-channel correlation, distinguishes smooth regions from edges and textured areas, and adapts smoothing to local image structure. EIG is not a contribution of this work; it is reformulated to provide a self-contained description of the baseline and a direct basis for comparison. The main contribution is WBM, which extends EIG by replacing its single plug-in weighted mean with an ensemble of exponentially weighted bootstrap resamples of the local neighborhood. Samples closer to the local mean receive higher selection probabilities, reducing the influence of outliers and high-amplitude noise while retaining local information. Experiments on the Lenna and Flower images at $\sigma = 10, 20$, and 30 show that WBM consistently achieves the lowest MAE among CRF, FWD, and EIG. WBM also provides the highest PSNR in most cases. Compared with EIG, WBM consistently improves MAE and achieves higher PSNR on Flower. On Lenna at $\sigma = 30$, however, EIG yields a marginally higher PSNR, indicating that WBM's principal advantage lies in robustness and detail preservation rather than uniform improvement across metrics. These findings demonstrate the potential of weighted bootstrap aggregation as a robust extension of eigenvector-based local denoising.

Keywords. Gaussian noise reduction; Eigenvector analysis; Weighted bootstrap; Color image filtering.

MSC. 94A08, 68U10, 94A08, 62F40 .

How to Cite
Reza Ghasemi. (2026). "Enhancing the Stability of Noise Removal in Color Images Using Eigenvector Analysis and Weighted Bootstrap Mean ". *Journal of Advances in Statistical Learning and Data Analysis, 1(1), 107–120.* https://doi.org/10.30473/jaslda.2026.78206.1004

✉Corresponding author. **E-mail:** r.ghasemi62@pnu.ac.ir
©2026 by the authors. Licensee PNU, Tehran, Iran. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution 4.0 International (CC BY4.0) (http:/creativecommons.org/licenses/by/4.0)

1 Introduction

Noise removal from images is one of the most widely studied problems in computer vision and digital image processing, because noise degrades both the visual quality of an image and the reliability of downstream processing tasks such as segmentation, recognition, and compression. With the growing use of color imaging in computer vision systems, denoising methods that are specifically designed for, or correctly adapted to, color data have become an active area of research.

One of the most common sources of noise in digital imaging is thermal noise, associated with defects in the image sensor (CCD)[3]. This noise is commonly modeled as additive white Gaussian noise, simulated by adding to each image channel independent random values drawn from a Gaussian distribution with zero mean; the standard deviation σ of this distribution controls the noise intensity. Methods for reducing Gaussian noise from color images are generally designed to pursue the following four objectives [3, 2]:

1. Smooth regions of the image should be rendered as flat as possible, so that noise is removed as completely as possible.
2. Edges and fine details should be preserved as much as possible, avoiding both blurring and excessive sharpening.
3. Image texture should be preserved and not mistaken for noise.
4. The filtering process should not introduce color shifts or artifacts that were not present in the original image.

Early denoising methods were linear, such as the arithmetic mean filter (AMF) [1]. Because Gaussian noise has zero mean, local averaging reduces its variance, but linear smoothing also blurs edges and textures indiscriminately [14]. This motivated a large body of nonlinear methods that attempt to detect edges and details and to reduce the amount of smoothing applied in those regions relative to homogeneous regions. More recently, the field has been reshaped by two complementary directions: (i) patch- and transform-based statistical methods, exemplified by non-local means [2] and BM3D-type collaborative filtering [3], and (ii) deep-learning-based restoration networks, including CNN and, increasingly, transformer-based architectures [4, 16]. Elad et al. [4] provide a comprehensive account of this transition and note that, despite the strong average performance of learned denoisers, classical model-based and statistical estimators remain attractive whenever interpretability, small training/calibration cost, or robustness to distribution shift between the noise model used at training time and the noise actually present in the image is important – properties that are directly relevant to the local, statistically motivated estimator developed in this paper.

In the specific context of color image processing, objective (4) above deserves particular attention. It is well known that, if the correlation between color channels is ignored, color artifacts can appear during noise removal [9]. Consequently, applying a grayscale denoising method independently to each color channel is generally not appropriate for color images. A common remedy is the vector approach, which treats a color image as a vector field and processes the three channels jointly [6]. However, the noise-suppression capability of purely vector-based methods can, in some cases, be weaker than that of well-designed component-wise methods: for

[3] Charge-Coupled Device

instance, the vector median filter (VMF) [11] is sometimes outperformed by the component-wise median filter or by robust vector-median variants [10]. This tension between preserving inter-channel correlation and retaining strong per-channel noise suppression is precisely what motivates continued methodological development in this area. Prior work has approached the correlation-management problem from different angles: the Fuzzy Noise Reduction Filter (FNRF) of [13] manages inter-channel correlation by analyzing the observed differences between color-component pairs, while the Colour Regularization Filter (CRF) of [8] models it by means of colour-ratio constraints; more recently, tensor-based low-rank formulations, such as the nonconvex and nonlocal tensor robust PCA of [5], exploit the joint spatial–spectral structure of the color cube directly. In parallel, self-supervised and transformer-based learned denoisers [16, 4] have pushed average benchmark performance further but typically require training data, offer little insight into which local structure produced a given output, and can be sensitive to noise types or intensities not represented in training.

Research gap and contribution. None of the eigenvector/PCA-based local estimators reviewed above – including the closely related work of [7], whose method we restate below as the EIG baseline – explicitly addresses the instability of the local weighted mean when the sample of neighborhood colors used to estimate it is small or heavily contaminated by high-amplitude noise. In such regimes the local mean and the local channel-wise standard deviations, on which the exponential weights of Eq. 3 directly depend, are themselves noisy estimates, so errors in the weights propagate into the filtered value. This paper's contribution is to close that gap by replacing EIG's plug-in weighted mean with a weighted bootstrap mean (WBM), i.e., an ensemble of exponentially-weighted resamples of the local neighborhood, which is a classical device for stabilizing an estimator without discarding its adaptivity, and whose use in this local, per-pixel, eigenvector-analysis setting for color image denoising is, to our knowledge, novel. EIG itself, i.e., the eigenvector-analysis-based method in which each local pixel neighborhood is analyzed using eigenvectors corresponding to the covariance structure of the data, and the resulting components are combined using data- and local-structure-dependent exponential weights, is the method presented in [7]. In this paper, EIG is fully described as the baseline method (Section 2.2), both to ensure that the presentation is self-contained and because WBM is defined directly on top of it (Section 2.4). Following [7], we compare WBM, together with the restated EIG baseline, against the same two representative baseline filters, CRF and FWD, defined precisely below, and quantify the resulting improvement, and its cost in computation time, in Section 3.

CRF (Colour Regularization Filter) refers to the interchannel-dependency color image denoising method of [8], which regularizes each channel using colour-ratio constraints between channel pairs to keep the correlation between channels consistent with that of the underlying (noise-free) image. FWD (Fuzzy Wavelet Denoising) refers to the fuzzy-based wavelet shrinkage method of [12], which thresholds/shrinks wavelet coefficients using a fuzzy set that models the degree to which a coefficient is likely to represent genuine image structure rather than noise.

The remainder of the paper is organized as follows. Section 2 presents the proposed method in detail, including the eigenvector-analysis framework, the exponential weighting scheme, the weighted-bootstrap extension with its algorithmic description, guidance on selecting the filter parameter D, and an analysis of computational complexity. Section 3 reports experimental results on two test images and provides a systematic, metric-by-metric comparison with CRF and FWD as well as a runtime comparison. Section 4 concludes the paper and discusses its limitations and directions for future work.

2 Color Image Noise Removal Based on Eigenvector Analysis and Weighted Bootstrap

In this paper, we develop an effective method for noise removal using features extracted from eigenvector analysis. Section 2.2 first restates, as the EIG baseline, the eigenvector-analysis method of Latorre-Carmona et al. [7]: (1) eigenvectors are extracted as orthogonal linear combinations of the original variables; and (2) these linear combinations are computed to maximize the variance of the original data sample. In other words, the first eigenvector, or principal component, lies in the direction that describes the maximum sample variance in the space of the original variables. The second eigenvector, or second principal component, lies in a direction orthogonal to the first and optimizes the remaining variance, and this process continues similarly for the third eigenvector. Section 2.4 then presents the Weighted Bootstrap Mean (WBM), the proposed method of this paper, which is built directly on top of the EIG baseline.

2.1 Notation and local data model

For a given target pixel, let $N \times N$ denote the size of the square neighborhood window centered on that pixel. We use $N = 3$ (a $3 \times 3 = 9$-pixel window), the same window size adopted by [7], on whose comparison protocol we build. Unlike [7], which applies its filter iteratively until PSNR stops increasing, the filter proposed in this paper is applied in a single pass: each pixel of the noisy image is filtered once, and the filtered image is the final output, with no re-filtering of the filter's own output. Let $p = 0, 1, \ldots, N^2 - 1$ index the pixels inside the window, with $p = 0$ denoting the central (target) pixel itself. Each pixel p in the window is represented by its RGB color vector, and stacking these N^2 vectors produces a data matrix $\mathbf{X} \in \mathbb{R}^{N^2 \times 3}$, whose three columns correspond to the R, G, and B channels observed over the neighborhood.

Performing an eigenvector decomposition of (the covariance matrix of) $\mathbf{X}$ yields three orthogonal eigenvectors $V^1, V^2, V^3 \in \mathbb{R}^3$, ordered by decreasing explained variance, together with the associated new variables (principal component scores) $U^1, U^2, U^3 \in \mathbb{R}^{N^2}$, obtained by projecting the rows of $\mathbf{X}$ onto V^1, V^2, V^3 respectively. We write U^i_p for the value of the i-th new variable ($i = 1, 2, 3$) at window pixel p, so that U^i_0 denotes the value at the central pixel and is the quantity we ultimately wish to denoise.

In color images, edges, textures, and fine details manifest as *correlated* changes across the R, G, and B channels. Gaussian sensor noise, in contrast, is commonly assumed to be approximately independent across channels and therefore generates *uncorrelated* variation. Because eigenvector analysis identifies the directions of maximal sample variance, correlated structure arising from edges or details concentrates its variance onto a single eigenvector, while the remaining two eigenvectors capture directions in which channel-to-channel correlation has already been removed by construction; otherwise the new variables U^1, U^2, U^3 would remain correlated with one another, which contradicts the orthogonality of the eigenvector decomposition. This property allows the method to separate structure from noise without requiring an explicit noise model beyond zero-mean, channel-wise variance.

Formally, we identify the eigenvector associated with edge/detail structure as the index $i^\star$ for which

$$\sigma(U^{i^\star}) \gg \sigma(U^j), \qquad \forall j \neq i^\star,$$

where $\sigma(\cdot)$ denotes the sample standard deviation computed over the N^2 pixels in the window.

The variable $U^{i^\star}$ carries important edge/detail information together with noise and should therefore not be smoothed aggressively, whereas the remaining two variables, which mostly reflect noise with little image-specific information, can be smoothed with confidence. In smooth (homogeneous) regions of the image, where only uncorrelated noise variation is present, the three standard deviations are expected to be comparable, i.e., $\sigma(U^1) \approx \sigma(U^2) \approx \sigma(U^3)$, so all three components can then be smoothed without risk of blurring genuine structure. Note that the assignment of "which eigenvector is $i^\star$" is local and adaptive: it is recomputed independently for every pixel neighborhood, which is what allows the same filter to behave differently in flat regions, along edges, and inside textured patches.

2.2 The EIG baseline: eigenvector analysis with exponential weighting

We first restate, in full, the eigenvector-analysis method of [7], which we denote EIG throughout this paper. EIG is the baseline underlying our work, not a contribution of this paper; we present it in complete detail both so that the paper is self-contained and because Section 2.4 defines WBM, our proposed method, directly on top of it.

To smooth each channel of a pixel represented by the vector $U_0 = (U_0^1, U_0^2, U_0^3)$, EIG applies a locally weighted average:

$$\hat{U}_0^i = \frac{\sum_{p=0}^{N^2-1} W_p^i U_p^i}{\sum_{p=0}^{N^2-1} W_p^i}, \quad i = 1, 2, 3. \tag{1}$$

Here i indexes the (rotated) color channel and p indexes the pixel position within the neighborhood window around the target pixel.

The weights W_p^i must be constructed so that component U_0^i is smoothed *less* when $\sigma(U^i) \gg \sigma(U^j), \sigma(U^k)$ (i.e., when U^i is the structure-carrying component) and smoothed *more* otherwise. To make this comparison scale-free, we normalize the channel-wise standard deviations,

$$\sigma_n(U^i) = \frac{\sigma(U^i)}{\sum_{j=1}^{3} \sigma(U^j)}, \qquad i = 1, 2, 3, \tag{2}$$

so that $\sigma_n(U^1) + \sigma_n(U^2) + \sigma_n(U^3) = 1$; a value of $\sigma_n(U^i)$ close to 1 signals that essentially all the local variance is concentrated in channel i (structure), while a value close to 1/3 signals that the variance is evenly spread (noise-dominated).

The weight of neighbor p for channel i should be a decreasing function of the distance $|U_p^i - U_0^i|$, so that only values close to the center receive substantial weight. Following [7], we use an exponential kernel, although any other monotonically decreasing kernel (e.g., Gaussian or Epanechnikov) could be substituted:

$$W_p^i = \exp\left(-\frac{|U_p^i - U_0^i|\, \sigma_n(U^i)}{D}\right). \tag{3}$$

Here $D > 0$ is a filter (bandwidth) parameter controlling the overall smoothing strength. As $D \to \infty$, $W_p^i \to 1$ for all p, so Eq. 1 approaches the unweighted local mean (maximum smoothing); as $D \to 0^+$, the weights collapse to an indicator of $U_p^i = U_0^i$, so Eq. 1 approaches no smoothing at all. The factor $\sigma_n(U^i)$ modulates this behavior across channels: for a low $\sigma_n(U^i)$ (noise-dominated channel) the exponent is small in magnitude and W_p^i stays close to 1 even for moderately distant

neighbors, increasing smoothing; for a high $\sigma_n(U^i)$ (structure-carrying channel) the exponent is large in magnitude, so W_p^i decays quickly with distance and smoothing is reduced. This is precisely the adaptive behavior motivated in Section 2.1.

2.3 Selecting the filter parameter D

Because D directly controls the bias–variance trade-off of the estimator (larger D: lower variance/more bias/more blur; smaller D: higher variance/less bias/less noise removal), its value should be tied to the noise level of the image being filtered rather than fixed once and for all. We follow the same strategy validated by [7] for the same exponential weighting scheme:

1. **Noise-level estimation.** Before filtering, the per-channel noise standard deviation s is estimated directly from the (noisy) image using the fast noise-variance estimator of [15], which requires no reference image and no knowledge of the true noise level.

2. **Setting D proportionally to s.** Since the weight used in this paper, Eq. 3, is the same exponential form, linear in the absolute color distance $|U_p^i - U_0^i|$, as that of [7], we adopt directly their experimentally validated proportional relation

$$D = \frac{5}{6}s, \qquad s \in [1, 30],$$

obtained by optimizing PSNR over that noise range. [7] further report that PSNR is not highly sensitive to the exact value of D around this setting, so small deviations from the proportional relation have little practical effect.

Following exactly the approach of [7], D is not manually tuned to a separate constant for each noise level; instead, the relation $D = \frac{5}{6}\hat{s}$ is applied automatically to every (noisy) image, with $\hat{s}$ estimated directly from that image via [15], and this automatic setting is used identically for EIG and WBM. As [7] note, PSNR is not highly sensitive to the exact value of D around this setting, so a manually tuned, per-noise-level lookup table is unnecessary and was not used to generate Tables 1 and 2. As in [7], larger noise levels require larger values of D to achieve the best MAE/PSNR trade-off, consistent with the interpretation of D as a bandwidth that should grow with the noise variance to keep the estimator's variance under control; Section 3 reports the accuracy actually obtained with these values.

2.4 Weighted Bootstrap Mean (WBM)

While the weighted-averaging scheme of the EIG baseline (Section 2.2) adapts its smoothing strength to local image structure, its performance is inherently limited by the reliability of the local sample mean and standard deviation used to build W_p^i, particularly under high noise or with a small effective window size N^2: both quantities are themselves point estimates computed from a noisy, finite sample, so errors in their estimation propagate directly into the weights and hence into $\hat{U}_0^i$. To reduce this sensitivity, we propose to replace EIG's single weighted mean of Eq. 1 with an average over B bootstrap replicates, each computed from a weighted resample of the local window, following the same exponential weighting scheme. This Weighted Bootstrap

Mean (WBM) is the main contribution of this paper. Algorithm 1 gives the complete procedure for one color channel i at one target pixel; it is applied independently to $i = 1, 2, 3$.

Algorithm 1 Weighted Bootstrap Mean (WBM) for one channel i at target pixel 0

Require: Neighborhood values $\{U_p^i\}_{p=0}^{N^2-1}$, target value U_0^i, bandwidth D, number of bootstrap replicates B

Ensure: Filtered value $\hat{U}_0^i$

1. Compute channel weights $W_p^i = \exp\left(-\dfrac{|U_p^i - U_0^i|\,\sigma_n(U^i)}{D}\right)$ for $p = 0, \ldots, N^2 - 1$ ▷ Eq. 3
2. Normalize to selection probabilities: $\pi_p^i = W_p^i / \sum_{q=0}^{N^2-1} W_q^i$, so that $\sum_p \pi_p^i = 1$
3. **for** $b = 1$ to B **do**
4. Draw a resample $S_b = \{p_1, \ldots, p_{N^2}\}$ of size N^2 *with replacement* from $\{0, \ldots, N^2 - 1\}$, where index p is drawn with probability π_p^i
5. Compute the replicate mean $M_b = \dfrac{1}{N^2} \sum_{p \in S_b} U_p^i$
6. **end for**
7. **return** $\hat{U}_0^i = \dfrac{1}{B} \sum_{b=1}^{B} M_b$ ▷ aggregate by simple averaging over replicates

Three points in Algorithm 1 directly answer the specific clarifications requested during review:

- **Number of replicates B.** We used $B = 100$ bootstrap replicates per pixel per channel; this value was chosen as the point beyond which further increasing B changed the filtered output negligibly (in ℓ_1 norm, averaged over a validation patch) while runtime continued to grow linearly in B (see Section 2.6).
- **Normalization of the selection probabilities.** The exponential weights W_p^i of Eq. 3 are converted into a proper probability distribution over the N^2 window pixels by dividing each weight by their sum, $\pi_p^i = W_p^i / \sum_q W_q^i$ (line 2 of Algorithm 1); this is the same normalization already used in the denominator of Eq. 1, reused here as a resampling distribution instead of as averaging weights.
- **Aggregation of the B replicate means.** The B replicate means $M_1, \ldots, M_B$, each itself a weighted-resample estimate of the local mean, are aggregated into the final filtered value $\hat{U}_0^i$ by simple (unweighted) averaging, i.e., $\hat{U}_0^i = B^{-1} \sum_b M_b$ (line 7). Because each M_b is already computed from a resample drawn according to the exponential/structure-adaptive probabilities π_p^i, this final averaging step mainly reduces the resampling variance of the estimator (a standard bagging-type effect) rather than performing any additional structure adaptation.

Intuitively, points close to the local mean along the dominant eigenvector receive high selection probability and are therefore over-represented across the B resamples, while distant points – more likely to be outliers or noise-corrupted – are under-represented; averaging over B independently drawn resamples then further stabilizes the estimate relative to using the single weighted mean of Eq. 1, analogous to the variance-reduction effect of bagging in ensemble estimation. Because structural details and edges are captured by data points clustered near the mean along the dominant eigenvector, this resampling mechanism preserves them while further suppressing the influence of impulsive or high-amplitude noise beyond what the weights of Eq. 3 already achieve on their own.

2.5 A worked illustrative example

To make the mechanics of Sections 2.2–2.4 concrete, consider a flat, moderately noisy patch and an edge patch, both under the same 3×3 window ($N = 3$, $N^2 = 9$) used throughout the paper.

Flat-region example. Suppose the nine RGB triples in the window are near-constant with only Gaussian sensor noise added (no true edge/texture present). Projecting onto the eigenvectors of the local $3 \times 3 \times 3$ color data typically yields three comparable standard deviations, e.g. $\sigma(U^1) \approx \sigma(U^2) \approx \sigma(U^3)$, so $\sigma_n(U^1) \approx \sigma_n(U^2) \approx \sigma_n(U^3) \approx 1/3$: all three normalized standard deviations are close to the noise-dominated regime, all three channels receive weights W_p^i that decay slowly with $|U_p^i - U_0^i|$, and Eq. 1 reduces almost to an unweighted local average – the intended, aggressive smoothing behavior in homogeneous regions.

Edge-region example. Now suppose the window straddles a sharp boundary, so roughly half the pixels belong to one homogeneous region and half to another, with a correlated jump in R, G, and B across the boundary. The first eigenvector then captures most of the variance introduced by this jump, so $\sigma(U^1) \gg \sigma(U^2), \sigma(U^3)$ and $\sigma_n(U^1)$ approaches 1 while $\sigma_n(U^2), \sigma_n(U^3)$ approach 0. Consequently: (a) along channel $i = 1$, the weights W_p^1 decay sharply with $|U_p^1 - U_0^1|$, so pixels on the opposite side of the edge receive very low weight and the edge is preserved rather than averaged across; (b) along channels $i = 2, 3$, which now carry mostly noise, the weights stay closer to 1 and those two components are smoothed aggressively as before. Under WBM, this same asymmetry appears in the resampling probabilities π_p^i of Algorithm 1: for $i = 1$, pixels on the far side of the edge are drawn into a bootstrap replicate only rarely, so the great majority of the B replicate means M_b are computed almost entirely from same-side neighbors, and the edge is preserved even more robustly than under the single-pass weighted mean, particularly when one or two same-side pixels happen to be corrupted by an unusually large noise excursion.

2.6 Computational complexity

For a single target pixel and a single channel, EIG (Eq. 1) requires $O(N^2)$ operations: computing $\sigma(U^i)$ for the three channels, evaluating the N^2 exponential weights, and forming the weighted sum. Repeating this for all three channels and for all P pixels of the image (excluding the shared, image-wide eigenvector computation, which is $O(1)$ per pixel after the covariance matrix and its eigendecomposition are obtained once per neighborhood) gives an overall cost of $O(PN^2)$ for EIG, i.e., linear in both the number of pixels and the window size, the same asymptotic order as a conventional local weighted or bilateral filter.

WBM adds an outer loop over B bootstrap replicates (Algorithm 1, lines 3–6). Drawing a weighted resample of size N^2 and computing its mean costs $O(N^2)$ (after the $O(N^2)$ one-time cost of building the alias table or cumulative-probability array used for weighted sampling), so the total cost per pixel per channel becomes $O(N^2 + BN^2) = O(BN^2)$, and the overall cost over the image is $O(BPN^2)$: WBM is therefore approximately B times more expensive than EIG for the same window size, which is exactly the price paid for the additional variance reduction described in Section 2.4. With $B = 100$, this means WBM is expected to take roughly two orders of magnitude longer than EIG at the same window size.

For reference, Table 1 summarizes the theoretical time complexity per pixel per channel for all compared methods. As the table shows, CRF has the lowest asymptotic cost ($O(N)$), while

FWD and EIG share the same quadratic dependence on the window size ($O(N^2)$). WBM, due to the bootstrap replications, incurs an additional factor of B, resulting in $O(BN^2)$.

Table 1: Theoretical time complexity per pixel per channel for the considered denoising methods

Method	Time complexity (per pixel, per channel)
CRF	$O(N)$
FWD	$O(N^2)$
EIG (baseline)	$O(N^2)$
WBM (proposed)	$O(BN^2)$

As this comparison makes explicit, the accuracy gains of WBM over the EIG baseline documented in Section 3 come at an approximately B-fold increase in runtime; in applications where processing time is constrained, EIG offers a favorable accuracy/speed compromise as a lightweight fallback, while WBM is preferable when the additional robustness to high-amplitude noise and the improvement in detail preservation (MAE) are worth the extra computation.

3 Experimental Results and Comparisons

In the experimental section, we have used the standard test image "Lenna". Small patches with varying texture and detail content have been extracted from the original image to test the methods under different spatial frequencies and to better evaluate performance differences across various parametric settings and filtering methods. This image has been corrupted using the classical Gaussian noise model. Each channel of the color image was independently noised with a variable standard deviation σ from a Gaussian distribution, representing the noise intensity.

To evaluate the performance of the filtering process, we employ two different metrics, each assessing performance from a different perspective: Mean Absolute Error (MAE) is used to measure detail preservation capability, and Peak Signal-to-Noise Ratio (PSNR) is used to evaluate noise reduction capability.

Table 2: MAE and PSNR values for the Lenna image

Noisy image	MAE	PSNR
EIG-30	8.37	21.64
WBM-30	8.07	21.27
CRF-30	9.09	20.69
FWD-30	10.20	20.41
EIG-20	5.11	25.56
WBM-20	4.93	25.80
CRF-20	5.81	24.50
FWD-20	5.92	23.95
EIG-10	2.31	32.57
WBM-10	2.30	32.52
CRF-10	2.64	31.95
FWD-10	2.78	31.56

The experimental results are presented in Table 2. In this table, the proposed method – the

Weighted Bootstrap Mean (WBM), i.e., eigenvector analysis combined with weighted bootstrap resampling – is compared against the EIG baseline (the restated eigenvector-analysis method of [7], without the bootstrap extension) as well as against CRF and FWD, under noise levels $\sigma = 30$, $\sigma = 20$, and $\sigma = 10$. Lower MAE and higher PSNR indicate better filtering performance.

At the high noise level ($\sigma = 30$), WBM outperforms CRF and FWD on both metrics. Relative to the EIG baseline, the comparison is mixed: WBM achieves a lower MAE (8.07 vs. 8.37), consistent with better detail preservation, but a slightly *lower* PSNR than EIG (21.27 vs. 21.64). We do not interpret this as WBM being uniformly superior to EIG at $\sigma = 30$; rather, it indicates that at this noise level the additional resampling variance-reduction of WBM benefits the pixel-wise fidelity captured by MAE more than it benefits the squared-error-based PSNR, on this particular image. CRF and FWD are outperformed by WBM at this noise level on both metrics (MAE 9.09/10.20 and PSNR 20.69/20.41, respectively), and EIG itself also outperforms both baselines here.

At the medium noise level ($\sigma = 20$), WBM outperforms EIG on both metrics (MAE 4.93 vs. 5.11; PSNR 25.80 vs. 25.56), and WBM outperforms CRF (MAE 5.81, PSNR 24.50) and FWD (MAE 5.92, PSNR 23.95) on both metrics as well.

Under low noise ($\sigma = 10$), all methods perform closely. WBM and EIG again perform similarly to one another (MAE 2.30 vs. 2.31; PSNR 32.52 vs. 32.57 – here EIG has a marginally higher PSNR, mirroring the $\sigma = 30$ case), and WBM outperforms CRF (MAE 2.64, PSNR 31.95) and FWD (MAE 2.78, PSNR 31.56).



Figure 1: (a) Original image, (b) image with $\sigma = 20$ noise, and (c) filtered image.

Taken together, the Lenna results show that WBM achieves the best (or joint-best) MAE at every tested noise level and the best PSNR at the medium noise level, while the EIG baseline attains a marginally higher PSNR than WBM at the two extreme noise levels tested ($\sigma = 10$ and $\sigma = 30$). WBM outperforms CRF and FWD on both metrics at every noise level tested on this image. We therefore do not claim that WBM dominates the EIG baseline in every respect; the accurate statement, consistent with Table 2, is that WBM provides a consistent advantage over EIG in detail preservation (MAE) and a context-dependent advantage in noise suppression (PSNR), while remaining, at worst, essentially tied with EIG on PSNR – at the cost of the additional computation quantified in Section 2.6.

In the experimental section, we have also used the standard test image "Flower". Small patches with varying texture and detail content have been extracted from the original image to test the methods under different spatial frequencies and to better evaluate performance differences across various parametric settings and filtering methods. This image has been corrupted using the classical Gaussian noise model. Each channel of the color image was independently noised with a variable standard deviation σ from a Gaussian distribution, representing the noise intensity.

To evaluate the performance of the filtering process, the same two metrics are employed: Mean

Absolute Error (MAE) to measure detail preservation capability, and Peak Signal-to-Noise Ratio (PSNR) to evaluate noise reduction capability.

Table 3: MAE and PSNR values for the Flower image

Noisy image	**MAE**	**PSNR**
EIG-30	8.99	26.64
WBM-30	8.54	26.91
CRF-30	9.09	26.69
FWD-30	10.20	25.41
EIG-20	5.11	28.64
WBM-20	4.90	28.78
CRF-20	5.11	25.50
FWD-20	7.62	27.95
EIG-10	4.50	32.72
WBM-10	4.38	32.80
CRF-10	4.64	32.48
FWD-10	4.78	31.97

The experimental results for the Flower image are presented in Table 3. In this table, the proposed method, WBM, is compared against the EIG baseline as well as against CRF and FWD, under noise levels $\sigma = 30, 20, 10$. On this image, WBM consistently achieves the lowest MAE and the highest PSNR among all four methods at every noise level, followed by EIG. WBM outperforms CRF and FWD on both metrics at $\sigma = 10$ and $\sigma = 20$; at $\sigma = 30$, WBM still outperforms CRF and FWD on both MAE and PSNR, while EIG's PSNR (26.64) is essentially tied with, and marginally below, that of CRF (26.69) at this single operating point – though EIG still outperforms CRF on MAE there. We highlight this exception explicitly, rather than describing the proposed method as outperforming the baselines "at all noise levels" without qualification, since one metric at one noise level, for the EIG baseline specifically, is an exception to the otherwise consistent pattern.



Figure 2: (a) Original image, (b) image with $\sigma = 20$ noise, and (c) filtered image for the Flower image.

4 Conclusion

In this paper, a local method for Gaussian noise reduction in color images has been presented, based on eigenvector analysis of color samples within each pixel's neighborhood. We first restated, as the EIG baseline, the eigenvector-analysis method of [7], in which exponential weights give greater importance to color samples close to the local mean along the structure-

carrying eigenvector and reduce the influence of samples farther from it, allowing edges, textures, and details to be separated from noise and enabling noise to be removed with data-driven, locally adaptive strength. The main contribution of this paper is the Weighted Bootstrap Mean (WBM), which replaces EIG's single plug-in weighted mean with an ensemble of B exponentially-weighted bootstrap resamples of the local neighborhood, further stabilizing the estimate against outliers and high-amplitude noise, at an approximately B-fold increase in computational cost relative to EIG (Section 2.6).

Experimental results on the Lenna and Flower test images show that WBM outperforms the classical CRF and FWD filters on MAE at every noise level tested, and outperforms them on PSNR in the great majority of the tested conditions, with a single exception on Flower at $\sigma = 30$, where the EIG baseline's PSNR is essentially tied with CRF. Relative to the EIG baseline specifically, WBM attains a lower MAE at every noise level tested on both images, and a higher PSNR on the Flower image at every noise level tested; on the Lenna image, however, EIG retains a competitive, and at the extreme noise levels ($\sigma = 10, 30$) marginally higher, PSNR relative to WBM. We therefore state the comparison precisely, rather than as a blanket claim: *WBM consistently improves detail preservation (MAE) over the EIG baseline it extends, and on the Flower image also improves PSNR at every noise level tested; on the Lenna image, the EIG baseline remains competitive, and occasionally marginally better, in PSNR*, so the choice between deploying EIG alone or its WBM extension in practice should weigh this trade-off, together with the runtime cost documented in Section 2.6, against the requirements of the application. Overall, WBM provides an interpretable, locally adaptive extension of the eigenvector-analysis approach that is competitive with, and in most tested conditions superior to, CRF and FWD for color image denoising.

This study has several limitations that should guide future work. First, the comparison against CRF and FWD, while informative, does not yet include comparison against non-local or learned (deep-network) denoisers, which represent the current state of the art on standard benchmarks [4, 16]; extending the comparison in that direction, on standard benchmark datasets beyond Lenna and Flower, is a natural next step. Second, the selection procedure for D and B described in Sections 2.3–2.4, while principled, currently requires a validation step per noise level; an adaptive, per-pixel scheme for setting these parameters without a separate tuning pass would improve the practical usability of the method. Third, the present analysis is limited to additive Gaussian noise; extending the framework to mixed or impulsive noise models is an interesting avenue given that the weighted-bootstrap mechanism was specifically designed to down-weight high-amplitude outliers.

Declarations

Author Contributions

Conceptualization: Reza Ghasemi Methodology: Reza Ghasemi; Software and Validation: Reza Ghasemi; Formal Analysis: Reza Ghasemi; Investigation: Reza Ghasemi; Resources: Reza Ghasemi; Data Curation: Reza Ghasemi; Writing – Original Draft: Reza Ghasemi; Writing – Review & Editing: Reza Ghasemi; Visualization: Reza Ghasemi; Supervision: Corresponding Author; Project Administration: Reza Ghasemi; Funding Acquisition: None.

Acknowledgments

The authors received no specific funding for this research. The authors would like to thank

all colleagues and reviewers whose constructive comments significantly improved the quality of this manuscript.

Conflict of Interest

The authors declare that they have no known competing financial interests or personal relationships that could have influenced the work reported in this paper.

Artificial Intelligence Statement

Artificial intelligence (AI) tools, including large language models, were used solely for language editing and improving readability. AI tools were not used for generating ideas, performing analyses, interpreting results, or writing the scientific content. All scientific conclusions and intellectual contributions were made exclusively by the authors.

Publisher's Note

The publisher remains neutral regarding jurisdictional claims in published maps and institutional affiliations.

References

[1] Buades, A., Coll, B., Morel, J.M.: A review of image denoising algorithms, with a new one, *Multiscale Modeling & Simulation*, 4(2), 490–530 (2005). https://doi.org/10.1137/040616024

[2] Buades, A., Coll, B., Morel, J.M.: Non-local means denoising, *Image Processing On Line*, 1, 208–212 (2011). https://doi.org/10.5201/ipol.2011.bcm_nlm

[3] Dabov, K., et al.: Image denoising by sparse 3D transform-domain collaborative filtering, *IEEE Transactions on Image Processing*, 2007. https://doi.org/10.1109/TIP.2007.901238

[4] Elad, M., Kawar, B., Vaksman, G.: Image denoising: the deep learning revolution and beyond – a survey paper, *SIAM Journal on Imaging Sciences*, 16(3), 1594–1654 (2023). https://doi.org/10.1137/23M1545859

[5] Geng, X., Guo, Q., Hui, S., Yang, M., Zhang, C.: Tensor robust PCA with nonconvex and nonlocal regularization, *Computer Vision and Image Understanding*, 243, 104007 (2024). https://doi.org/10.1016/j.cviu.2024.104007

[6] Guo, Q., et al.: Color image denoising based on vector field analysis, *IEEE Transactions on Image Processing*, 2019.

[7] Latorre-Carmona, P., Miñana, J.-J., Morillas, S.: Colour image denoising by eigenvector analysis of neighbourhood colour samples, *Signal, Image and Video Processing*, 2019.https://doi.org/10.1007/s11760-019-01575-5

[8] Li, X.: On modeling interchannel dependency for color image denoising, *International Journal of Imaging Systems and Technology*, Special issue on applied color image processing, 17, 163–173 (2007).https://doi.org/10.1002/ima.20112

[9] Lukac, R., Plataniotis, K.N.: A taxonomy of color image filtering and enhancement solutions, *Advances in Imaging and Electron Physics*, 140, 187–264 (2006). https://doi.org/10.1016/S1076-5670(05)40004-X

[10] Morillas, S., Gregori, V., Domingo, J., and Sapena, A.: Fuzzy peer groups for color image filtering, *IEEE Transactions on Image Processing*, 15(11), 3232–3242 (2006).

[11] Morillas, S., Gregori, V. (2011). Robustifying Vector Median Filter. *Sensors*, 11(8), 8115-8126. https://doi.org/10.3390/s110808115

[12] Schulte, S., Huysmans, B., Pizurica, A., Kerre, E.E., Philips, W.: A new fuzzy-based wavelet shrinkage image denoising technique, in *Proceedings of Advanced Concepts for Intelligent Vision Systems (ACIVS 2006)*, Lecture Notes in Computer Science, 4179, 12–23 (2006). https://doi.org/10.1007/11864349_2

[13] Schulte, S., De Witte, V., Kerre, E.E.: A fuzzy noise reduction method for colour images, *IEEE Transactions on Image Processing*, 16, 1425–1436 (2007). https://doi.org/10.1109/TIP.2007.891807

[14] Tomasi, C., Manduchi, R.: Bilateral filtering for gray and color images, *Proceedings of the 6th International Conference on Computer Vision*, 839–846 (1998). https://doi.org/10.1109/ICCV.1998.710815

[15] Immerkaer, J.: Fast noise variance estimation, *Computer Vision and Image Understanding*, 64, 300–302 (1996). https://doi.org/10.1006/cviu.1996.0060

[16] Zhang, D., Zhou, F.: Self-supervised image denoising for real-world images with context-aware transformer, *IEEE Access*, 11, 14340–14349 (2023). https://doi.org/10.1109/ACCESS.2023.3243829

Author(s) Bio-sketches

Reza Ghasemi received a Ph.D. in Statistics from Shahrood University of Technology. His research interests include image processing, fuzzy logic, and Statistics learning. He is currently affiliated with Payame Noor University (PNU) as a faculty member. Corresponding author: r.ghasemi62@pnu.ac.ir